
Boost.Chrono 2.0.0

Howard Hinnant

Beman Dawes

Vicente J. Botet Escriba

Copyright © 2008 Howard Hinnant

Copyright © 2006, 2008 Beman Dawes

Copyright © 2009-2012 Vicente J. Botet Escriba

Distributed under the Boost Software License, Version 1.0. (See accompanying file LICENSE_1_0.txt or copy at http://www.boost.org/LICENSE_1_0.txt)

Table of Contents

| | |
|--|-----|
| Overview | 2 |
| Motivation | 2 |
| Description | 3 |
| User's Guide | 5 |
| Getting Started | 5 |
| Tutorial | 7 |
| Examples | 23 |
| External Resources | 36 |
| Reference | 37 |
| Header <boost/chrono/include.hpp> | 37 |
| Included on the C++11 Recommendation | 37 |
| Chrono I/O V1 | 63 |
| Chrono I/O V2 | 65 |
| Chrono Rounding Utilities | 104 |
| Other Clocks | 105 |
| Appendices | 111 |
| Appendix: History | 111 |
| Appendix: Rationale | 114 |
| Appendix: Implementation Notes | 115 |
| Appendix: FAQ | 115 |
| Appendix: Acknowledgements | 116 |
| Appendix: Future plans | 116 |

]

]

Overview

“What is time, then? If nobody asks me, I know; if I have to explain it to someone who has asked me, I do not know.”

-- Augustine

How to Use This Documentation

This documentation makes use of the following naming and formatting conventions.

- Code is in `fixed width font` and is syntax-highlighted.
- Replaceable text that you will need to supply is in *italics*.
- Free functions are rendered in the code font followed by `()`, as in `free_function()`.
- If a name refers to a class template, it is specified like this: `class_template<>`; that is, it is in code font and its name is followed by `<>` to indicate that it is a class template.
- If a name refers to a function-like macro, it is specified like this: `MACRO()`; that is, it is uppercase in code font and its name is followed by `()` to indicate that it is a function-like macro. Object-like macros appear without the trailing `()`.
- Names that refer to *concepts* in the generic programming sense are specified in CamelCase.



Note

In addition, notes such as this one specify non-essential information that provides additional background or rationale.

Finally, you can mentally add the following to any code fragments in this document:

```
// Include all of Chrono files
#include <boost/chrono.hpp>
```

Motivation

Time

We all deal with time every day of our lives. We've intuitively known it since birth. Thus we are all very familiar with it and believe it to be a simple matter. The modeling of time in computer programs should be similarly simple. The unfortunate truth is that this perceived simplicity is only skin deep. Fortunately, we do not need a terribly complicated solution to meet the bulk of our needs. However, overly simplistic solutions can be dangerous and inefficient, and won't adapt as the computer industry evolves.

Boost.Chrono implements the new time facilities in C++11, as proposed in [N2661 - A Foundation to Sleep On](#). That document provides background and motivation for key design decisions and is the source of a good deal of information in this documentation.

In addition to the clocks provided by the standard proposal, **Boost.Chrono** provides specific process and thread clocks.

Wall clock versus system and user time

To make the timing facilities of Boost.Chrono more generally useful, the library provides a number of clocks that are thin wrappers around the operating system's process time API, thereby allowing the extraction of wall clock time, user CPU time, and system CPU time of the process. Wall clock time is the sum of CPU time and system CPU time. (On POSIX-like systems, this relies on `times()`. On Windows, it relies on `GetProcessTimes()`.)

Description

The **Boost.Chrono** library provides:

Standard

- A means to represent time durations: managed by the generic `duration` class. Examples of time durations include `days`, `minutes`, `seconds` and `nanoseconds`, which can be represented with a fixed number of clock ticks per unit. All of these units of time duration are united with a generic interface by the `duration` facility.
- A type for representing points in time: `time_point`. A `time_point` represents an epoch plus or minus a `duration`. The library leaves epochs unspecified. A `time_point` is associated with a `clock`.
- Several clocks, some of which may not be available on a particular platform: `system_clock`, `steady_clock` and `high_resolution_clock`. A clock is a pairing of a `time_point` and `duration`, and a function which returns a `time_point` representing *now*.

Other clocks

To make the timing facilities more generally useful, **Boost.Chrono** provides a number of clocks that are thin wrappers around the operating system's time APIs, thereby allowing the extraction of wall clock time, user CPU time, system CPU time spent by the process,

- `process_real_cpu_clock`, captures wall clock CPU time spent by the current process.
- `process_user_cpu_clock`, captures user-CPU time spent by the current process.
- `process_system_cpu_clock`, captures system-CPU time spent by the current process.
- A tuple-like class `process_cpu_clock`, that captures real, user-CPU, and system-CPU process times together.
- A `thread_clock` thread steady clock giving the time spent by the current thread (when supported by a platform).

Lastly, **Boost.Chrono** includes `typedef` registration for `duration` and `time_point` to permit using emulated auto with C++03 compilers.

I/O

It provides I/O for `duration` and `time_point`. This I/O makes use of these types much more convenient. In following the "you only pay for what you use" philosophy, this extra functionality is located in a header separate from `<boost/chrono/chrono.hpp>`, namely `<boost/chrono/chrono_io.hpp>`.

It builds on `<boost/ratio/ratio_io.hpp>` to provide readable and flexible formatting and parsing for types in `<boost/chrono.hpp>`. This textual representation uses **SI prefixes** whenever possible. This makes it easy for `boost::milliseconds` to be represented by the text "milliseconds", or a hypothetical meter class to print out "millimeter". The `duration` and the `time_point` i/o can be customized through the new facets: `duration_units` and `__time_point_units`. The user can specialize these facets so that the the chrono i/o could be localizable. However Boost.Chrono doesn't provides a complete locale solution.

`system_clock::time_point` I/O is proposed in terms of UTC timepoints, strongly guided by ISO 9899:1999, Programming languages - C, ISO 9945:2003, Information Technology - Portable Operating System Interface (POSIX) and ISO 8601:2004, Data elements and interchange formats - Information interchange - Representation of dates and times.

Rounding utilities

A few simple rounding utility functions for working with durations.

Caveat Emptor

The underlying clocks provided by operating systems are subject to many seemingly arbitrary policies and implementation irregularities. That's a polite way of saying they tend to be flakey, and each operating system or even each clock has its own cruel and unusual forms of flakiness. Don't bet the farm on their accuracy, unless you have become deeply familiar with exactly what the specific operating system is guaranteeing, which is often very little.

User's Guide

Getting Started

Installing Chrono

Getting Boost.Chrono

Boost.Chrono is in the latest Boost release in the folder `/boost/chrono`. Documentation, tests and examples folder are at `boost/libs/chrono/`.

You can also access the latest (unstable?) state from the [Boost trunk](#) directories `boost/chrono` and `libs/chrono`. Just go to [here](#) and follow the instructions there for anonymous SVN access.

Where to install Boost.Chrono?

The simple way is to decompress (or checkout from SVN) the files in your `BOOST_ROOT` directory.

Building Boost.Chrono

Boost.Chrono can be configured as a header-only library defining `BOOST_CHRONO_HEADER_ONLY`. However **Boost.Chrono** depends on the non header-only library **Boost.System**, so that you will need to link with `boost_system`.

Boost.System has an undocumented feature (use of macro `BOOST_ERROR_CODE_HEADER_ONLY`) to make it header only, but it is buggy (see [#7347](#) duplicate symbol while `BOOST_ERROR_CODE_HEADER_ONLY` is defined)

If `BOOST_CHRONO_HEADER_ONLY` is not defined you need to compile it and build the library before use, for example using:

```
bjam libs/chrono/build
```

Requirements

In particular, **Boost.Chrono** depends on:

| | |
|-------------------------------|---|
| Boost.Config | for configuration purposes, ... |
| Boost.Exception | for <code>throw_exception</code> , ... |
| Boost.Integer | for <code>cstdint</code> conformance, ... |
| Boost.MPL | for <code>MPL Assert</code> and <code>bool</code> , logical ... |
| Boost.Operators | for operators, ... |
| Boost.Ratio | for <code>ratio</code> , <code>milli</code> , <code>micro</code> , ... |
| Boost.System | for <code>error_code</code> , ... |
| Boost.TypeTraits | for <code>is_base</code> , <code>is_convertible</code> , <code>common_type</code> , ... |
| Boost.Utility/EnableIf | for <code>enable_if</code> , ... |

Building an Executable that Uses Boost.Chrono

In addition to link with the **Boost.Chrono** library you need also to link with the **Boost.System** library. If **Boost.System** is configured defining `BOOST_ERROR_CODE_HEADER_ONLY` you will no need to link with it as the dependent part is header only then.

Exception safety

All functions in the library are exception-neutral and provide strong guarantee of exception safety as long as the underlying parameters provide it.

Thread safety

All functions in the library are thread-unsafe except when noted explicitly.

As Boost.Chrono doesn't use mutable global variables the thread-safety analysis is limited to the access to each instance variable. It is not thread safe to use a function that modifies the access to a user variable if another can be reading or writing it.

Tested compilers

The implementation will eventually work with most C++03 conforming compilers. Currently I use to test with on:

Windows with

- MSVC 10.0

MinGW with

- GCC 4.5.0
- GCC 4.5.0 -std=c++0x
- GCC 4.5.2
- GCC 4.5.2 -std=c++0x
- GCC 4.6.0
- GCC 4.6.0 -std=c++0x

Ubuntu with * GCC 4.4.6 * GCC 4.4.6 -std=c++0x * GCC 4.5.4 * GCC 4.5.4 -std=c++0x * GCC 4.6.1 * GCC 4.6.1 -std=c++0x * Intel 12.1.3 * Intel 12.1.3 -std=c++0x

OsX with

- GCC 4.1.2
- GCC 4.6.2
- GCC 4.6.2 -std=c++0x
- GCC 4.7.0
- GCC 4.7.0 -std=c++0x
- GCC 4.7.1
- GCC 4.7.1 -std=c++0x
- clang 1.6
- clang 2.9
- clang 2.9 -std=c++0x
- clang 3.0
- clang 3.0 -std=c++0x

- clang 3.1
- clang 3.1 -std=c++0x
- clang 3.1 -std=c++0x -stdlib=libc++
- clang 3.2
- clang 3.2 -std=c++11
- clang 3.2 -std=c++11 -stdlib=libc++

The committed code is tested with much more compilers. There are two compilers (VACPP and Borland) that don't provide the needed features. Other as Intel and Sun have some issues with i/o. While everything compiles and link correctly, there are some runtime issues I have not cached yet. See the regression tests for details.



Note

Please let us know how this works on other platforms/compilers.



Note

Please send any questions, comments and bug reports to `boost <at> lists <dot> boost <dot> org`.

Hello World!

Tutorial

Duration

The `duration` is the heart of this library. The interface that the user will see in everyday use is nearly identical to that of **Boost.DateTime** time `durations` authored by Jeff Garland, both in syntax and in behavior. This has been a very popular boost library for 7 years. There is an enormous positive history with this interface.

The library consists of six units of time `duration`:

- `hours`
- `minutes`
- `seconds`
- `milliseconds`
- `microseconds`
- `nanoseconds`

These units were chosen as a subset of the boost library because they are the most common units used when sleeping, waiting on a condition variable, or waiting to obtain the lock on a mutex. Each of these units is nothing but a thin wrapper around a signed integral count. That is, when you construct `minutes(3)`, all that happens is a 3 is stored inside `minutes`. When you construct `microseconds(3)`, all that happens is a 3 is stored inside `microseconds`.

The only context in which these different types differ is when being converted to one another. At this time, unit-specific compile-time conversion constants are used to convert the source unit to the target unit. Only conversions from coarser units to finer units are allowed (in Boost). This restriction ensures that all conversions are always exact. That is, `microseconds` can always represent any value `minutes` has.

In **Boost.DateTime**, these units are united via inheritance. **Boost.Chrono** instead unites these units through the class template `duration`. That is, in **Boost.Chrono** all six of the above units are nothing but typedefs to different instantiations of `duration`. This change from **Boost.DateTime** has a far reaching positive impact, while not changing the syntax of the everyday use at all.

The most immediate positive impact is that the library can immediately generate any unit, with any precision it needs. This is sometimes necessary when doing comparisons or arithmetic between `durations` of differing precision, assuming one wants the comparison and arithmetic to be exact.

A secondary benefit is that by publishing the class template `duration` interface, user code can very easily create `durations` with any precision they desire. The `ratio` utility is used to specify the precision, so as long as the precision can be expressed by a rational constant with respect to seconds, this framework can exactly represent it (one third of a second is no problem, and neither is one third of a femto second). All of this utility and flexibility comes at no cost just by making use of the no-run-time-overhead `ratio` facility.

In **Boost.DateTime**, `hours` does not have the same representation as `nanoseconds`. The former is usually represented with a `long` whereas a `long long` is required for the latter. The reason for this is simply range. You don't need many hours to cover an extremely large range of time. But this isn't true of nanoseconds. Being able to reduce the sizeof overhead for some units when possible, can be a significant performance advantage.

Boost.Chrono continues, and generalizes that philosophy. Not only can one specify the precision of a `duration`, one can also specify its representation. This can be any integral type, or even a floating-point type. Or it can be a user-defined type which emulates an arithmetic type. The six predefined units all use signed integral types as their representation. And they all have a minimum range of ± 292 years. `nanoseconds` needs 64 bits to cover that range. `hours` needs only 23 bits to cover that range.

So What Exactly is a `duration` and How Do I Use One?

A `duration` has a representation and a tick period (precision).

```
template <class Rep, class Period = ratio<1> > class duration;
```

The representation is simply any arithmetic type, or an emulation of such a type. The representation stores a count of ticks. This count is the only data member stored in a `duration`. If the representation is floating-point, it can store fractions of a tick to the precision of the representation. The tick period is represented by a `ratio` and is encoded into the `duration`'s type, instead of stored. The tick period only has an impact on the behavior of the `duration` when a conversion between different `durations` is attempted. The tick period is completely ignored when simply doing arithmetic among like `durations`.

Example:

```
typedef boost::chrono::duration<long, boost::ratio<60> > minutes;
minutes m1(3); // m1 stores 3
minutes m2(2); // m2 stores 2
minutes m3 = m1 + m2; // m3 stores 5

typedef boost::chrono::duration<long long, boost::micro> microseconds;
microseconds us1(3); // us1 stores 3
microseconds us2(2); // us2 stores 2
microseconds us3 = us1 + us2; // us3 stores 5

microseconds us4 = m3 + us3; // us4 stores 30000005
```

In the final line of code above, there is an implicit conversion from minutes to microseconds, resulting in a relatively large number of microseconds.

If you need to access the tick count within a `duration`, there is a member `count()` which simply returns the stored tick count.

```
long long tc = us4.count(); // tc is 30000005
```

These `duration`'s have very simple, very predictable, and very observable behavior. After all, this is really nothing but the time-tested interface of Jeff's boost time `duration` library (unified with templates instead of inheritance).

What Happens if I Assign `m3 + us3` to `minutes` Instead of `microseconds`?

```
minutes m4 = m3 + us3;
```

It won't compile! The rationale is that implicit truncation error should not be allowed to happen. If this were to compile, then `m4` would hold 5, the same value as `m3`. The value associated with `us3` has been effectively ignored. This is similar to the problem of assigning a double to an `int`: the fractional part gets silently discarded.

But What if the Truncation Behavior is What I Want to Do?

There is a `duration_cast` facility to explicitly ask for this behavior:

```
minutes m4 = boost::chrono::duration_cast<minutes>(m3 + us3); // m4.count() == 5
```

In general, one can perform `duration` arithmetic at will. If `duration_cast` isn't used, and it compiles, the arithmetic is exact. If one wants to override this exact arithmetic behavior, `duration_cast` can be used to explicitly specify that desire. The `duration_cast` has the same efficiency as the implicit conversion, and will even be exact as often as it can.

You can use `duration_cast<>` to convert the `duration` into whatever units you desire. This facility will round down (truncate) if an exact conversion is not possible. For example:

```
boost::chrono::nanoseconds start;
boost::chrono::nanoseconds end;
typedef boost::chrono::milliseconds ms;
ms d = boost::chrono::duration_cast<ms>(end - start);

// d now holds the number of milliseconds from start to end.

std::cout << ms.count() << "ms\n";
```

We can convert to `nanoseconds`, or some integral-based duration which `nanoseconds` will always exactly convert to, then `duration_cast<>` is unnecessary:

```
typedef boost::chrono::nanoseconds ns;
ns d = end - start;
std::cout << ns.count() << "ns\n";
```

If you need seconds with a floating-point representation you can also eliminate the `duration_cast<>`:

```
typedef boost::chrono::duration<double> sec; // seconds, stored with a double
sec d = end - start;
std::cout << sec.count() << "s\n";
```

If you're not sure if you need `duration_cast<>` or not, feel free to try it without. If the conversion is exact, or if the destination has a floating-point representation, it will compile: else it will not compile.

If you need to use `duration_cast<>`, but want to round up, instead of down when the conversion is inexact, here is a handy little helper function to do so. Writing it is actually a good starter project for understanding **Boost.Chrono**:

```

template <class ToDuration, class Rep, class Period>
ToDuration
round_up(boost::chrono::duration<Rep, Period> d)
{
    // first round down
    ToDuration result = boost::chrono::duration_cast<ToDuration>(d);
    if (result < d) // comparisons are *always* exact
        ++result; // increment by one tick period
    return result;
}

typedef boost::chrono::milliseconds ms;
ms d = round_up<ms>(end - start);
// d now holds the number of milliseconds from start to end, rounded up.
std::cout << ms.count() << "ms\n";

```

Rounding functions

Boost.Chrono provides few simple rounding utility functions for working with durations.

```

// round down
template <class To, class Rep, class Period>
To
floor(const duration<Rep, Period>& d)
{
    return duration_cast<To>(d);
}

// round to nearest, to even on tie
template <class To, class Rep, class Period>
To
round(const duration<Rep, Period>& d)
{
    To t0 = duration_cast<To>(d);
    To t1 = t0;
    ++t1;
    BOOST_AUTO(diff0, d - t0);
    BOOST_AUTO(diff1, t1 - d);
    if (diff0 == diff1)
    {
        if (t0.count() & 1)
            return t1;
        return t0;
    }
    else if (diff0 < diff1)
        return t0;
    return t1;
}

// round up
template <class To, class Rep, class Period>
To
ceil(const duration<Rep, Period>& d)
{
    To t = duration_cast<To>(d);
    if (t < d)
        ++t;
    return t;
}

```

The beauty of the chrono library is the ease and accuracy with which such conversions can be made. For example to convert from **milliseconds** (1/1000 of a second), to 1/30 of a second, one must multiply the milliseconds by 0.03. It is common knowledge

that you can't exactly represent 0.03 in a computer. Nevertheless `round` will exactly (with no round off error) detect a tie and round to even when this happens. The differences `diff0` and `diff1` are not approximate, but exact differences, even when `d` has the units of millisecond and `T0` is 1/30 of a second. The unit of `diff0` and `diff1` is 1/3000 of a second which both millisecond and 1/30 of a second exactly convert to (with no truncation error).

Similarly, the comparison `t < d` in `ceil` is exact, even when there is no exact conversion between `t` and `d`. Example use of rounding functions

```
#include <iostream>
#include <boost/chrono/chrono_io.hpp>
#include <boost/chrono/floor.hpp>
#include <boost/chrono/round.hpp>
#include <boost/chrono/ceil.hpp>

int main()
{
    using namespace boost::chrono;
    milliseconds ms(2500);
    std::cout << floor<seconds>(ms) << '\n';
    std::cout << round<seconds>(ms) << '\n';
    std::cout << ceil<seconds>(ms) << '\n';
    ms = milliseconds(2516);
    typedef duration<long, boost::ratio<1, 30> > frame_rate;
    std::cout << floor<frame_rate>(ms) << '\n';
    std::cout << round<frame_rate>(ms) << '\n';
    std::cout << ceil<frame_rate>(ms) << '\n';

    return 0;
}
```

The output of this program should be

```
2 seconds
2 seconds
3 seconds
75 [1/30]seconds
75 [1/30]seconds
76 [1/30]seconds
```

Trafficking in floating-point Durations

I don't want to deal with writing `duration_cast` all over the place. I'm content with the precision of my floating-point representation.

Not a problem. When the destination of a conversion has floating-point representation, all conversions are allowed to happen implicitly.

```
typedef boost::chrono::duration<double, ratio<60> > dminutes;
dminutes dm4 = m3 + us3; // dm4.count() == 5.000000083333333
```

How Expensive is All of this?

If you were writing these conversions by hand, you could not make it more efficient. The use of `ratio` ensures that all conversion constants are simplified as much as possible at compile-time. This usually results in the numerator or denominator of the conversion factor simplifying to 1, and being subsequently ignored in converting the run-time values of the tick counts.

How Complicated is it to Build a Function Taking a `duration` Parameter?

There are several options open to the user:

- If the author of the function wants to accept any `duration`, and is willing to work in floating-point `durations`, he can simply use any floating-point `duration` as the parameter:

```
void f(boost::chrono::duration<double> d) // accept floating-point seconds
{
    // d.count() == 3.e-6 when passed boost::chrono::microseconds(3)
}

f(boost::chrono::microseconds(3));
```

- If the author of the function wants to traffic only in integral `durations`, and is content with handling nothing finer than say nanoseconds (just as an example), he can simply specify nanoseconds as the parameter:

```
void f(boost::chrono::nanoseconds d)
{
    // d.count() == 3000 when passed boost::chrono::microseconds(3)
}

f(boost::chrono::microseconds(3));
```

In this design, if the client wants to pass in a floating-point `duration`, or a `duration` of finer precision than nanoseconds, then the client is responsible for choosing his own rounding mode in the conversion to nanoseconds.

```
boost::chrono::duration<double> s(1./3); // 1/3 of a second
f(boost::chrono::duration_cast<boost::chrono::nanoseconds>(s)); // round towards zero in conversion to nanoseconds
```

In the example above, the client of `f` has chosen "round towards zero" as the desired rounding mode to nanoseconds. If the client has a `duration` that won't exactly convert to nanoseconds, and fails to choose how the conversion will take place, the compiler will refuse the call:

```
f(s); // does not compile
```

- If the author of the function wants to accept any `duration`, but wants to work with integral representations and wants to control the rounding mode internally, then he can template the function:

```
template <class Rep, class Period>
void f(boost::chrono::duration<Rep, Period> d)
{
    // convert d to nanoseconds, rounding up if it is not an exact conversion
    boost::chrono::nanoseconds ns = boost::chrono::duration_cast<boost::chrono::nanoseconds>(d);
    if (ns < d)
        ++ns;
    // ns.count() == 333333334 when passed 1/3 of a floating-point second
}

f(boost::chrono::duration<double>(1./3));
```

- If the author in the example does not want to accept floating-point based `durations`, he can enforce that behavior like so:

```

template <class Period>
void f(boost::chrono::duration<long long, Period> d)
{
    // convert d to nanoseconds, rounding up if it is not an exact conversion
    boost::chrono::nanoseconds ns = boost::chrono::duration_cast<nanoseconds>(d);
    if (ns < d)
        ++ns;
    // ns.count() == 333333334 when passed 333333333333 picoseconds
}
// About 1/3 of a second worth of picoseconds
f(boost::chrono::duration<long long, boost::pico>(333333333333));

```

Clients with floating-point `duration`s who want to use `f` will now have to convert to an integral `duration` themselves before passing the result to `f`.

In summary, the author of `f` has quite a bit of flexibility and control in the interface he wants to provide his clients with, and easy options for manipulating that `duration` internal to his function.

Is it possible for the user to pass a `duration` to a function with the units being ambiguous?

No. No matter which option the author of `f` chooses above, the following client code will not compile:

```
f(3); // Will not compile, 3 is not implicitly convertible to any __duration
```

Can Durations Overflow?

This depend on the representation. The default typedefs uses a representation that don't handle overflows. The user can define his own representation that manage overflow as required by its application.

Clocks

While `duration`s only have precision and representation to concern themselves, clocks and `time_point`s are intimately related and refer to one another. Because clocks are simpler to explain, we will do so first without fully explaining `time_point`s. Once clocks are introduced, it will be easier to then fill in what a `time_point` is.

A clock is a concept which bundles 3 things:

1. A concrete `duration` type.
2. A concrete `time_point` type.
3. A function called `now()` which returns the concrete `time_point`.

The standard defines three system-wide clocks that are associated to the computer time.

- `system_clock` represents system-wide realtime clock that can be synchronized with an external clock.
- `steady_clock` can not be changed explicitly and the time since the initial epoch increase in a steady way.
- `high_resolution_clock` intend to use the system-wide clock provided by the platform with the highest resolution.

Boost.Chrono provides them when supported by the underlying platform. A given platform may not be able to supply all three of these clocks.

The library adds some clocks that are specific to a process or a thread, that is there is a clock per process or per thread.

The user is also able to easily create more clocks.

Given a clock named `Clock`, it will have:

```
class Clock {
public:
    typedef an arithmetic-like type        rep;
    typedef an instantiation of ratio      period;
    typedef boost::chrono::duration<rep, period> duration;
    typedef boost::chrono::time_point<Clock> time_point;
    static constexpr bool is_steady =      true or false;

    static time_point now();
};
```

One can get the current time from Clock with:

```
Clock::time_point t1 = Clock::now();
```

And one can get the time `duration` between two `time_points` associated with Clock with:

```
Clock::duration d = Clock::now() - t1;
```

And one can specify a past or future `time_point` with:

```
Clock::time_point t2 = Clock::now() + d;
```

Note how even if a particular clock becomes obsolete, the next clock in line will have the same API. There is no new learning curve to come up. The only source code changes will be simply changing the type of the clock. The same `duration` and `time_point` framework continues to work as new clocks are introduced. And multiple clocks are safely and easily handled within the same program.

Time Point

A `time_point` represents a point in time, as opposed to a `duration` of time. Another way of saying the same thing, is that a `time_point` represents an epoch plus or minus a `duration`. Examples of `time_points` include:

- 3 minutes after the computer booted.
- 03:14:07 UTC on Tuesday, January 19, 2038
- 20 milliseconds after I started that timer.

In each of the examples above, a different epoch is implied. Sometimes an epoch has meaning for several millennia. Other times the meaning of an epoch is lost after a while (such as the start of a timer, or when the computer booted). However, if two `time_points` are known to share the same epoch, they can be subtracted, yielding a valid `duration`, even if the definition of the epoch no longer has meaning.

In **Boost.Chrono**, an epoch is a purely abstract and unspecified concept. There is no type representing an epoch. It is simply an idea that relates (or doesn't) `time_points` to a clock, and in the case that they share a clock, `time_points` to one another. `time_points` associated with different clocks are generally not interoperable unless the relationship between the epochs associated with each clock is known.

So What Exactly is a `time_point` and How Do I Use One?

A `time_point` has a clock and a `duration`.

```
template <class Clock, class Duration = typename Clock::duration> class time_point;
```

The `time_point`'s clock is not stored. It is simply embedded into the `time_point`'s type and serves two purposes:

1. Because `time_points` originating from different clocks have different types, the compiler can be instructed to fail if incompatible `time_points` are used in inappropriate ways.
2. Given a `time_point`, one often needs to compare that `time_point` to "now". This is very simple as long as the `time_point` knows what clock it is defined with respect to.

A `time_point`'s `duration` is stored as the only data member of the `time_point`. Thus `time_points` and their corresponding `duration` have exactly the same layout. But they have very different meanings. For example, it is one thing to say I want to sleep for 3 minutes. It is a completely different thing to say I want to sleep until 3 minutes past the time I started that timer (unless you just happened to start that timer now). Both meanings (and options for sleeping) have great practical value in common use cases for sleeping, waiting on a condition variable, and waiting for a mutex's lock. These same concepts and tools are found (for example) in Ada.

A timer example:

```
void f()
{
    boost::chrono::steady_clock::time_point start = boost::chrono::steady_clock::now();
    g();
    h();
    duration<double> sec = boost::chrono::steady_clock::now() - start;
    cout << "f() took " << sec.count() << " seconds\n";
}
```

Note that if one is using the `duration` between two clock `time_points` in a way where the precision of the `duration` matters, it is good practice to convert the clock's `duration` to a known `duration`. This insulates the code from future changes which may be made to the clock's precision in the future. For example `steady_clock` could easily be based on the clock speed of the cpu. When you upgrade to a faster machine, you do not want your code that assumed a certain tick period of this clock to start experiencing run-time failures because your timing code has silently changed meaning.

A delay loop example:

```
// delay for at least 500 nanoseconds:
auto go = boost::chrono::steady_clock::now() + boost::chrono::nanoseconds(500);
while (boost::chrono::steady_clock::now() < go)
    ;
```

The above code will delay as close as possible to half a microsecond, no matter what the precision of `steady_clock` is. The more precise `steady_clock` becomes, the more accurate will be the delay to 500 nanoseconds.

Specific Clocks

`system_clock`

`system_clock` is useful when you need to correlate the time with a known epoch so you can convert it to a calendar time. Note the specific functions in the `system_clock` class.

`steady_clock`

`steady_clock` is useful when you need to wait for a specific amount of time. `steady_clock` time can not be reset. As other steady clocks, it is usually based on the processor tick.

Here is a polling solution, but it will probably be too inefficient:

```
boost::chrono::steady_clock::time_point start= chrono::steady_clock::now();
boost::chrono::steady_clock::duration delay= chrono::seconds(5);
while (boost::chrono::steady_clock::now() - start <= delay) {}
```

high_resolution_clock

When available, `high_resolution_clock` is usually more expensive than the other system-wide clocks, so they are used only when the provided resolution is required to the application.

process_cpu_clock

Process and thread clocks are used usually to measure the time spent by code blocks, as a basic time-spent profiling of different blocks of code (Boost.Chrono.Stopwatch is a clear example of this use).

thread_clock

You can use `thread_clock` whenever you want to measure the time spent by the current thread. For example:

```
boost::chrono::thread_clock::time_point start=boost::chrono::thread_clock::now();
// ... do something ...

typedef boost::chrono::milliseconds ms;
ms d = boost::chrono::thread_clock::now() - start;
// d now holds the number of milliseconds from start to end.
std::cout << ms.count() << "ms\n";
```

If you need seconds with a floating-point representation you can do:

```
typedef boost::chrono::duration<double> sec; // seconds, stored with a double.
sec d = end - start;
std::cout << sec.count() << "s\n";
```

If you would like to programmatically inspect `thread_clock::duration`, you can get the representation type with `thread_clock::rep`, and the tick period with `thread_clock::period` (which should be a type ratio which has nested values `ratio::num` and `ratio::den`). The tick period of `thread_clock` is `thread_clock::period::num / thread_clock::period::den` seconds: 1/1000000000 in this case (1 billionth of a second), stored in a long long.

I/O

duration

Any `duration` can be streamed out to a `basic_ostream`. The run-time value of the `duration` is formatted according to the rules and current format settings for `duration::rep` `get_duration_style` and the `durationpunct` facet.

the format is either

```
<value> <unit>
```

or

```
<unit> <value>
```



Warning

Need to be changed This is followed by a single space and then the compile-time unit name of the `duration`. This unit name is built on the string returned from `ratio_string<>` and the data used to construct the `duration_punct` which was inserted into the stream's locale. If a `duration_punct` has not been inserted into the stream's locale, a default constructed `duration_punct` will be added to the stream's locale.

`duration` unit names come in two varieties: long(prefix) and short(symbol). The default constructed `duration_punct` provides names in the long(prefix) format. These names are English descriptions. Other languages are supported by constructing a `duration_punct` with the proper spellings for "hours", "minutes" and "seconds", and their abbreviations (for the short format). The short or long format can be easily chosen by streaming a `duration_short()` or `duration_long()` manipulator respectively or using the parameterized manipulator `duration_fmt(duration_style::prefix)` or `duration_fmt(duration_style::symbol)`.

Example:

```
#include <iostream>
#include <boost/chrono/chrono_io.hpp>

int main()
{
    using namespace std;
    using namespace boost;

    cout << "milliseconds(1) = "
         << boost::chrono::milliseconds(1) << '\n';

    cout << "milliseconds(3) + microseconds(10) = "
         << boost::chrono::milliseconds(3) + boost::chrono::microseconds(10) << '\n';

    cout << "hours(3) + minutes(10) = "
         << boost::chrono::hours(3) + boost::chrono::minutes(10) << '\n';

    typedef boost::chrono::duration<long long, boost::ratio<1, 2500000000> > ClockTick;
    cout << "ClockTick(3) + boost::chrono::nanoseconds(10) = "
         << ClockTick(3) + boost::chrono::nanoseconds(10) << '\n';

    // ...
    return 0;
}
```

The output could be

```
milliseconds(1) = 1 microsecond
milliseconds(3) + microseconds(10) = 3010 microseconds
hours(3) + minutes(10) = 190 minutes
ClockTick(3) + nanoseconds(10) = 56 [1/5000000000]seconds

Set cout to use short names:
milliseconds(3) + microseconds(10) = 3010 μs
hours(3) + minutes(10) = 190 m
ClockTick(3) + nanoseconds(10) = 56 [1/5000000000]s

system_clock::now() = 129387415616250000 [1/10000000]s since Jan 1, 1970
monotonic_clock::now() = 37297387636417 ns since boot

Set cout to use long names:
high_resolution_clock::now() = 37297387655134 nanoseconds since boot
```

As can be seen, each duration type can be streamed without having to manually stream the compile-time units after the run-time value. And when the compile-time unit is known to be a "common unit", English names are used. For "uncommon units" a unit name is composed from the reduced numerator and denominator of the associated `ratio`. Whatever stream/locale settings are set for `duration::rep` are used for the value. Additionally, when the value is 1, singular forms for the units are used.

Sometimes it is desired to shorten these names by using the SI symbols instead of SI prefixes. This can be accomplished with the use of the `symbol_format` manipulator¹:

```
cout << "\nSet cout to use short names:\n";
cout << boost::chrono::symbol_format;

cout << "milliseconds(3) + microseconds(10) = "
    << boost::chrono::milliseconds(3) + boost::chrono::microseconds(10) << '\n';

cout << "hours(3) + minutes(10) = "
    << boost::chrono::hours(3) + boost::chrono::minutes(10) << '\n';

cout << "ClockTick(3) + nanoseconds(10) = "
    << ClockTick(3) + boost::chrono::nanoseconds(10) << '\n';
```

The output could be

```
Set cout to use short names:
milliseconds(3) + microseconds(10) = 3010 µs
hours(3) + minutes(10) = 190 m
ClockTick(3) + nanoseconds(10) = 56 [1/5000000000]s

system_clock::now() = 129387415616250000 [1/10000000]s since Jan 1, 1970
monotonic_clock::now() = 37297387636417 ns since boot

Set cout to use long names:
high_resolution_clock::now() = 37297387655134 nanoseconds since boot
```

The μ for microsecond is specified to be U+00B5, encoded as UTF-8, UTF-16 or UTF-32 as appropriate for the stream's character size.

When the format decision is taken at runtime, it could be better to use the parameterized manipulator `duration_fmt` as in

```
duration_style style;
//...
cout << duration_fmt(style);
```

Parsing a `duration` follows rules analogous to the `duration` converting constructor. A value and a unit (SI symbol or prefixed) are read from the `basic_istream`. If the `duration` has an integral representation, then the value parsed must be exactly representable in the target `duration` (after conversion to the target `duration` units), else `failbit` is set. `durations` based on floating-point representations can be parsed using any units that do not cause overflow.

For example a stream containing "5000 milliseconds" can be parsed into seconds, but if the stream contains "3001 ms", parsing into seconds will cause `failbit` to be set.

Example:

¹ `duration_short` in V1

```

#include <boost/chrono/chrono_io.hpp>
#include <sstream>
#include <cassert>

int main()
{
    using namespace std;

    istringstream in("5000 milliseconds 4000 ms 3001 ms");
    boost::chrono::seconds d(0);
    in >> d;
    assert(in.good());
    assert(d == seconds(5));
    in >> d;
    assert(in.good());
    assert(d == seconds(4));
    in >> d;
    assert(in.fail());
    assert(d == seconds(4));

    return 0;
}

```

Note that a `duration` failure may occur late in the parsing process. This means that the characters making up the failed parse in the stream are usually consumed despite the failure to successfully parse.

Sometimes in templated code it is difficult to know what the unit of your duration is. It is all deterministic, and inspect-able. But it can be inconvenient to do so, especially if you just need to print out a "debugging" statement. For example:

```

// round to nearest, to even on tie
template <class To, class Rep, class Period>
To
round(const duration<Rep, Period>& d)
{
    To t0 = duration_cast<To>(d);
    To t1 = t0;
    ++t1;
    auto diff0 = d - t0;
    cout << "diff0 = " << diff0 << '\n';
    auto diff1 = t1 - d;
    cout << "diff1 = " << diff1 << '\n';
    if (diff0 == diff1)
    {
        if (t0.count() & 1)
            return t1;
        return t0;
    }
    else if (diff0 < diff1)
        return t0;
    return t1;
}

```

This is where I/O for duration really shines. The compiler knows what the type of `diff0` is and with this proposal that type (with proper units) will automatically be printed out for you. For example:

```

milliseconds ms = round<milliseconds>(nanoseconds(123)); // diff0 = 123 nanoseconds
// diff1 = 999877 nanoseconds
milliseconds ms = round<milliseconds>(Ticks(44)); // diff0 = 2 [1/3000]seconds
// diff1 = 1 [1/3000]second

```

This simple I/O will make duration so much more accessible to programmers.

`system_clock::time_point`

`system_clock` is special. It is the only clock that has conversions between its `time_point` and `time_t`. C subsequently relates `time_t` to the [Gregorian calendar](#) via `ctime`, `gmtime`, `localtime`, and `strftime`. Neither C, nor POSIX relate `time_t` to any calendar other than the [Gregorian calendar](#). ISO 8601 is specified only in terms of the [Gregorian calendar](#).

Boost.Chrono provides `system_clock::time_point` I/O in terms of the Gregorian calendar, and no other calendar. However as `system_clock::time_point` remains convertible with `time_t`, it is possible for clients to create other calendars which interoperate with `time_t` and subsequently `system_clock::time_point`.

Furthermore, it is existing practice for all major hosted operating systems to store system time in a format which facilitates display as [Coordinated Universal Time](#) (UTC). Therefore **Boost.Chrono** provides that the default output for `system_clock::time_point` be in a format that represents a point in time with respect to UTC.

```
cout << system_clock::now() << '\n';
```

could output

```
2011-09-15 18:36:59.325132 +0000
```

This format is strongly influenced by ISO 8601, but places a ' ' between the date and time instead of a 'T'. The former appears to more accurately represent existing practice. A fully numeric format was chosen so as to be understandable to as large a group of human readers as possible. A 24 hour format was chosen for the same reasons.

Of the referenced standards, only ISO 8601 discusses the output of fractional seconds. Neither C nor POSIX have built-in functionality for this. However it appears to be universal (as of this writing) that `system_clock::period` is sub-second. And it seems desirable that if you stream out a `system_clock::time_point`, you ought to be able to stream it back in and get the same value. Therefore the streaming of fractional seconds (at least by default) appears to be unavoidable.

Finally the trailing " +0000" disambiguates the UTC-formatted `system_clock::time_point` from one formatted with respect to the local time zone of the computer. The latter can easily be achieved with:

```
cout << time_fmt(local) << system_clock::now() << '\n';
```

that could result in

```
2011-09-15 14:36:59.325132 -0400
```

Note that `system_clock::time_point` itself is neither UTC, nor the local time. However in practice, `system_clock::time_point` is a count of ticks beyond some epoch which is synchronized with UTC. So as a mobile computer moves across time zones, the time zone traversal does not impact the value of a `system_clock::time_point` produced by `system_clock::now()`. And it is only in formatting it for human consumption that one can choose UTC or the local time zone. C and POSIX treat `time_t` just as **Boost.Chrono** treats `system_clock::time_point`:

```
tm* gmtime(const time_t* timer) -> UTC
tm* localtime(const time_t* timer) -> local time
```

This proposal simply extends the C/POSIX `time_t` functionality to C++ syntax and `system_clock::time_point`.

The `time_fmt()` manipulator is "sticky". It will remain in effect until the stream destructs or until it is changed. The stream can be reset to its default state with:

```
cout << time_fmt(utc);
```

And the formatting can be further customized by using the time format sequences. For example:

```
cout << time_fmt(local, "%A %B %e, %Y %r");
cout << system_clock::now() << '\n'; // Sunday April 24, 2011 02:36:59 PM
```

When specifying formatting manipulators for wide streams, use wide strings.

You can use the same manipulators with istreams to specify parsing sequences.

Unfortunately there are no formatting/parsing sequences which indicate fractional seconds. **Boost.Chrono** does not provide such sequences. In the meantime, one can format and parse fractional seconds for `system_clock::time_point` by defaulting the format, or by using an empty string in `time_fmt()`.

The stream's current locale may impact the parsing/format sequences supplied to the `system_clock::time_point` manipulators (e.g. names of days of the week, and names of months).

Other clocks `time_point`

Unlike `system_clock::time_point`, the other clocks have no conversion with `time_t`. There is likely no relationship between `steady_clock::time_point` and UTC at all (UTC is not steady).

In general a `time_point` is formatted by outputting its internal `duration` followed by a string that describes the `time_point::clock` epoch. This string will vary for each distinct clock, and for each implementation of the supplied clocks.

```
#ifdef BOOST_CHRONO_HAS_CLOCK_STEADY
    cout << "steady_clock::now() = " << boost::chrono::steady_clock::now() << '\n';
#endif
cout << "\nSet cout to use long names:\n"
    << boost::chrono::duration_long
    << "high_resolution_clock::now() = "
    << boost::chrono::high_resolution_clock::now() << '\n';
```

The output could be

```
steady_clock::now() = 37297387636417 ns since boot

Set cout to use long names:
high_resolution_clock::now() = 37297387655134 nanoseconds since boot
```

Parsing a `time_point` involves first parsing a `duration` and then parsing the epoch string. If the epoch string does not match that associated with `time_point::clock` then `failbit` will be set.

Example:

```

#include <boost/chrono/chrono_io.hpp>
#include <sstream>
#include <iostream>
#include <cassert>

int main()
{
    using namespace std;

    boost::chrono::high_resolution_clock::time_point t0 = boost::chrono::high_resolu-
tion_clock::now();
    stringstream io;
    io << t0;
    boost::chrono::high_resolution_clock::time_point t1;
    io >> t1;
    assert(!io.fail());
    cout << io.str() << '\n';
    cout << t0 << '\n';
    cout << t1 << '\n';
    boost::chrono::high_resolution_clock::time_point t = boost::chrono::high_resolu-
tion_clock::now();
    cout << t << '\n';

    cout << "That took " << t - t0 << '\n';
    cout << "That took " << t - t1 << '\n';

    return 0;
}

```

The output could be:

```

50908679121461 nanoseconds since boot
That took 649630 nanoseconds

```

Here's a simple example to find out how many hours the computer has been up (on this platform):

```

#include <boost/chrono/chrono_io.hpp>
#include <iostream>

int main()
{
    using namespace std;
    using namespace boost;

    typedef boost::chrono::time_point<boost::chrono::steady_clock, boost::chrono::dura-
tion<double, boost::ratio<3600> > > > T;
    T tp = boost::chrono::steady_clock::now();
    std::cout << tp << '\n';
    return 0;
}

```

The output could be:

```

17.8666 hours since boot

```

Low level I/O

The I/O interface described in the preceding I/O sections were at the user level. These services are based on low level services that are useful when writing libraries. The low level services are related to access to the associated ios state and locale facets. The design follows the C++ IOStreams standard design:

The library encapsulate the locale-dependent parsing and formatting of `duration` into a new facet class. Let's focus on formatting in this example. The concerned facet class is `duration_put`, analogous to `time_put`, `money_put`, etc.

The use of this facet is similar to the `time_put` facet.

Examples

Duration

How you Override the Duration's Default Constructor

Next we show how to override the `duration`'s default constructor to do anything you want (in this case set it to zero). All we need to do is to change the representation

```
namespace I_dont_like_the_default_duration_behavior {

template <class R>
class zero_default
{
public:
    typedef R rep;

private:
    rep rep_;
public:
    zero_default(rep i = 0) : rep_(i) {}
    operator rep() const {return rep_;}

    zero_default& operator+=(zero_default x) {rep_ += x.rep_; return *this;}
    zero_default& operator-=(zero_default x) {rep_ -= x.rep_; return *this;}
    zero_default& operator*=(zero_default x) {rep_ *= x.rep_; return *this;}
    zero_default& operator/=(zero_default x) {rep_ /= x.rep_; return *this;}

    zero_default operator+ () const {return *this;}
    zero_default operator- () const {return zero_default(-rep_);}
    zero_default& operator++() {++rep_; return *this;}
    zero_default& operator++(int) {return zero_default(rep_++);}
    zero_default& operator--() {--rep_; return *this;}
    zero_default& operator--(int) {return zero_default(rep_--);}

    friend zero_default operator+(zero_default x, zero_default y) {return x += y;}
    friend zero_default operator-(zero_default x, zero_default y) {return x -= y;}
    friend zero_default operator*(zero_default x, zero_default y) {return x *= y;}
    friend zero_default operator/(zero_default x, zero_default y) {return x /= y;}

    friend bool operator==(zero_default x, zero_default y) {return x.rep_ == y.rep_;}
    friend bool operator!=(zero_default x, zero_default y) {return !(x == y);}
    friend bool operator< (zero_default x, zero_default y) {return x.rep_ < y.rep_;}
    friend bool operator<=(zero_default x, zero_default y) {return !(y < x);}
    friend bool operator> (zero_default x, zero_default y) {return y < x;}
    friend bool operator>=(zero_default x, zero_default y) {return !(x < y);}
};

typedef boost::chrono::duration<zero_default<long long>, boost::nano > nanoseconds;
```

```

typedef boost::chrono::duration<zero_default<long long>, boost::micro      > microseconds;
typedef boost::chrono::duration<zero_default<long long>, boost::milli      > milliseconds;
typedef boost::chrono::duration<zero_default<long long>, boost::ratio<1>   > seconds;
typedef boost::chrono::duration<zero_default<long long>, boost::ratio<60>  > minutes;
typedef boost::chrono::duration<zero_default<long long>, boost::ratio<3600> > hours;
}

```

Usage

```

using namespace I_dont_like_the_default_duration_behavior;

milliseconds ms;
std::cout << ms.count() << '\n';

```

See the source file [example/i_dont_like_the_default_duration_behavior.cpp](#)

Saturating

A "saturating" signed integral type is developed. This type has +/- infinity and a NaN (like IEEE floating-point) but otherwise obeys signed integral arithmetic. This class is subsequently used as the template parameter Rep in boost::chrono::duration to demonstrate a duration class that does not silently ignore overflow.

See the source file [example/saturating.cpp](#)

xtime Conversions

Example round_up utility: converts d to To, rounding up for inexact conversions Being able to **easily** write this function is a major feature!

```

#include <boost/chrono.hpp>
#include <boost/type_traits.hpp>

#include <iostream>

template <class To, class Rep, class Period>
To
round_up(boost::chrono::duration<Rep, Period> d)
{
    To result = boost::chrono::duration_cast<To>(d);
    if (result < d)
        ++result;
    return result;
}

```

To demonstrate interaction with an xtime-like facility:

```

struct xtime
{
    long sec;
    unsigned long usec;
};

template <class Rep, class Period>
xtime
to_xtime_truncate(boost::chrono::duration<Rep, Period> d)
{
    xtime xt;
    xt.sec = static_cast<long>(boost::chrono::duration_cast<seconds>(d).count());
    xt.usec = static_cast<long>(boost::chrono::duration_cast<microseconds>(d - seconds(xt.sec)).count());
    return xt;
}

template <class Rep, class Period>
xtime
to_xtime_round_up(boost::chrono::duration<Rep, Period> d)
{
    xtime xt;
    xt.sec = static_cast<long>(boost::chrono::duration_cast<seconds>(d).count());
    xt.usec = static_cast<unsigned long>(round_up<boost::chrono::microseconds>(d - boost::chrono::seconds(xt.sec)).count());
    return xt;
}

microseconds
from_xtime(xtime xt)
{
    return boost::chrono::seconds(xt.sec) + boost::chrono::microseconds(xt.usec);
}

void print(xtime xt)
{
    std::cout << '{' << xt.sec << ',' << xt.usec << "}\n";
}

```

Usage

```

xtime xt = to_xtime_truncate(seconds(3) + boost::chrono::milliseconds(251));
print(xt);
boost::chrono::milliseconds ms = boost::chrono::duration_cast<boost::chrono::milliseconds>(from_xtime(xt));
std::cout << ms.count() << " milliseconds\n";
xt = to_xtime_round_up(ms);
print(xt);
xt = to_xtime_truncate(boost::chrono::seconds(3) + nanoseconds(999));
print(xt);
xt = to_xtime_round_up(boost::chrono::seconds(3) + nanoseconds(999));
print(xt);

```

See the source file [xtime.cpp](#)

Clocks

Cycle count

Users can easily create their own clocks, with both points in time and time durations which have a representation and precision of their own choosing. For example if there is a hardware counter which simply increments a count with each cycle of the cpu, one can

very easily build clocks, time points and durations on top of that, using only a few tens of lines of code. Such systems can be used to call the time-sensitive threading API's such as `sleep`, wait on a condition variable, or wait for a mutex lock. The API proposed herein is not sensitive as to whether this is a 300MHz clock (with a 3 1/3 nanosecond tick period) or a 3GHz clock (with a tick period of 1/3 of a nanosecond). And the resulting code will be just as efficient as if the user wrote a special purpose clock cycle counter.

```
#include <boost/chrono.hpp>
#include <boost/type_traits.hpp>
#include <iostream>

template <long long speed>
struct cycle_count
{
    typedef typename boost::_ratio_multiply__<boost::ratio<speed>, boost::mega>::type
        frequency; // Mhz
    typedef typename boost::_ratio_divide__<boost::ratio<1>, frequency>::type period;
    typedef long long rep;
    typedef boost::chrono::duration<rep, period> duration;
    typedef boost::chrono::time_point<cycle_count> time_point;

    static time_point now()
    {
        static long long tick = 0;
        // return exact cycle count
        return time_point(duration(++tick)); // fake access to clock cycle count
    }
};

template <long long speed>
struct approx_cycle_count
{
    static const long long frequency = speed * 1000000; // MHz
    typedef nanoseconds duration;
    typedef duration::rep rep;
    typedef duration::period period;
    static const long long nanosec_per_sec = period::den;
    typedef boost::chrono::time_point<approx_cycle_count> time_point;

    static time_point now()
    {
        static long long tick = 0;
        // return cycle count as an approximate number of nanoseconds
        // compute as if nanoseconds is only duration in the std::lib
        return time_point(duration(++tick * nanosec_per_sec / frequency));
    }
};
```

See the source file [cycle_count.cpp](#)

xtime_clock

This example demonstrates the use of a timeval-like struct to be used as the representation type for both `duration` and `time_point`.

```

class xtime {
private:
    long tv_sec;
    long tv_usec;

    void fixup() {
        if (tv_usec < 0) {
            tv_usec += 1000000;
            --tv_sec;
        }
    }
public:
    explicit xtime(long sec, long usec) {
        tv_sec = sec;
        tv_usec = usec;
        if (tv_usec < 0 || tv_usec >= 1000000) {
            tv_sec += tv_usec / 1000000;
            tv_usec %= 1000000;
            fixup();
        }
    }

    explicit xtime(long long usec) {
        tv_usec = static_cast<long>(usec % 1000000);
        tv_sec = static_cast<long>(usec / 1000000);
        fixup();
    }

    // explicit
    operator long long() const {return static_cast<long long>(tv_sec) * 1000000 + tv_usec;}

    xtime& operator += (xtime rhs) {
        tv_sec += rhs.tv_sec;
        tv_usec += rhs.tv_usec;
        if (tv_usec >= 1000000) {
            tv_usec -= 1000000;
            ++tv_sec;
        }
        return *this;
    }

    xtime& operator -= (xtime rhs) {
        tv_sec -= rhs.tv_sec;
        tv_usec -= rhs.tv_usec;
        fixup();
        return *this;
    }

    xtime& operator %= (xtime rhs) {
        long long t = tv_sec * 1000000 + tv_usec;
        long long r = rhs.tv_sec * 1000000 + rhs.tv_usec;
        t %= r;
        tv_sec = static_cast<long>(t / 1000000);
        tv_usec = static_cast<long>(t % 1000000);
        fixup();
        return *this;
    }

    friend xtime operator+(xtime x, xtime y) {return x += y;}
    friend xtime operator-(xtime x, xtime y) {return x -= y;}
    friend xtime operator%(xtime x, xtime y) {return x %= y;}

```

```

friend bool operator==(xtime x, xtime y)
    { return (x.tv_sec == y.tv_sec && x.tv_usec == y.tv_usec); }

friend bool operator<(xtime x, xtime y) {
    if (x.tv_sec == y.tv_sec)
        return (x.tv_usec < y.tv_usec);
    return (x.tv_sec < y.tv_sec);
}

friend bool operator!=(xtime x, xtime y) { return !(x == y); }
friend bool operator>(xtime x, xtime y) { return y < x; }
friend bool operator<=(xtime x, xtime y) { return !(y < x); }
friend bool operator>=(xtime x, xtime y) { return !(x < y); }

friend std::ostream& operator<<(std::ostream& os, xtime x)
    {return os << '{' << x.tv_sec << ',' << x.tv_usec << '}';}
};

```

Clock based on timeval-like struct.

```

class xtime_clock
{
public:
    typedef xtime                rep;
    typedef boost::micro        period;
    typedef boost::chrono::duration<rep, period>    duration;
    typedef boost::chrono::time_point<xtime_clock> time_point;

    static time_point now()
    {
#ifdef BOOST_CHRONO_WINDOWS_API
        time_point t(duration(xtime(0)));
        gettimeofday((timeval*)&t, 0);
        return t;
#elif defined(BOOST_CHRONO_MAC_API)

        time_point t(duration(xtime(0)));
        gettimeofday((timeval*)&t, 0);
        return t;
#elif defined(BOOST_CHRONO_POSIX_API)
        //time_point t(0,0);

        timespec ts;
        ::clock_gettime( CLOCK_REALTIME, &ts );

        xtime xt( ts.tv_sec, ts.tv_nsec/1000);
        return time_point(duration(xt));
#endif // POSIX
    }
};

```

Usage of xtime_clock

```

std::cout << "sizeof xtime_clock::time_point = " << sizeof(xtime_clock::time_point) << '\n';
std::cout << "sizeof xtime_clock::duration = " << sizeof(xtime_clock::duration) << '\n';
std::cout << "sizeof xtime_clock::rep = " << sizeof(xtime_clock::rep) << '\n';
xtime_clock::duration delay(boost::chrono::milliseconds(5));
xtime_clock::time_point start = xtime_clock::now();
while (xtime_clock::now() - start <= delay) {}
xtime_clock::time_point stop = xtime_clock::now();
xtime_clock::duration elapsed = stop - start;
std::cout << "paused " << boost::chrono::nanoseconds(elapsed).count() << " nanoseconds\n";

```

See the source file [example/timeval_demo.cpp](#)

Time Point

min Utility

The user can define a function returning the earliest `time_point` as follows:

```

template <class Clock, class Duration1, class Duration2>
typename boost::common_type<time_point<Clock, Duration1>,
                           time_point<Clock, Duration2> >::type
min(time_point<Clock, Duration1> t1, time_point<Clock, Duration2> t2)
{
    return t2 < t1 ? t2 : t1;
}

```

Being able to **easily** write this function is a major feature!

```

BOOST_AUTO(t1, system_clock::now() + seconds(3));
BOOST_AUTO(t2, system_clock::now() + nanoseconds(3));
BOOST_AUTO(t3, min(t1, t2));

```

See the source file [example/min_time_point.cpp](#)

A Tiny Program that Times How Long Until a Key is Struck

```

#include <boost/chrono.hpp>
#include <iostream>
#include <iomanip>

using namespace boost::chrono;

template< class Clock >
class timer
{
    typename Clock::time_point start;
public:
    timer() : start( Clock::now() ) {}
    typename Clock::duration elapsed() const
    {
        return Clock::now() - start;
    }
    double seconds() const
    {
        return elapsed().count() * ((double)Clock::period::num/Clock::period::den);
    }
};

int main()
{
    timer<system_clock> t1;
    timer<steady_clock> t2;
    timer<high_resolution_clock> t3;

    std::cout << "Type the Enter key: ";
    std::cin.get();

    std::cout << std::fixed << std::setprecision(9);
    std::cout << "system_clock-----: "
        << t1.seconds() << " seconds\n";
    std::cout << "steady_clock-----: "
        << t2.seconds() << " seconds\n";
    std::cout << "high_resolution_clock--: "
        << t3.seconds() << " seconds\n";

    system_clock::time_point d4 = system_clock::now();
    system_clock::time_point d5 = system_clock::now();

    std::cout << "\nsystem_clock latency-----: " << (d5 - d4).count() << std::endl;

    steady_clock::time_point d6 = steady_clock::now();
    steady_clock::time_point d7 = steady_clock::now();

    std::cout << "steady_clock latency-----: " << (d7 - d6).count() << std::endl;

    high_resolution_clock::time_point d8 = high_resolution_clock::now();
    high_resolution_clock::time_point d9 = high_resolution_clock::now();

    std::cout << "high_resolution_clock latency--: " << (d9 - d8).count() << std::endl;

    std::time_t now = system_clock::to_time_t(system_clock::now());

    std::cout << "\nsystem_clock::now() reports UTC is "
        << std::asctime(std::gmtime(&now)) << "\n";

    return 0;
}

```

The output of this program run looks like this:

See the source file [example/await_keystroke.cpp](#)

24 Hours Display

In the example above we take advantage of the fact that `time_points` convert as long as they have the same clock, and as long as their internal `durations` convert. We also take advantage of the fact that a `duration` with a floating-point representation will convert from anything. Finally the I/O system discovers the more readable "hours" unit for our `duration<double, ratio<3600>>`.

There are many other ways to format `durations` and `time_points`. For example see [ISO 8601](#). Instead of coding every possibility into `operator<<`, which would lead to significant code bloat for even the most trivial uses, this document seeks to inform the reader how to write custom I/O when desired.

As an example, the function below streams arbitrary `durations` to arbitrary `basic_ostreams` using the format:

```
[ - ]d/hh:mm:ss.cc
```

Where:

- `d` is the number of days
- `h` is the number of hours
- `m` is the number of minutes
- `ss.cc` is the number of seconds rounded to the nearest hundredth of a second

1. `include <boost/chrono/chrono_io.hpp>`
2. `include <ostream>`
3. `include <iostream>`

```

// format duration as [-]d/hh:mm:ss.cc
template <class CharT, class Traits, class Rep, class Period>
std::basic_ostream<CharT, Traits>&
display(std::basic_ostream<CharT, Traits>& os,
        boost::chrono::duration<Rep, Period> d)
{
    using namespace std;
    using namespace boost;

    typedef boost::chrono::duration<long long, boost::ratio<86400> > days;
    typedef boost::chrono::duration<long long, boost::centi> centiseconds;

    // if negative, print negative sign and negate
    if (d < boost::chrono::duration<Rep, Period>(0))
    {
        d = -d;
        os << '-';
    }
    // round d to nearest centiseconds, to even on tie
    centiseconds cs = boost::chrono::duration_cast<centiseconds>(d);
    if (d - cs > boost::chrono::milliseconds(5)
        || (d - cs == boost::chrono::milliseconds(5) && cs.count() & 1))
        ++cs;
    // separate seconds from centiseconds
    boost::chrono::seconds s = boost::chrono::duration_cast<boost::chrono::seconds>(cs);
    cs -= s;
    // separate minutes from seconds
    boost::chrono::minutes m = boost::chrono::duration_cast<boost::chrono::minutes>(s);
    s -= m;
    // separate hours from minutes
    boost::chrono::hours h = boost::chrono::duration_cast<boost::chrono::hours>(m);
    m -= h;
    // separate days from hours
    days dy = boost::chrono::duration_cast<days>(h);
    h -= dy;
    // print d/hh:mm:ss.cc
    os << dy.count() << '/';
    if (h < boost::chrono::hours(10))
        os << '0';
    os << h.count() << ':';
    if (m < boost::chrono::minutes(10))
        os << '0';
    os << m.count() << ':';
    if (s < boost::chrono::seconds(10))
        os << '0';
    os << s.count() << '.';
    if (cs < boost::chrono::centiseconds(10))
        os << '0';
    os << cs.count();
    return os;
}

int main()
{
    using namespace std;
    using namespace boost;

    display(cout, boost::chrono::steady_clock::now().time_since_epoch()
            + boost::chrono::duration<long, boost::mega>(1) << '\n');
    display(cout, -boost::chrono::milliseconds(6) << '\n');
    display(cout, boost::chrono::duration<long, boost::mega>(1) << '\n');
    display(cout, -boost::chrono::duration<long, boost::mega>(1) << '\n');
}

```

The output could be:

```
12/06:03:22.95
-0/00:00:00.01
11/13:46:40.00
-11/13:46:40.00
```

Simulated Thread Interface Demonstration Program

The C++11 standard library's multi-threading library requires the ability to deal with the representation of time in a manner consistent with modern C++ practices. Next is a simulation of this interface.

The non-member sleep functions can be emulated as follows:

```
namespace boost { namespace this_thread {

template <class Rep, class Period>
void sleep_for(const chrono::duration<Rep, Period>& d) {
    chrono::microseconds t = chrono::duration_cast<chrono::microseconds>(d);
    if (t < d)
        ++t;
    if (t > chrono::microseconds(0))
        std::cout << "sleep_for " << t.count() << " microseconds\n";
}

template <class Clock, class Duration>
void sleep_until(const chrono::time_point<Clock, Duration>& t) {
    using namespace chrono;
    typedef time_point<Clock, Duration> Time;
    typedef system_clock::time_point SysTime;
    if (t > Clock::now()) {
        typedef typename common_type<typename Time::duration,
                                     typename SysTime::duration>::type D;
        /* auto */ D d = t - Clock::now();
        microseconds us = duration_cast<microseconds>(d);
        if (us < d)
            ++us;
        SysTime st = system_clock::now() + us;
        std::cout << "sleep_until ";
        detail::print_time(st);
        std::cout << " which is " << (st - system_clock::now()).count() << " microseconds away\n";
    }
}

}}
```

Next is the `boost::thread::timed_mutex` modified functions

```

namespace boost {
struct timed_mutex {
    // ...

    template <class Rep, class Period>
    bool try_lock_for(const chrono::duration<Rep, Period>& d) {
        chrono::microseconds t = chrono::duration_cast<chrono::microseconds>(d);
        if (t <= chrono::microseconds(0))
            return try_lock();
        std::cout << "try_lock_for " << t.count() << " microseconds\n";
        return true;
    }

    template <class Clock, class Duration>
    bool try_lock_until(const chrono::time_point<Clock, Duration>& t)
    {
        using namespace chrono;
        typedef time_point<Clock, Duration> Time;
        typedef system_clock::time_point SysTime;
        if (t <= Clock::now())
            return try_lock();
        typedef typename common_type<typename Time::duration,
            typename Clock::duration>::type D;
        /* auto */ D d = t - Clock::now();
        microseconds us = duration_cast<microseconds>(d);
        SysTime st = system_clock::now() + us;
        std::cout << "try_lock_until ";
        detail::print_time(st);
        std::cout << " which is " << (st - system_clock::now()).count()
            << " microseconds away\n";
        return true;
    }
};
}

```

boost::thread::condition_variable time related function are modified as follows:

```

namespace boost {
struct condition_variable
{
    // ...

    template <class Rep, class Period>
    bool wait_for(mutex&, const chrono::duration<Rep, Period>& d) {
        chrono::microseconds t = chrono::duration_cast<chrono::microseconds>(d);
        std::cout << "wait_for " << t.count() << " microseconds\n";
        return true;
    }

    template <class Clock, class Duration>
    bool wait_until(mutex&, const chrono::time_point<Clock, Duration>& t) {
        using namespace boost::chrono;
        typedef time_point<Clock, Duration> Time;
        typedef system_clock::time_point SysTime;
        if (t <= Clock::now())
            return false;
        typedef typename common_type<typename Time::duration,
            typename Clock::duration>::type D;
        /* auto */ D d = t - Clock::now();
        microseconds us = duration_cast<microseconds>(d);
        SysTime st = system_clock::now() + us;
        std::cout << "wait_until      ";
        detail::print_time(st);
        std::cout << " which is " << (st - system_clock::now()).count()
            << " microseconds away\n";
        return true;
    }
};
}

```

Next follows how simple is the usage of this functions:

```

boost::mutex m;
boost::timed_mutex mut;
boost::condition_variable cv;

using namespace boost;

this_thread::sleep_for(chrono::seconds(3));
this_thread::sleep_for(chrono::nanoseconds(300));
chrono::system_clock::time_point time_limit = chrono::system_clock::now() + chrono::seconds(4) + chrono::milliseconds(500);
this_thread::sleep_until(time_limit);

mut.try_lock_for(chrono::milliseconds(30));
mut.try_lock_until(time_limit);

cv.wait_for(m, chrono::minutes(1)); // real code would put this in a loop
cv.wait_until(m, time_limit); // real code would put this in a loop

// For those who prefer floating-point
this_thread::sleep_for(chrono::duration<double>(0.25));
this_thread::sleep_until(chrono::system_clock::now() + chrono::duration<double>(1.5));

```

See the source file [example/simulated_thread_interface_demo.cpp](#)

IO

French Output

Example use of output in French

```
#include <boost/chrono/chrono_io.hpp>
#include <iostream>
#include <locale>

int main()
{
    using namespace std;
    using namespace boost;
    using namespace boost::chrono;

    cout.imbue(locale(locale(), new duration_punct<char>
        (
            duration_punct<char>::use_long,
            "secondes", "minutes", "heures",
            "s", "m", "h"
        )))
    hours h(5);
    minutes m(45);
    seconds s(15);
    milliseconds ms(763);
    cout << h << ", " << m << ", " << s << " et " << ms << '\n';
}
```

Output is:

```
5 heures, 45 minutes, 15 secondes et 763 millisecondes
```

See the source file [example/french.cpp](#)

External Resources

- | | |
|--|--|
| C++ Standards Committee's current Working Paper | The most authoritative reference material for the library is the C++ Standards Committee's current Working Paper (WP). 20.11 Time utilities "time" |
| N2661 - A Foundation to Sleep On | From Howard E. Hinnant, Walter E. Brown, Jeff Garland and Marc Paterno. Is very informative and provides motivation for key design decisions |
| LGW 934. duration is missing operator% | From Terry Golubiewski. Is very informative and provides motivation for key design decisions |
| LGW 935. clock error handling needs to be specified | From Beman Dawes. This issue has been stated as NAD Future. |

Reference

As `constexpr` will not be supported by some compilers, it is replaced in the code by `BOOST_CONSTEXPR` for `constexpr` functions and `BOOST_STATIC_CONSTEXPR` for struct/class static fields. The same applies to `noexcept` which is replaced by `noexcept` in the code.

The documentation doesn't use these macros.

Header `<boost/chrono/include.hpp>`

Include all the chrono header files.

```
#include <boost/chrono/chrono.hpp>
#include <boost/chrono/chrono_io.hpp>
#include <boost/chrono/process_cpu_clocks.hpp>
#include <boost/chrono/thread_clocks.hpp>
#include <boost/chrono/ceil.hpp>
#include <boost/chrono/floor.hpp>
#include <boost/chrono/round.hpp>
```

Included on the C++11 Recommendation

Header `<boost/chrono.hpp>`

Include only the standard files.

```
#include <boost/chrono/chrono.hpp>
```

Header `<boost/chrono/chrono.hpp>`

Include only the standard files.

```
#include <boost/chrono/duration.hpp>
#include <boost/chrono/time_point.hpp>
#include <boost/chrono/system_clocks.hpp>
#include <boost/chrono/typeof/boost/chrono/chrono.hpp>
```

Limitations and Extensions

At present, there is no known limitation respect to the C++11 standard.

The current implementation provides in addition:

- clock error handling as specified in [clock error handling needs to be specified](#).
- process and thread clocks.

Configuration Macros

How Assert Behaves?

When `BOOST_NO_STATIC_ASSERT` is defined, the user can select the way static assertions are reported. Define

- `BOOST_CHRONO_USES_STATIC_ASSERT`: define it if you want to use `Boost.StaticAssert`.
- `BOOST_CHRONO_USES_MPL_ASSERT`: define it if you want to use `Boost.MPL` static assertions.

- `BOOST_CHRONO_USES_ARRAY_ASSERT`: define it if you want to use internal static assertions.

The default behavior is as `BOOST_CHRONO_USES_ARRAY_ASSERT` was defined.

When `BOOST_CHRONO_USES_MPL_ASSERT` is not defined the following symbols are defined as

```
#define BOOST_CHRONO_A_DURATION_REPRESENTATION_CAN_NOT_BE_A_DURATION \
    "A duration representation can not be a duration"
#define BOOST_CHRONO_SECOND_TEMPLATE_PARAMETER_OF_DURATION_MUST_BE_A_STD_RATIO \
    "Second template parameter of duration must be a boost::ratio"
#define BOOST_CHRONO_DURATION_PERIOD_MUST_BE_POSITIVE \
    "duration period must be positive"
#define BOOST_CHRONO_SECOND_TEMPLATE_PARAMETER_OF_TIME_POINT_MUST_BE_A_BOOST_CHRONO_DURATION \
    "Second template parameter of time_point must be a boost::chrono::duration"
```

Depending on the static assertion used system you will have an hint of the failing assertion either through the symbol or through the text.

Don't provide Hybrid Error Handling

When `BOOST_CHRONO_DONT_PROVIDE_HYBRID_ERROR_HANDLING` is defined the lib don't provides the hybrid error handling prototypes:

```
Clock::time_point Clock::now(system::error_code&ec=boost::throws());
```

This allow to be closer to the standard and to avoid the Boost.System dependency, making possible to have Boost.Chrono as a header-only library.

By default `BOOST_CHRONO_PROVIDE_HYBRID_ERROR_HANDLING` is defined.

How to Build Boost.Chrono as a Header Only Library?

When `BOOST_CHRONO_HEADER_ONLY` is defined the lib is header-only.

If in addition `BOOST_USE_WINDOWS_H` is defined `<windows.h>` is included, otherwise files in `boost/detail/win` are used to reduce the impact of including `<windows.h>`.

However, you will either need to define `BOOST_CHRONO_DONT_PROVIDE_HYBRID_ERROR_HANDLING` or link with Boost.System.

Deprecated IO

Version 2.0.0 deprecates the preceding IO features.

These deprecated features will be provided by default up to boost 1.55. If you don't want to include the deprecated features you could define `BOOST_CHRONO_DONT_PROVIDES_DEPRECATED_IO_SINCE_V2_0_0`. Since 1.55 these features will not be included any more by default. Since this version, if you want to include the deprecated features yet you could define `BOOST_CHRONO_PROVIDES_DEPRECATED_IO_SINCE_V2_0_0`. These deprecated features will be only available until boost 1.58, that is you have 1 year and a half to move to the new features.

time_point<system_clock,D> specialization limitation

Version

`BOOST_CHRONO_VERSION` defines the Boost.Chrono version. The default version is 1. In this case the following breaking or extending macros are defined if the opposite is not requested:

- `BOOST_CHRONO_PROVIDES_DEPRECATED_IO_SINCE_V2_0_0`

The user can request the version 2 by defining `BOOST_CHRONO_VERSION` to 2. In this case the following breaking or extending macros are defined if the opposite is not requested:

- Breaking change BOOST_CHRONO_DONT_PROVIDES_DEPRECATED_IO_SINCE_V2_0_0

The default value for BOOST_CHRONO_VERSION will be changed to 2 since Boost 1.55.

Header `<boost/chrono/duration.hpp>`

This file contains duration specific classes and non-member functions.

```

namespace boost {
  namespace chrono {

    template <class Rep, class Period = ratio<1> > class duration;

  }
  template <class Rep1, class Period1, class Rep2, class Period2>
  struct common_type<duration<Rep1, Period1>,
                    duration<Rep2, Period2> >;

  namespace chrono {

    // customization traits
    template <class Rep> struct treat_as_floating_point;
    template <class Rep> struct duration_values;

    // duration arithmetic
    template <class Rep1, class Period1, class Rep2, class Period2>
    constexpr
    typename common_type<duration<Rep1, Period1>, duration<Rep2, Period2> >::type
    operator+(
      const duration<Rep1, Period1>& lhs,
      const duration<Rep2, Period2>& rhs);

    template <class Rep1, class Period1, class Rep2, class Period2>
    constexpr
    typename common_type<duration<Rep1, Period1>, duration<Rep2, Period2> >::type
    operator-(
      const duration<Rep1, Period1>& lhs,
      const duration<Rep2, Period2>& rhs);

    template <class Rep1, class Period, class Rep2>
    constexpr
    duration<typename common_type<Rep1, Rep2>::type, Period>
    operator*(
      const duration<Rep1, Period>& d,
      const Rep2& s);

    template <class Rep1, class Period, class Rep2>
    constexpr
    duration<typename common_type<Rep1, Rep2>::type, Period>
    operator*(
      const Rep1& s,
      const duration<Rep2, Period>& d);

    template <class Rep1, class Period, class Rep2>
    constexpr
    duration<typename common_type<Rep1, Rep2>::type, Period>
    operator/(
      const duration<Rep1, Period>& d,
      const Rep2& s);

    template <class Rep1, class Period1, class Rep2, class Period2>
    constexpr
  
```

```

typename common_type<Rep1, Rep2>::type
operator/(
    const duration<Rep1, Period1>& lhs,
    const duration<Rep2, Period2>& rhs);

#ifdef BOOST_CHRONO_EXTENSIONS
// Used to get frequency of events
template <class Rep1, class Rep2, class Period>
constexpr
double operator/(
    const Rep1& s,
    const duration<Rep2, Period>& d);
#endif

// duration comparisons
template <class Rep1, class Period1, class Rep2, class Period2>
constexpr bool operator==(
    const duration<Rep1, Period1>& lhs,
    const duration<Rep2, Period2>& rhs);

template <class Rep1, class Period1, class Rep2, class Period2>
constexpr bool operator!=(
    const duration<Rep1, Period1>& lhs,
    const duration<Rep2, Period2>& rhs);

template <class Rep1, class Period1, class Rep2, class Period2>
constexpr bool __duration_op_le_1(
    const duration<Rep1, Period1>& lhs,
    const duration<Rep2, Period2>& rhs);
template <class Rep1, class Period1, class Rep2, class Period2>
constexpr bool operator<=(
    const duration<Rep1, Period1>& lhs,
    const duration<Rep2, Period2>& rhs);

template <class Rep1, class Period1, class Rep2, class Period2>
constexpr bool operator>(
    const duration<Rep1, Period1>& lhs,
    const duration<Rep2, Period2>& rhs);
template <class Rep1, class Period1, class Rep2, class Period2>
constexpr bool operator>=(
    const duration<Rep1, Period1>& lhs,
    const duration<Rep2, Period2>& rhs);

// duration_cast

template <class ToDuration, class Rep, class Period>
constexpr
ToDuration duration_cast(const duration<Rep, Period>& d);

// convenience typedefs
typedef duration<boost::int_least64_t, nano> nanoseconds; // at least 64 bits needed
typedef duration<boost::int_least64_t, micro> microseconds; // at least 55 bits needed
typedef duration<boost::int_least64_t, milli> milliseconds; // at least 45 bits needed
typedef duration<boost::int_least64_t> seconds; // at least 35 bits needed
typedef duration<boost::int_least32_t, ratio< 60> > minutes; // at least 29 bits needed
typedef duration<boost::int_least32_t, ratio<3600> > hours; // at least 23 bits needed
}
}

```

Time-related Traits

Metafunction `treat_as_floating_point<>`

```
template <class Rep> struct treat_as_floating_point
    : boost::is_floating_point<Rep> {};
```

The `duration` template uses the `treat_as_floating_point` trait to help determine if a `duration` with one tick period can be converted to another `duration` with a different tick period. If `treat_as_floating_point<Rep>::value` is true, then `Rep` is a floating-point type and implicit conversions are allowed among `durations`. Otherwise, the implicit convertibility depends on the tick periods of the `durations`. If `Rep` is a class type which emulates a floating-point type, the author of `Rep` can specialize `treat_as_floating_point` so that `duration` will treat this `Rep` as if it were a floating-point type. Otherwise `Rep` is assumed to be an integral type, or a class emulating an integral type.

Class Template `duration_values`

```
template <class Rep>
struct duration_values
{
public:
    static constexpr Rep zero();
    static constexpr Rep max();
    static constexpr Rep min();
};
```

The `duration` template uses the `duration_values` trait to construct special values of the `duration`'s representation (`Rep`). This is done because the representation might be a class type with behavior which requires some other implementation to return these special values. In that case, the author of that class type should specialize `duration_values` to return the indicated values.

Static Member Function `zero()`

```
static constexpr Rep zero();
```

Returns: `Rep(0)`. **Note:** `Rep(0)` is specified instead of `Rep()` since `Rep()` may have some other meaning, such as an uninitialized value.

Remarks: The value returned corresponds to the additive identity.

Static Member Function `max()`

```
static constexpr Rep max();
```

Returns: `numeric_limits<Rep>::max()`.

Remarks: The value returned compares greater than `zero()`.

Static Member Function `min()`

```
static constexpr Rep min();
```

Returns: `numeric_limits<Rep>::lowest()`.

Remarks: The value returned compares less than or equal to `zero()`.

common_type Specialization

```
template <class Rep1, class Period1, class Rep2, class Period2>
struct common_type<chrono::duration<Rep1, Period1>, chrono::duration<Rep2, Period2> >
{
    typedef chrono::duration<typename common_type<Rep1, Rep2>::type, see below> type;
};
```

The period of the `duration` indicated by this specialization of `common_type` is the greatest common divisor of `Period1` and `Period2`. This can be computed by forming a `ratio` of the greatest common divisor of `Period1::num` and `Period2::num`, and the least common multiple of `Period1::den` and `Period2::den`.

Note: The typedef type is the `duration` with the largest tick period possible where both `duration` arguments will convert to it without requiring a division operation. The representation of this type is intended to be able to hold any value resulting from this conversion, with the possible exception of round-off error when floating-point `durations` are involved (but not truncation error).

Class Template `duration<>`

A `duration` measures time between two points in time (`time_point`). A `duration` has a representation which holds a count of ticks, and a tick period. The tick period is the amount of time which occurs from one tick to another in units of a second. It is expressed as a rational constant using `ratio`.

```

namespace boost { namespace chrono {

    template <class Rep, class Period>
    class duration {
    public:
        typedef Rep rep;
        typedef Period period;
    private:
        rep rep_; // exposition only
    public:
        constexpr duration();
        template <class Rep2>
        constexpr explicit duration(const Rep2& r);

        template <class Rep2, class Period2>
        constexpr duration(const duration<Rep2, Period2>& d);

        duration& operator=(const duration&) = default;

        constexpr rep count() const;

        constexpr duration __duration__op_plus();
        constexpr duration __duration__op_minus();
        duration& operator++();
        duration operator++(int);
        duration& operator--();
        duration operator--(int);

        duration& operator+=(const duration& d);
        duration& operator-=(const duration& d);

        duration& operator*==(const rep& rhs);
        duration& operator/=(const rep& rhs);
        duration& operator%=(const rep& rhs);
        duration& operator%=(const duration& rhs);

        static constexpr duration zero();
        static constexpr duration min();
        static constexpr duration max();
    };
}}

```

Rep must be an arithmetic type, or a class emulating an arithmetic type, compile diagnostic otherwise. If `duration` is instantiated with the type of Rep being a `duration`, compile diagnostic is issued.

Period must be an instantiation of `ratio`, compile diagnostic otherwise.

`Period::num` must be positive, compile diagnostic otherwise.

Examples:

- `duration<long, ratio<60> >` holds a count of minutes using a long.
- `duration<long long, milli>` holds a count of milliseconds using a long long.
- `duration<double, ratio<1, 30> >` holds a count using a double with a tick period of 1/30 second (a tick frequency of 30 Hz).

The following members of `duration` do not throw an exception unless the indicated operations on the representations throw an exception.

Constructor `duration()`

```
constexpr duration();
```

Effects: Constructs an object of type `duration` from `duration_values<rep>::zero()`.

Constructor `duration(const Rep2&)`

```
template <class Rep2>
constexpr explicit duration(const Rep2& r);
```

Remarks: `Rep2` is implicitly convertible to `rep`, and

- `treat_as_floating_point<rep>::value` is true, or
- `!treat_as_floating_point<rep>::value && !treat_as_floating_point<Rep2>::value` is true.

If these constraints are not met, this constructor will not participate in overload resolution. **Note:** This requirement prevents construction of an integral-based `duration` with a floating-point representation. Such a construction could easily lead to confusion about the value of the `duration`.

Example:

```
duration<int, milli> d(3.5); // do not compile
duration<int, milli> d(3);  // ok
```

Effects: Constructs an object of type `duration`.

Post Conditions: `count() == static_cast<rep>(r)`.

Constructor `duration(const duration&)`

```
template <class Rep2, class Period2>
constexpr duration(const duration<Rep2, Period2>& d);
```

Remarks: `treat_as_floating_point<rep>::value`, or `ratio_divide<Period2, period>::type::den == 1`, else this constructor will not participate in overload resolution. **note** This requirement prevents implicit truncation error when converting between integral-based `durations`. Such a construction could easily lead to confusion about the value of the `duration`.

Example:

```
duration<int, milli> ms(3);
duration<int, micro> us = ms; // ok
duration<int, milli> ms2 = us; // do not compile
```

Effects: Constructs an object of type `duration`, constructing `rep_` from `duration_cast<duration>(d).count()`.

Member Function `count() const`

```
constexpr rep count() const;
```

Returns: `rep_`.

Member Function `operator+() const`

```
constexpr duration operator+() const;
```

Returns: *this.

Member Function operator-() const

```
constexpr duration operator-() const;
```

Returns: duration(-rep_).

Member Function operator++()

```
duration& operator++();
```

Effects: ++rep_.

Returns: *this.

Member Function operator++(int)

```
duration operator++(int);
```

Returns: duration(rep_++).

Member Function operator--()

```
duration& operator--();
```

Effects: --rep_.

Returns: *this.

Member Function operator--(int)

```
duration operator--(int);
```

Returns: duration(rep_--).

Member Function operator+=(const duration&)

```
duration& operator+=(const duration& d);
```

Effects: rep_ += d.count().

Returns: *this.

Member Function operator-=(const duration&)

```
duration& operator-=(const duration& d);
```

Effects: rep_ -= d.count().

Returns: *this.

Member Function operator%=(const duration&)

```
duration& operator%=(const duration& d);
```

Effects: `rep_ %= d.count()`.

Returns: `*this`.

Member Function `operator*=(const rep&)`

```
duration& operator*=(const rep& rhs);
```

Effects: `rep_ *= rhs`.

Returns: `*this`.

Member Function `operator/=(const rep&)`

```
duration& operator/=(const rep& rhs);
```

Effects: `rep_ /= rhs`.

Returns: `*this`.

Member Function `operator%=(const rep&)`

```
duration& operator%=(const rep& rhs);
```

Effects: `rep_ %= rhs`.

Returns: `*this`.

Static Member Function `zero()`

```
static constexpr duration zero();
```

Returns: `duration(duration_values<rep>::zero())`.

Static Member Function `min()`

```
static constexpr duration min();
```

Returns: `duration(duration_values<rep>::min())`.

Static Member Function `max()`

```
static constexpr duration max();
```

Returns: `duration(duration_values<rep>::max())`.

duration Non-Member Arithmetic

Non-Member Function `operator+(duration, duration)`

```
template <class Rep1, class Period1, class Rep2, class Period2>
constexpr
typename common_type<duration<Rep1, Period1>, duration<Rep2, Period2> >::type
operator+(const duration<Rep1, Period1>& lhs, const duration<Rep2, Period2>& rhs);
```

Returns: `CD(CD(lhs).count() + CD(rhs).count())` where CD is the type of the return value.

Non-Member Function operator-(duration,duration)

```
template <class Rep1, class Period1, class Rep2, class Period2>
constexpr
typename common_type<duration<Rep1, Period1>, duration<Rep2, Period2> >::type
operator-(const duration<Rep1, Period1>& lhs, const duration<Rep2, Period2>& rhs);
```

Returns: $CD(CD(lhs).count() - CD(rhs).count())$ where CD is the type of the return value.

Non-Member Function operator*(duration,Rep1)

```
template <class Rep1, class Period, class Rep2>
constexpr
duration<typename common_type<Rep1, Rep2>::type, Period>
operator*(const duration<Rep1, Period>& d, const Rep2& s);
```

Requires: Let CR represent the `common_type` of Rep1 and Rep2. This function will not participate in overload resolution unless both Rep1 and Rep2 are implicitly convertible to CR.

Returns: $CD(CD(d).count() * s)$ where CD is the type of the return value.

Non-Member Function operator*(Rep1,duration)

```
template <class Rep1, class Period, class Rep2>
constexpr
duration<typename common_type<Rep1, Rep2>::type, Period>
operator*(const Rep1& s, const duration<Rep2, Period>& d);
```

Requires: Let CR represent the `common_type` of Rep1 and Rep2. This function will not participate in overload resolution unless both Rep1 and Rep2 are implicitly convertible to CR.

Returns: $d * s$.

Non-Member Function operator/(duration,Rep2)

```
template <class Rep1, class Period, class Rep2>
constexpr
duration<typename common_type<Rep1, Rep2>::type, Period>
operator/(const duration<Rep1, Period>& d, const Rep2& s);
```

Requires: Let CR represent the `common_type` of Rep1 and Rep2. This function will not participate in overload resolution unless both Rep1 and Rep2 are implicitly convertible to CR, and Rep2 is not an instantiation of `duration`.

Returns: $CD(CD(d).count() / s)$ where CD is the type of the return value.

Non-Member Function operator/(duration,duration)

```
template <class Rep1, class Period1, class Rep2, class Period2>
constexpr
typename common_type<Rep1, Rep2>::type
operator/(const duration<Rep1, Period1>& lhs, const duration<Rep2, Period2>& rhs);
```

Remarks: Let CD represent the `common_type` of the two `duration` arguments. **Returns:** Returns $CD(lhs).count() / CD(rhs).count()$.

Non-Member Function operator/(Rep1,duration)

Included only if `BOOST_CHRONO_EXTENSIONS` is defined.

This overloading could be used to get the frequency of an event counted by Rep1.

```
template <class Rep1, class Rep2, class Period>
constexpr
double operator/(const Rep1& s, const duration<Rep2, Period>& d);
```

Remarks: Let CR represent the `common_type` of Rep1 and Rep2. This function will not participate in overload resolution unless both Rep1 and Rep2 are implicitly convertible to CR, and Rep1 is not an instantiation of `duration`. Let CD represent `duration<CR,Period>`.

Returns: `CR(s)/CD(d).count()` where CD is the type of the return value.

Non-Member Function `operator%(duration,Rep2)`

```
template <class Rep1, class Period, class Rep2>
constexpr
duration<typename common_type<Rep1, Rep2>::type, Period>
operator%(const duration<Rep1, Period>& d, const Rep2& s);
```

Remarks: Let CR represent the `common_type` of Rep1 and Rep2. This function will not participate in overload resolution unless Rep2 must be implicitly convertible to CR and Rep2 must not be an instantiation of `duration`.

Returns: `CD(CD(d).count() % s)` where CD is the type of the return value.

Non-Member Function `operator%(duration,duration)`

```
template <class Rep1, class Period1, class Rep2, class Period2>
constexpr
typename common_type<duration<Rep1, Period1>, duration<Rep2, Period2> >::type
operator%(const duration<Rep1, Period1>& lhs,
          const duration<Rep2, Period2>& rhs);
```

Remarks: This function will not participate in overload resolution unless

Returns: `CD(CD(lhs).count() % CD(rhs).count())` where CD is the type of the return value.

`duration` Non-Member Comparaisons

Non-Member Function `operator==(duration,duration)`

```
template <class Rep1, class Period1, class Rep2, class Period2>
bool operator==(const duration<Rep1, Period1>& lhs,
                const duration<Rep2, Period2>& rhs);
```

Returns: Let CD represent the `common_type` of the two `duration` arguments.

Returns: Returns `CD(lhs).count() == CD(rhs).count()`

Non-Member Function `operator!=(duration,duration)`

```
template <class Rep1, class Period1, class Rep2, class Period2>
bool operator!=(const duration<Rep1, Period1>& lhs,
                const duration<Rep2, Period2>& rhs);
```

Returns: `!(lhs == rhs)`.

Non-Member Function operator<(duration,duration)

```
template <class Rep1, class Period1, class Rep2, class Period2>
bool operator< (const duration<Rep1, Period1>& lhs,
               const duration<Rep2, Period2>& rhs);
```

Returns: Let CD represent the `common_type` of the two `duration` arguments. Returns `CD(lhs).count() < CD(rhs).count()`

Non-Member Function operator<=(duration,duration)

```
template <class Rep1, class Period1, class Rep2, class Period2>
bool operator<=(const duration<Rep1, Period1>& lhs,
               const duration<Rep2, Period2>& rhs);
```

Returns: `!(rhs < lhs)`.

Non-Member Function operator>(duration,duration)

```
template <class Rep1, class Period1, class Rep2, class Period2>
bool operator> (const duration<Rep1, Period1>& lhs,
               const duration<Rep2, Period2>& rhs);
```

Returns: `rhs < lhs`.

Non-Member Function operator>=(duration,duration)

```
template <class Rep1, class Period1, class Rep2, class Period2>
bool operator>=(const duration<Rep1, Period1>& lhs,
               const duration<Rep2, Period2>& rhs);
```

Returns: `!(lhs < rhs)`.

Non-Member Function duration_cast(duration)

```
template <class ToDuration, class Rep, class Period>
ToDuration duration_cast(const duration<Rep, Period>& d);
```

Requires: This function will not participate in overload resolution unless `ToDuration` is an instantiation of `duration`.

Returns: Forms `CF` which is a ratio resulting from `ratio_divide<Period, typename ToDuration::period>::type`. Let `CR` be the `common_type` of `ToDuration::rep`, `Rep`, and `intmax_t`.

- If `CF::num == 1` and `CF::den == 1`, then returns `ToDuration(static_cast<typename ToDuration::rep>(d.count()))`
- else if `CF::num != 1` and `CF::den == 1`, then returns `ToDuration(static_cast<typename ToDuration::rep>(static_cast<CR>(d.count()) * static_cast<CR>(CF::num)))`
- else if `CF::num == 1` and `CF::den != 1`, then returns `ToDuration(static_cast<typename ToDuration::rep>(static_cast<CR>(d.count()) / static_cast<CR>(CF::den)))`
- else returns `ToDuration(static_cast<typename ToDuration::rep>(static_cast<CR>(d.count()) * static_cast<CR>(CF::num) / static_cast<CR>(CF::den)))`

Remarks: This function does not rely on any implicit conversions. All conversions must be accomplished through `static_cast`. The implementation avoids all multiplications or divisions when it is known at compile-time that it can be avoided because one or more arguments are 1. All intermediate computations are carried out in the widest possible representation and only converted to the destination representation at the final step.

duration typedefs

```
// convenience typedefs
typedef duration<boost::int_least64_t, nano> nanoseconds; // at least 64 bits needed
typedef duration<boost::int_least64_t, micro> microseconds; // at least 55 bits needed
typedef duration<boost::int_least64_t, milli> milliseconds; // at least 45 bits needed
typedef duration<boost::int_least64_t> seconds; // at least 35 bits needed
typedef duration<boost::int_least32_t, ratio< 60> > minutes; // at least 29 bits needed
typedef duration<boost::int_least32_t, ratio<3600> > hours; // at least 23 bits needed
```

clock Requirements

A clock represents a bundle consisting of a [duration](#), a [time_point](#), and a function `now()` to get the current [time_point](#). A clock must meet the requirements in the following Table.

In this table C1 and C2 denote `clock` types. `t1` and `t2` are values returned from `C1::now()` where the call returning `t1` happens before the call returning `t2` and both of these calls occur before `C1::time_point::max()`. (note This means C1 did not wrap around between `t1` and `t2`).

Table 1. Clock Requirements

| expression | return type | operational semantics |
|-----------------------------|--|---|
| <code>C1::rep</code> | An arithmetic type or class emulating an arithmetic type. | The representation type of the duration and time_point . |
| <code>C1::period</code> | <code>ratio</code> | The tick period of the clock in seconds. |
| <code>C1::duration</code> | <code>chrono::duration<C1::rep, C1::period></code> | The duration type of the clock. |
| <code>C1::time_point</code> | <code>chrono::time_point<C1></code> or <code>chrono::time_point<C2, C1::duration></code> | The time_point type of the clock. Different clocks are permitted to share a time_point definition if it is valid to compare their time_points by comparing their respective durations . C1 and C2 must refer to the same epoch. |
| <code>C1::is_steady</code> | <code>constexpr bool</code> | true if <code>t1 <= t2</code> is always true, else false. Note: A clock that can be adjusted backwards is not steady |
| <code>C1::now()</code> | <code>C1::time_point</code> | Returns a time_point representing the current point in time. |

Models of `clock`:

- [system_clock](#)
- [steady_clock](#)
- [high_resolution_clock](#)
- [process_real_cpu_clock](#)
- [process_user_cpu_clock](#)
- [process_system_cpu_clock](#)

- [process_cpu_clock](#)
- [thread_clock](#)

TrivialClock Requirements

A type TC meets the TrivialClock requirements if:

- TC satisfies the Clock requirements,
- the types `TC::rep`, `TC::duration`, and `TC::time_point` satisfy the requirements of `EqualityComparable`, `LessThanComparable`, `DefaultConstructible`, `CopyConstructible`, `CopyAssignable`, `Destructible`, and the requirements of numeric types.



Note

This means, in particular, that operations on these types will not throw exceptions.

- lvalues of the types `TC::rep`, `TC::duration`, and `TC::time_point` are swappable,
- the function `TC::now()` does not throw exceptions, and
- the type `TC::time_point::clock` meets the TrivialClock requirements, recursively.

Models of TrivialClock:

- [system_clock](#)
- [steady_clock](#)
- [high_resolution_clock](#)
- [process_real_cpu_clock](#)
- [process_user_cpu_clock](#)
- [process_system_cpu_clock](#)
- [thread_clock](#)

EcClock Requirements

A type EcC meets the EcClock requirements if

- TC satisfies the TrivialClock requirements, and
- it add `now()` interfaces allowing to recover internal error codes as described in the following table.

In this table C1 denotes a EcClock type and `ec` is an instance of a `boost::system::error_code`.

Table 2. Clock Requirements

| expression | return type | operational semantics |
|---------------------------------------|-----------------------------|--|
| <code>C1::now(ec)</code> | <code>C1::time_point</code> | Returns a time_point representing the current point in time. <code>ec</code> will store the error-code in case something was wrong internally. |
| <code>C1::now(boost::throws())</code> | <code>C1::time_point</code> | Returns a time_point representing the current point in time. Throws a <code>boost::system::system_error</code> exception in case something was wrong internally. |

Models of [Clock](#):

- [system_clock](#)
- [steady_clock](#)
- [high_resolution_clock](#)
- [process_real_cpu_clock](#)
- [process_user_cpu_clock](#)
- [process_system_cpu_clock](#)
- [process_cpu_clock](#)
- [thread_clock](#)

Header `<boost/chrono/time_point.hpp>`

This file contains [time_point](#) specific classes and non-member functions.

```

namespace boost {
  namespace chrono {

    template <class Clock, class Duration = typename Clock::duration>
    class time_point;

  }
  template <class Clock, class Duration1, class Duration2>
  struct common_type<time_point<Clock, Duration1>,
                    time_point<Clock, Duration2> >;

  namespace chrono {

    // time_point arithmetic
    template <class Clock, class Duration1, class Rep2, class Period2>
    constexpr time_point<Clock, typename common_type<Duration1, duration<Rep2, Period2> >::type>
    operator+(const time_point<Clock, Duration1>& lhs,
              const duration<Rep2, Period2>& rhs);

    template <class Rep1, class Period1, class Clock, class Duration2>
    constexpr time_point<Clock, typename common_type<duration<Rep1, Period1>, Duration2>::type>
    operator+(const duration<Rep1, Period1>& lhs,
              const time_point<Clock, Duration2>& rhs);

    template <class Clock, class Duration1, class Rep2, class Period2>
    constexpr time_point<Clock, typename common_type<Duration1, duration<Rep2, Period2> >::type>
    operator-(const time_point<Clock, Duration1>& lhs,
              const duration<Rep2, Period2>& rhs);

    template <class Clock, class Duration1, class Duration2>
    constexpr typename common_type<Duration1, Duration2>::type
    operator-(const time_point<Clock, Duration1>& lhs,
              const time_point<Clock, Duration2>& rhs);

    // time_point comparisons
    template <class Clock, class Duration1, class Duration2>
    constexpr bool
    operator==(const time_point<Clock, Duration1>& lhs,
               const time_point<Clock, Duration2>& rhs);
    template <class Clock, class Duration1, class Duration2>
    constexpr bool
    operator!=(const time_point<Clock, Duration1>& lhs,
               const time_point<Clock, Duration2>& rhs);
    template <class Clock, class Duration1, class Duration2>
    constexpr bool
    operator<(const time_point<Clock, Duration1>& lhs,
              const time_point<Clock, Duration2>& rhs);
    template <class Clock, class Duration1, class Duration2>
    constexpr bool
    operator<=(const time_point<Clock, Duration1>& lhs,
               const time_point<Clock, Duration2>& rhs);
    template <class Clock, class Duration1, class Duration2>
    constexpr bool
    operator>(const time_point<Clock, Duration1>& lhs,
              const time_point<Clock, Duration2>& rhs);
    template <class Clock, class Duration1, class Duration2>
    constexpr bool
    operator>=(const time_point<Clock, Duration1>& lhs,
               const time_point<Clock, Duration2>& rhs);

    // time_point_cast

```

```
template <class ToDuration, class Clock, class Duration>
constexpr time_point<Clock, ToDuration>
time_point_cast(const time_point<Clock, Duration>& t);
}
}
```

common_type specialization

```
template <class Clock, class Duration1, class Duration2>
struct common_type<chrono::time_point<Clock, Duration1>, chrono::time_point<Clock, Duration2> >
{
    typedef chrono::time_point<Clock, typename common_type<Duration1, Duration2>::type> type;
};
```

The `common_type` of two `time_points` is a `time_point` with the same `Clock` (both have the same `Clock`), and the `common_type` of the two `durations`.

Class template `time_point<>`

A `time_point` represents a point in time with respect to a specific clock.

```

template <class Clock, class Duration>
class time_point {
public:
    typedef Clock                clock;
    typedef Duration             duration;
    typedef typename duration::rep    rep;
    typedef typename duration::period period;
private:
    duration d_; // exposition only
public:
    constexpr time_point();

    constexpr explicit time_point(const duration& d);

    // conversions
    template <class Duration2>
    constexpr
    time_point(const time_point<clock, Duration2>& t);

    // observer
    constexpr duration time_since_epoch() const;

    // arithmetic

#ifdef BOOST_CHRONO_EXTENSIONS
    constexpr time_point operator+();
    constexpr time_point operator-();
    time_point& operator++();
    time_point operator++(int);
    time_point& operator--();
    time_point operator--(int);

    time_point& __time_point__op_plus_eq_1(const rep& d);
    time_point& operator-=(const rep& d);
#endif

    time_point& __time_point__op_plus_eq_2(const duration& d);
    time_point& operator-=(const duration& d);

    // special values

    static constexpr time_point min();
    static constexpr time_point max();
};

```

Clock must meet the [Clock](#) requirements.

Duration must be an instantiation of [duration](#), compile diagnostic otherwise.

Constructor [time_point\(\)](#)

```
constexpr time_point();
```

Effects: Constructs an object of [time_point](#), initializing `d_` with `duration::zero()`. This [time_point](#) represents the epoch.

Constructor [time_point\(const duration&\)](#)

```
constexpr time_point(const duration& d);
```

Effects: Constructs an object of [time_point](#), initializing `d_` with `d`. This [time_point](#) represents the epoch + `d`.

Copy Constructor `time_point(const time_point&)`

```
template <class Duration2>
constexpr
time_point(const time_point<clock, Duration2>& t);
```

Requires: This function will not participate in overload resolution unless `Duration2` is implicitly convertible to `duration`.

Effects: Constructs an object of `time_point`, initializing `d_` with `t.time_since_epoch()`.

Member Function `time_since_epoch() const`

```
constexpr duration time_since_epoch() const;
```

Returns: `d_`.

Member Function `operator+() const`

```
constexpr time_point operator+() const;
```

Returns: `*this`.

Member Function `operator-() const`

```
constexpr time_point operator-() const;
```

Returns: `time_point(-d_)`.

Member Function `operator++()`

```
time_point& operator++();
```

Effects: `++d_`.

Returns: `*this`.

Member Function `operator++(int)`

```
time_point operator++(int);
```

Returns: `time_point(d_++)`.

Member Function `operator--()`

```
time_point& operator--();
```

Effects: `--d_`.

Returns: `*this`.

Member Function `operator--(int)`

```
time_point operator--(int);
```

Returns: `time_point(d_--)`.

Member Function operator+=(const rep&)

```
time_point& operator+=(const rep& r);
```

Effects: d_ += duration(r).

Returns: *this.

Member Function operator-=(const rep&)

```
time_point& operator-=(const rep& r);
```

Effects: d_ -= duration(r)

Returns: *this.

Member Function operator+=

```
time_point& operator+=(const duration& d);
```

Effects: d_ += d.

Returns: *this.

Member Function operator-=

```
time_point& operator-=(const duration& d);
```

Effects: d_ -= d

Returns: *this.

Static Member Function min

```
static constexpr time_point min();
```

Returns: time_point(duration::min()).

Static Member Function max

```
static constexpr time_point max();
```

Returns: time_point(duration::max()).

time_point non-member arithmetic**Non-Member Function operator+(time_point, duration)**

```
template <class Clock, class Duration1, class Rep2, class Period2>
constexpr
time_point<Clock, typename common_type<Duration1, duration<Rep2, Period2> >::type>
operator+(const time_point<Clock, Duration1>& lhs,
          const duration<Rep2, Period2>& rhs);
```

Returns: CT(lhs.time_since_epoch() + rhs) where CT is the type of the return value.

Non-Member Function operator+(duration,time_point)

```
template <class Rep1, class Period1, class Clock, class Duration2>
constexpr
time_point<Clock, typename common_type<duration<Rep1, Period1>, Duration2>::type>
operator+(const duration<Rep1, Period1>& lhs,
          const time_point<Clock, Duration2>& rhs);
```

Returns: rhs + lhs.

Non-Member Function operator-(time_point,duration)

```
template <class Clock, class Duration1, class Rep2, class Period2>
constexpr
time_point<Clock, typename common_type<Duration1, duration<Rep2, Period2> >::type>
operator-(const time_point<Clock, Duration1>& lhs,
          const duration<Rep2, Period2>& rhs);
```

Returns: lhs + (-rhs).

Non-Member Function operator-(time_point,time_point)

```
template <class Clock, class Duration1, class Duration2>
constexpr
typename common_type<Duration1, Duration2>::type
operator-(const time_point<Clock, Duration1>& lhs,
          const time_point<Clock, Duration2>& rhs);
```

Returns: lhs.time_since_epoch() - rhs.time_since_epoch().

time_point non-member comparisons**Non-Member Function operator==(time_point,time_point)**

```
template <class Clock, class Duration1, class Duration2>
constexpr
bool operator==(const time_point<Clock, Duration1>& lhs,
                const time_point<Clock, Duration2>& rhs);
```

Returns: lhs.time_since_epoch() == rhs.time_since_epoch().

Non-Member Function operator!=(time_point,time_point)

```
template <class Clock, class Duration1, class Duration2>
constexpr
bool operator!=(const time_point<Clock, Duration1>& lhs,
                const time_point<Clock, Duration2>& rhs);
```

Returns: !(lhs == rhs).

Non-Member Function operator<(time_point,time_point)

```
template <class Clock, class Duration1, class Duration2>
constexpr
bool operator<(const time_point<Clock, Duration1>& lhs,
               const time_point<Clock, Duration2>& rhs);
```

Returns: lhs.time_since_epoch() < rhs.time_since_epoch().

Non-Member Function operator<=(time_point,time_point)

```
template <class Clock, class Duration1, class Duration2>
constexpr
bool operator<=(const time_point<Clock, Duration1>& lhs,
                const time_point<Clock, Duration2>& rhs);
```

Returns: !(rhs < lhs).

Non-Member Function operator>(time_point,time_point)

```
template <class Clock, class Duration1, class Duration2>
constexpr
bool operator>(const time_point<Clock, Duration1>& lhs,
               const time_point<Clock, Duration2>& rhs);
```

Returns: rhs < lhs.

Non-Member Function operator>=(time_point,time_point)

```
template <class Clock, class Duration1, class Duration2>
constexpr
bool operator>=(const time_point<Clock, Duration1>& lhs,
                const time_point<Clock, Duration2>& rhs);
```

Returns: !(lhs < rhs).

Non-Member Function time_point_cast(time_point)

```
template <class ToDuration, class Clock, class Duration>
constexpr
time_point<Clock, ToDuration> time_point_cast(const time_point<Clock, Duration>& t);
```

Requires: This function will not participate in overload resolution unless ToDuration is an instantiation of [duration](#).

Returns: time_point<Clock, ToDuration>(duration_cast<ToDuration>(t.time_since_epoch())).

Header <boost/chrono/system_clocks.hpp>

This file contains the standard clock classes. The types defined in this section satisfy the [TrivialClock](#) requirements

```
namespace boost {
  namespace chrono {

    // Clocks
    class system_clock;
    class steady_clock;
    class high_resolution_clock;

    template <class CharT>
    struct clock_string<system_clock, CharT>;
    template <class CharT>
    struct clock_string<steady_clock, CharT>;

  }
}
```

Class `system_clock`

The `system_clock` class provides a means of obtaining the current wall-clock time from the system-wide real-time clock. The current time can be obtained by calling `system_clock::now()`. Instances of `system_clock::time_point` can be converted to and from `time_t` with the `system_clock::to_time_t()` and `system_clock::to_time_point()` functions. If system clock is not steady, a subsequent call to `system_clock::now()` may return an earlier time than a previous call (e.g. if the operating system clock is manually adjusted, or synchronized with an external clock).

The current implementation of `system_clock` is related an epoch (midnight UTC of January 1, 1970), but this is not in the contract. You need to use the static function `static`

```
std::time_t to_time_t(const time_point& t);
```

which returns a `time_t` type that is based on midnight UTC of January 1, 1970.

```
class system_clock {
public:
    typedef see bellow          duration;
    typedef duration::rep       rep;
    typedef duration::period    period;
    typedef chrono::time_point<system_clock> time_point;
    static constexpr bool is_steady = false;

    static time_point now() noexcept;
    static time_point now(system::error_code & ec);

    // Map to C API
    static std::time_t to_time_t(const time_point& t) noexcept;
    static time_point from_time_t(std::time_t t) noexcept;
};
```

`system_clock` satisfy the `Clock` requirements:

- `system_clock::duration::min() < system_clock::duration::zero()` is true.
- The nested `duration` typedef has a resolution that depends on the one provided by the platform.

Static Member Function `to_time_t(time_point)`

```
time_t to_time_t(const time_point& t) noexcept;
```

Returns: A `time_t` such that the `time_t` and `t` represent the same point in time, truncated to the coarser of the precisions among `time_t` and `time_point`.

Static Member Function `from_time_t(time_t)`

```
time_point from_time_t(time_t t) noexcept;
```

Returns: A `time_point` such that the `time_point` and `t` represent the same point in time, truncated to the coarser of the precisions among `time_point` and `time_t`.

Macro `BOOST_CHRONO_HAS_CLOCK_STEADY`

Defined if the platform support steady clocks.

Class `steady_clock`

`steady_clock` satisfy the `Clock` requirements.

`steady_clock` class provides access to the system-wide steady clock. The current time can be obtained by calling `steady_clock::now()`. There is no fixed relationship between values returned by `steady_clock::now()` and wall-clock time.

```

#ifdef BOOST_HAS_CLOCK_STEADY
    class steady_clock {
    public:
        typedef nanoseconds          duration;
        typedef duration::rep        rep;
        typedef duration::period    period;
        typedef chrono::time_point<steady_clock> time_point;
        static constexpr bool is_steady = true;

        static time_point now() noexcept;
        static time_point now(system::error_code & ec);
    };
#endif

```

Class `high_resolution_clock`

`high_resolution_clock` satisfy the `Clock` requirements.

```

#ifdef BOOST_CHRONO_HAS_CLOCK_STEADY
    typedef steady_clock high_resolution_clock; // as permitted by [time.clock.hires]
#else
    typedef system_clock high_resolution_clock; // as permitted by [time.clock.hires]
#endif

```

`clock_string<system_clock>` Specialization

```

template <class CharT>
struct clock_string<system_clock, CharT>
{
    static std::basic_string<CharT> name();
    static std::basic_string<CharT> since();
};

```

`clock_string<>::name()` returns "system_clock".

`clock_string<>::since()` returns " since Jan 1, 1970"

`clock_string<steady_clock>` Specialization

```

#ifdef BOOST_CHRONO_HAS_CLOCK_STEADY

template <class CharT>
struct clock_string<steady_clock, CharT>
{
    static std::basic_string<CharT> name();
    static std::basic_string<CharT> since();
};

#endif

```

`clock_string<>::name()` returns "steady_clock".

`clock_string<>::since()` returns " since boot"

Header `<boost/chrono/clock_strings.hpp>`

```
namespace boost {
  namespace chrono {

    template <class Clock, class CharT>
    struct clock_string;

  }
}
```

Template Class `clock_string<>`

```
template <class Clock, class CharT>
struct clock_string;
```

This template must be specialized for specific clocks. The specialization must define the following functions

```
static std::basic_string<CharT> name();
static std::basic_string<CharT> since();
```

`clock_string<>::name()` return the clock name, which usually corresponds to the class name.

`clock_string<>::since()` return the textual format of the clock epoch.

Header `<boost/chrono/typeof/boost/chrono/chrono.hpp>`

Register `duration<>` and `time_point<>` class templates to **Boost.Typeof**.

Chrono I/O V1

Header `<boost/chrono/chrono_io.hpp>`

```

namespace boost {
namespace chrono {

    template <class CharT>
    class duration_punct;

    template <class CharT, class Traits>
        std::basic_ostream<CharT, Traits>&
        duration_short(std::basic_ostream<CharT, Traits>& os);

    template <class CharT, class Traits>
        std::basic_ostream<CharT, Traits>&
        duration_long(std::basic_ostream<CharT, Traits>& os);

    template <class CharT, class Traits, class Rep, class Period>
        std::basic_ostream<CharT, Traits>&
        operator<<(std::basic_ostream<CharT, Traits>& os, const duration<Rep, Period>& d);

    template <class CharT, class Traits, class Rep, class Period>
        std::basic_istream<CharT, Traits>&
        operator>>(std::basic_istream<CharT, Traits>& is, duration<Rep, Period>& d);

    template <class CharT, class Traits, class Clock, class Duration>
        std::basic_ostream<CharT, Traits>&
        operator<<(std::basic_ostream<CharT, Traits>& os,
            const time_point<Clock, Duration>& tp);

    template <class CharT, class Traits, class Clock, class Duration>
        std::basic_istream<CharT, Traits>&
        operator>>(std::basic_istream<CharT, Traits>& is,
            time_point<Clock, Duration>& tp);

}
}

```

Template Class `duration_punct<>`

The `duration` unit names can be customized through the facet: `duration_punct`. `duration` unit names come in two varieties: long and short. The default constructed `duration_punct` provides names in the long format. These names are English descriptions. Other languages are supported by constructing a `duration_punct` with the proper spellings for "hours", "minutes" and "seconds", and their abbreviations (for the short format).

```

template <class CharT>
class duration_punct
    : public std::locale::facet
{
public:
    typedef std::basic_string<CharT> string_type;
    enum {use_long, use_short};

    static std::locale::id id;

    explicit duration_punct(int use = use_long);

    duration_punct(int use,
        const string_type& long_seconds, const string_type& long_minutes,
        const string_type& long_hours, const string_type& short_seconds,
        const string_type& short_minutes, const string_type& short_hours);

    duration_punct(int use, const duration_punct& d);

    template <class Period> string_type short_name() const;
    template <class Period> string_type long_name() const;
    template <class Period> string_type name() const;

    bool is_short_name() const;
    bool is_long_name() const;
};

```

I/O Manipulators

The short or long format can be easily chosen by streaming a `duration_short` or `duration_long` manipulator respectively.

```

template <class CharT, class Traits>
    std::basic_ostream<CharT, Traits>&
    duration_short(std::basic_ostream<CharT, Traits>& os);

```

Effects: Set the `duration_punct` facet to stream `durations` and `time_points` as abbreviations.

Returns: the output stream

```

template <class CharT, class Traits>
    std::basic_ostream<CharT, Traits>&
    duration_long(std::basic_ostream<CharT, Traits>& os);

```

Effects: Set the `duration_punct` facet to stream `durations` and `time_points` as long text.

Returns: the output stream

I/O Streams Operations

Any `duration` can be streamed out to a `basic_ostream`. The run-time value of the `duration` is formatted according to the rules and current format settings for `duration::rep`. This is followed by a single space and then the compile-time unit name of the `duration`. This unit name is built on the string returned from `ratio_string<>` and the data used to construct the `duration_punct` which was inserted into the stream's locale. If a `duration_punct` has not been inserted into the stream's locale, a default constructed `duration_punct` will be added to the stream's locale.

A `time_point` is formatted by outputting its internal `duration` followed by a string that describes the `time_point::clock` epoch. This string will vary for each distinct clock, and for each implementation of the supplied clocks.

```
template <class CharT, class Traits, class Rep, class Period>
    std::basic_ostream<CharT, Traits>&
    operator<<(std::basic_ostream<CharT, Traits>& os, const duration<Rep, Period>& d);
```

Effects: outputs the `duration` as an abbreviated or long text format depending on the state of the `duration_punct` facet.

Returns: the output stream

```
template <class CharT, class Traits, class Rep, class Period>
    std::basic_istream<CharT, Traits>&
    operator>>(std::basic_istream<CharT, Traits>& is, duration<Rep, Period>& d)
```

Effects: reads a `duration` from the input stream. If a format error is found, the input stream state will be set to `failbit`.

Returns: the input stream

```
template <class CharT, class Traits, class Clock, class Duration>
    std::basic_ostream<CharT, Traits>&
    operator<<(std::basic_ostream<CharT, Traits>& os,
               const time_point<Clock, Duration>& tp);
```

Effects: outputs the `time_point` as an abbreviated or long text format depending on the state of the `duration_punct` facet.

Returns: the output stream

```
template <class CharT, class Traits, class Clock, class Duration>
    std::basic_istream<CharT, Traits>&
    operator>>(std::basic_istream<CharT, Traits>& is,
               time_point<Clock, Duration>& tp);
```

Effects: reads a `time_point` from the input stream. If a format error is found, the input stream state will be set to `failbit`.

Returns: the input stream

Chrono I/O V2

Header `<boost/chrono/chrono_io.hpp>`

This file includes the i/o of the two major components, `duration` and `time_point`.

```
#include <boost/chrono/io/duration_style.hpp>
#include <boost/chrono/io/timezone.hpp>
#include <boost/chrono/io/ios_state.hpp>
#include <boost/chrono/io/duration_get.hpp>
#include <boost/chrono/io/duration_put.hpp>
#include <boost/chrono/io/duration_units.hpp>
#include <boost/chrono/io/duration_io.hpp>
#include <boost/chrono/io/time_point_get.hpp>
#include <boost/chrono/io/time_point_put.hpp>
#include <boost/chrono/io/time_point_units.hpp>
#include <boost/chrono/io/time_point_io.hpp>
```

Header <boost/chrono/io/duration_style.hpp>

```
namespace boost {
  namespace chrono {

    // typedefs
    enum class duration_style {
      prefix, symbol
    };
  }
}
```

Scoped enum `duration_style`

```
enum class duration_style {
  prefix, symbol
};
```

`duration` unit names come in two varieties: prefix and symbol.

Header <boost/chrono/io/timezone.hpp>

```
namespace boost {
  namespace chrono {

    struct timezone
    {
      enum type {
        utc, local
      };
    };
  }
}
```

Scoped enum `timezone`

```
enum class timezone {
  utc, local
};
```

Header <boost/chrono/io/ios_state.hpp>

```

namespace boost {
    namespace chrono {

        // setters and getters
        duration_style get_duration_style(std::ios_base & ios);
        void set_duration_style(std::ios_base& ios, duration_style style);

        timezone get_timezone(std::ios_base & ios);
        void set_timezone(std::ios_base& ios, timezone tz);

        template<typename CharT>
        std::basic_string<CharT> get_time_fmt(std::ios_base & ios);
        template<typename CharT>
        void set_time_fmt(std::ios_base& ios, std::basic_string<CharT> const& fmt);

        // i/o state savers
        struct duration_style_io_saver;
        template<typename CharT = char, typename Traits = std::char_traits<CharT> >
        struct timezone_io_saver;
        template<typename CharT = char, typename Traits = std::char_traits<CharT> >
        struct time_fmt_io_saver;
    }
}

```

Setter and getters

Non Member Function `get_duration_style(std::ios_base &)`

```
duration_style get_duration_style(std::ios_base & ios);
```

Returns: The stream's `duration_style` attribute associated to `ios`.

Non Member Function `set_duration_style(std::ios_base &,duration_style)`

```
void set_duration_style(std::ios_base& ios, duration_style style);
```

Effects: Set the stream's `duration_style` attribute associated to `ios` with the `style` parameter.

Non Member Function `get_timezone(std::ios_base&)`

```
timezone get_timezone(std::ios_base & ios);
```

Returns: The stream's `timezone` attribute associated to `ios`.

Non Member Function `set_timezone(std::ios_base&,duration_style)`

```
void set_timezone(std::ios_base& ios, timezone tz);
```

Effects: Set the stream's `timezone` attribute associated to `ios` with the `tz` parameter.

Non Member Function `get_time_fmt(std::ios_base &)`

```

template<typename CharT>
std::basic_string<CharT> get_time_fmt(std::ios_base & ios);

```

Returns: The stream's time format attribute associated to `ios`.

Non Member Function `set_time_fmt(std::ios_base&, std::basic_string<CharT> const&)`

```
template<typename CharT>
void set_time_fmt(std::ios_base& ios, std::basic_string<CharT> const& fmt);
```

Effects: Set the stream's time format attribute associated to `ios` with the `fmt` parameter.

I/O State Savers

Template Class `duration_style_io_saver`

```
// i/o state savers

struct duration_style_io_saver
{
    typedef std::ios_base state_type; // the state type is ios_base
    typedef duration_style aspect_type; // the aspect type is the __duration_style

    explicit duration_style_io_saver(state_type &s);
    duration_style_io_saver(state_type &s, aspect_type new_value);
    ~duration_style_io_saver();
    void restore();
};
```

The `state_type` is a version of the IOStreams base class `std::ios_base`.

Constructor `duration_style_io_saver(state_type&)`

The first constructor takes a stream object and saves a reference to the stream and the current value of a particular stream attribute.

```
explicit duration_style_io_saver(state_type &s);
```

Effects: Constructs a `duration_style_io_saver` by storing `s`.

Post Conditions: `static_cast<duration_style>(*this) == f`.

Constructor `duration_style_io_saver(state_type, aspect_type)`

The second constructor works like the first, and uses its second argument to change the stream's attribute to the new `aspect_type` value given.

```
explicit duration_style_io_saver(state_type &s, aspect_type new_value);
```

Effects: Constructs a `duration_style_io_saver` by storing `s`.

Post Conditions: `static_cast<duration_style>(*this) == f`.

Destructor `~duration_style_io_saver()`

The destructor restores the stream's attribute to the saved value.

```
~duration_style_io_saver();
```

Effects: As if `restore()`.

Member Function `restore()`

The restoration can be activated early (and often) with the `restore` member function.

```
void restore();
```

Effects: Restores the stream's `duration_style` attribute to the saved value.

Template Class `timezone_io_saver<>`

```
template<typename CharT = char, typename Traits = std::char_traits<CharT> >
struct timezone_io_saver
{
    typedef std::basic_ios<CharT, Traits> state_type;
    typedef timezone aspect_type;

    explicit timezone_io_saver(state_type &s);
    timezone_io_saver(state_type &s, aspect_type new_value);
    ~timezone_io_saver();
    void timezone_io_saver__restore();
};
```

The `state_type` is a version of the IOStreams base class template `std::basic_ios<CharT, Traits>`, where `CharT` is a character type and `Traits` is a character traits class. The user would usually place an actual input, output, or combined stream object for the `state-type` parameter, and not a base class object.

Constructor `timezone_io_saver(state_type&)`

The first constructor takes a stream object and saves a reference to the stream and the current value of a particular stream attribute.

```
explicit timezone_io_saver(state_type &s);
```

Effects: Constructs a `timezone_io_saver` by storing `s`.

Constructor `timezone_io_saver(state_type, aspect_type)`

The second constructor works like the first, and uses its second argument to change the stream's attribute to the new `aspect_type` value given.

```
explicit timezone_io_saver(state_type &s, aspect_type new_value);
```

Effects: Constructs a `timezone_io_saver` by storing `s`.

Destructor `~timezone_io_saver()`

The destructor restores the stream's attribute to the saved value.

```
~timezone_io_saver();
```

Effects: As if `restore()`.

Member Function `restore()`

The restoration can be activated early (and often) with the `restore` member function.

```
void restore();
```

Effects: Restores the stream's `timezone` attribute to the saved value.

Template Class `time_fmt_io_saver<>`

```
template<typename CharT = char, typename Traits = std::char_traits<CharT> >
struct time_fmt_io_saver
{
    typedef std::basic_ios<CharT, Traits> state_type;

    explicit time_fmt_io_saver(state_type &s);
    time_fmt_io_saver(state_type &s, basic_string<CharT> const& new_value);
    ~time_fmt_io_saver();
    void restore();
};
```

The `state_type` is a version of the IOStreams base class template `std::basic_ios<CharT, Traits>`, where `CharT` is a character type and `Traits` is a character traits class. The user would usually place an actual input, output, or combined stream object for the `state-type` parameter, and not a base class object.

Constructor `time_fmt_io_saver(state_type&)`

The first constructor takes a stream object and saves a reference to the stream and the current value of a particular stream attribute.

```
explicit time_fmt_io_saver(state_type &s);
```

Effects: Constructs a `time_fmt_io_saver` by storing `s`.

Constructor `time_fmt_io_saver(state_type, aspect_type)`

The second constructor works like the first, and uses its second argument to change the stream's attribute to the new `aspect_type` value given.

```
explicit time_fmt_io_saver(state_type &s, aspect_type new_value);
```

Effects: Constructs a `time_fmt_io_saver` by storing `s`.

Destructor `~time_fmt_io_saver()`

The destructor restores the stream's attribute to the saved value.

```
~time_fmt_io_saver();
```

Effects: As if `restore()`.

Member Function `restore()`

The restoration can be activated early (and often) with the `restore` member function.

```
void restore();
```

Effects: Restores the stream's time format attribute to the saved value.

Header <boost/chrono/io/duration_get.hpp>

```

namespace boost {
  namespace chrono {

    template <class CharT, class InputIterator = std::istreambuf_iterator<CharT> >
      class duration_get;

  }
}

```

Template Class duration_get

```

template <class CharT, class InputIterator = std::istreambuf_iterator<CharT> >
class duration_get: public std::locale::facet
{
public:
  typedef CharT char_type; // Type of character the facet is instantiated on
  typedef std::basic_string<CharT> string_type; // Type of character string passed to member ↵
  functions.
  typedef InputIterator iter_type; // Type of iterator used to scan the character buffer.

  explicit duration_get(size_t refs = 0);

  template <typename Rep, typename Period>
  iter_type get(
    iter_type s,
    iter_type end,
    std::ios_base& ios,
    std::ios_base::iostate& err,
    duration<Rep, Period>& d,
    const char_type* pattern,
    const char_type* pat_end
  ) const;

  template <typename Rep, typename Period>
  iter_type get(
    iter_type s,
    iter_type end,
    std::ios_base& ios,
    std::ios_base::iostate& err,
    duration<Rep, Period>& d
  ) const;

  template <typename Rep>
  iter_type get_value(
    iter_type s,
    iter_type end,
    std::ios_base& ios,
    std::ios_base::iostate& err,
    Rep& r
  ) const;

  iter_type get_unit(
    iter_type i,
    iter_type e,
    std::ios_base& is,
    std::ios_base::iostate& err,
    detail::rt_ratio &rt
  ) const

```

```

static std::locale::id id; // Unique identifier for this type of facet.

~duration_get()
{
}

};

```

The `duration_get` facet extracts duration from a character string and stores the resulting value in a class duration `d` argument. The facet parses the string using a specific format as a guide. If the string does not fit the format, then the facet will indicate an error by setting the `err` argument to `iosbase::failbit`. In other words, user confirmation is required for reliable parsing of user-entered durations, but machine-generated formats can be parsed reliably. This allows parsers to be aggressive about interpreting user variations on standard formats.

Constructor `duration_get(size_t)`

```
explicit duration_get(size_t refs);
```

Constructs a `duration_get` facet.

Parameters:

- **refs:** references

Effects: Constructs a `duration_get` facet. If the `refs` argument is 0 then destruction of the object is delegated to the locale, or locales, containing it. This allows the user to ignore lifetime management issues. On the other had, if `refs` is 1 then the object must be explicitly deleted; `locale` will not do so. In this case, the object can be maintained across the lifetime of multiple locales.

Destructor `~duration_get()`

```
~duration_get();
```

Destructs a `duration_get` facet.

Template Member Function `get(iter_type, iter_type, std::ios_base&, std::ios_base::iostate&, duration<Rep, Period>&, const char_type*, const char_type*) const`

```

template <typename Rep, typename Period>
iter_type get(iter_type s, iter_type end, std::ios_base& ios, std::ios_base::iostate& err,
              duration<Rep, Period> &d, const char_type *pattern, const char_type *pat_end) const;

```

Extracts a duration from the range `[s, end)` following the pattern `[pattern, pat_end)`.

Parameters:

- **s:** start input stream iterator
- **end:** end input stream iterator
- **ios:** a reference to a `ios_base`
- **err:** the `ios_base` state
- **d:** the duration
- **pattern:** begin of the formatting pattern
- **pat_end:** end of the formatting pattern

Requires: `[s, end)` and `[pattern, pat_end)` shall be valid ranges.

Effects: The function starts by evaluating `err = std::ios_base::goodbit`.

Then it computes an intermediate representation based on `Rep` according to the following rules:

- If `Rep` is a floating point type, the intermediate representation is `long double`.
- Else if `Rep` is a signed integral type, the intermediate representation is `long long`.
- Else if `Rep` is an unsigned integral type, the intermediate representation is `unsigned long long`.
- Else intermediate representation is `Rep`.

Next the following local variable `r` of type intermediate representation and `rt` of type `rt_ratio` are default constructed.

It then enters a loop, reading zero or more characters from `s` at each iteration. Unless otherwise specified below, the loop terminates when the first of the following conditions holds:

- The expression `pattern == pat_end` evaluates to true.
- The expression `err == std::ios_base::goodbit` evaluates to false.
- The expression `s == end` evaluates to true, in which case the function evaluates `err = std::ios_base::eofbit | std::ios_base::failbit`.
- The next element of `pattern` is equal to `'%'`, followed by a conversion specifier character, `format`. If the number of elements in the range `[pattern, pat_end)` is not sufficient to unambiguously determine whether the conversion specification is complete and valid, the function evaluates `err = std::ios_base::failbit`. Otherwise, the function evaluates `s = get_value(s, end, ios, err, r)` when the conversion specification is `'v'` and `s = get_value(s, end, ios, err, rt)` when the conversion specification is `'u'`. If `err == std::ios_base::goodbit` holds after the evaluation of the expression, the function increments `pattern` to point just past the end of the conversion specification and continues looping.
- The expression `isspace(*pattern, ios.getloc())` evaluates to true, in which case the function first increments `pattern` until `pattern == pat_end || !isspace(*pattern, ios.getloc())` evaluates to true, then advances `s` until `s == end || !isspace(*s, ios.getloc())` is true, and finally resumes looping.
- The next character read from `s` matches the element pointed to by `pattern` in a case-insensitive comparison, in which case the function evaluates `++pattern, ++s` and continues looping. Otherwise, the function evaluates `err = std::ios_base::failbit`.

If a duration representation value and a unit specifier have successfully been parsed, compute `(rt.num/rt.den)/(Period::num/Period::den)` reduced to lowest terms. If this ratio can not be stored without overflow, evaluates `err = std::ios_base::failbit`. Otherwise store the result of this division in `num` and `den`.

If the division did not result in overflow, then compute `r * num / den` in such a way as to avoid intermediate overflow. If `r` has integral type and this computation would not be exact, evaluates `err = std::ios_base::failbit`. If the result of the computation would overflow `Rep`, evaluates `err = std::ios_base::failbit`. Otherwise the result of `r * num / den` is used to construct a `duration<Rep, Period>` which is assigned to `d`.

Returns: `s`, an iterator pointing just beyond the last character that can be determined to be part of a valid duration.

Template Member Function `get(iter_type, iter_type, std::ios_base&, std::ios_base::iostate&, duration<Rep, Period>&) const`

```
template <typename Rep, typename Period>
iter_type get(
    iter_type s,
    iter_type end,
    std::ios_base& ios,
    std::ios_base::iostate& err,
    duration<Rep, Period>& d
) const;
```

Extracts a duration from the range `[s, end)` following the default pattern.

Parameters:

- **s**: start input stream iterator
- **end**: end input stream iterator
- **ios**: a reference to a `ios_base`
- **err**: the `ios_base` state
- **d**: the duration

Effects: Stores the duration pattern from the `__duration_unit` facet associated to 'ios in let say str'. Last as if

```
return get(s, end, ios, err, ios, d, str.data(), str.data() + str.size());
```

Returns: `s`, an iterator pointing just beyond the last character that can be determined to be part of a valid duration.

Template Member Function `get_value(iter_type, iter_type, std::ios_base&, std::ios_base::iostate&, Rep&) const`

```
template <typename Rep>
iter_type get_value(iter_type s, iter_type end, std::ios_base& ios, std::ios_base::iostate& err, Rep& r) const;
```

Extracts a duration representation from the range `[s, end)`.

Parameters:

- **s**: start input stream iterator
- **end**: end input stream iterator
- **ios**: a reference to a `ios_base`
- **err**: the `ios_base` state
- **r**: a reference to the duration representation

Effects: As if

```
return std::use_facet<std::num_get<char_type, iter_type>>(ios.getloc()).get(s, end, ios, err, r);
```

Returns: `s`, an iterator pointing just beyond the last character that can be determined to be part of a valid `Rep` value.

Member Function `get_unit(iter_type,iter_type, std::ios_base&, std::ios_base::iostate&, rt_ratio&)`
`const`

```
iter_type get_unit(iter_type i, iter_type e, std::ios_base& is, std::ios_base::iostate& err, de-
tail::rt_ratio &rt) const;
```

Extracts a duration unit from the range `[s, end)`.

Parameters:

- **s:** start input stream iterator
- **end:** end input stream iterator
- **ios:** a reference to a `ios_base`
- **err:** the `ios_base` state
- **rt:** a reference to the duration run-time ratio.

Effects:

- If the first character is '[' , an attempt is made to consume a pattern of the form "[N/D]" where N and D have type `unsigned long long`.
 - If successful, `rt` records the values of N and D, otherwise evaluates `err = std::ios_base::failbit` and return `i`.
 - Return the parse the longest string possible matching one of the durations units that can follow the pattern "[N/D]", as if

```
return do_get_n_d_prefix_unit(facet, i, e, is, err);
```

- Otherwise the next character is not '[' . Return the parse the longest string possible matching one of the durations units, as if

```
return do_get_prefix_unit(facet, i, e, is, err, rt);
```

Returns: `i`, an iterator pointing just beyond the last character that can be determined to be part of a valid duration unit.

Protected Member Function `do_get_n_d_prefix_unit(duration_units<CharT> const&, iter_type, iter_type, std::ios_base&, std::ios_base::iostate&)` `const`

```
virtual iter_type do_get_n_d_prefix_unit(
    duration_units<CharT> const &facet,
    iter_type i,
    iter_type e,
    std::ios_base&,
    std::ios_base::iostate& err
) const;
```

Extracts the run-time ratio associated to the duration when it is given in `[N/D]` form.

This is an extension point of this facet so that we can take in account other periods that can have a useful translation in other contexts, as e.g. days and weeks.

Parameters:

- **s:** start input stream iterator
- **end:** end input stream iterator

- **ios**: a reference to a `ios_base`
- **err**: the `ios_base` state
- **rt**: a reference to the duration run-time ratio.

Effects: Scan `s` for the longest of all the plural forms associated with the duration units. If successful, sets the matched ratio in `rt`. Otherwise evaluates `err = std::ios_base::failbit`.

Returns: `s`, an iterator pointing just beyond the last character that can be determined to be part of a valid name.

Protected Member Function `do_get_prefix_unit(duration_units<CharT> const&, iter_type, iter_type, std::ios_base&, std::ios_base::iostate&, detail::rt_ratio&) const`

```
virtual iter_type do_get_prefix_unit(
    duration_units<CharT> const &facet,
    iter_type i,
    iter_type e,
    std::ios_base&,
    std::ios_base::iostate& err,
    detail::rt_ratio &rt
) const;
```

Extracts the run-time ratio associated to the duration when it is given in prefix form.

This is an extension point of this facet so that we can take in account other periods that can have a useful translation in other contexts, as e.g. days and weeks.

Parameters:

- **s**: start input stream iterator
- **end**: end input stream iterator
- **ios**: a reference to a `ios_base`
- **err**: the `ios_base` state
- **rt**: a reference to the duration run-time ratio.

Effects: Scan `s` for the longest of all the plural forms associated with the duration units. If successful, sets the matched ratio in `rt`. Otherwise evaluates `err = std::ios_base::failbit`.

Returns: `s`, an iterator pointing just beyond the last character that can be determined to be part of a valid name.

Header `<boost/chrono/io/duration_put.hpp>`

```
namespace boost {
    namespace chrono {

        template <class CharT, class OutputIterator = std::ostreambuf_iterator<CharT> >
        class duration_put;

    }
}
```

Template Class `duration_put`

```

template <class CharT, class OutputIterator = std::ostreambuf_iterator<CharT> >
class duration_put: public std::locale::facet
{
public:
    typedef CharT char_type; // Type of character the facet is instantiated on.
    typedef std::basic_string<CharT> string_type; // Type of character string passed to member
functions.
    typedef OutputIterator iter_type; // Type of iterator used to write in the character buffer.

    explicit duration_put(size_t refs = 0);

    template <typename Rep, typename Period>
    iter_type put(iter_type s, std::ios_base& ios, char_type fill, duration<Rep, Peri-
od> const& d, const CharT* pattern,
        const CharT* pat_end) const;

    template <typename Rep, typename Period>
    iter_type put(iter_type s, std::ios_base& ios, char_type fill, duration<Rep, Peri-
od> const& d) const;

    template <typename Rep, typename Period>
    iter_type put_value(iter_type s, std::ios_base& ios, char_type fill, duration<Rep, Peri-
od> const& d) const;

    template <typename Rep, typename Period>
    iter_type put_unit(iter_type s, std::ios_base& ios, char_type fill, duration<Rep, Peri-
od> const& d) const;

    static std::locale::id id; // Unique identifier for this type of facet.

    ~duration_put();
};

```

Constructor `duration_put(size_t)`

```
explicit duration_put(size_t refs);
```

Constructs a `duration_put` facet.

Parameters:

- **refs:** references

Effects: Constructs a `duration_put` facet. If the `refs` argument is 0 then destruction of the object is delegated to the locale, or locales, containing it. This allows the user to ignore lifetime management issues. On the other had, if `refs` is 1 then the object must be explicitly deleted; `locale` will not do so. In this case, the object can be maintained across the lifetime of multiple locales.

Destructor `~duration_put()`

```
~duration_put();
```

Destroys a `duration_put` facet.

Member Function `put(iter_type, std::ios_base&, char_type, duration<Rep, Period> const&, const CharT*, const CharT*)`

```
template <typename Rep, typename Period>
iter_type put(iter_type s, std::ios_base& ios, char_type fill, duration<Rep, Period>
od> const& d, const CharT* pattern,
    const CharT* pat_end) const;
```

Parameters:

- **s:** an output stream iterator
- **ios:** a reference to a ios_base
- **d:** the duration
- **pattern:** begin of the formatting pattern
- **pat_end:** end of the formatting pattern

Effects: Steps through the sequence from `pattern` to `pat_end`, identifying characters that are part of a pattern sequence. Each character that is not part of a pattern sequence is written to `s` immediately, and each pattern sequence, as it is identified, results in a call to `put_value` or `put_unit`; thus, pattern elements and other characters are interleaved in the output in the order in which they appear in the pattern. Pattern sequences are identified by converting each character `c` to a `char` value as if by `ct.narrow(c, 0)`, where `ct` is a reference to `ctype<charT>` obtained from `ios.getloc()`. The first character of each sequence is equal to `'%'`, followed by a pattern specifier character specifier, which can be `'v'` for the duration value or `'u'` for the duration unit. For each valid pattern sequence identified, calls `put_value(s, ios, d)` or `put_unit(s, ios, d)`.

Returns: An iterator pointing immediately after the last character produced.

Member Function `put(iter_type, std::ios_base&, char_type fill, duration<Rep, Period> const&)`

```
template <typename Rep, typename Period>
iter_type put(iter_type s, std::ios_base& ios, char_type fill, duration<Rep, Period>
od> const& d) const;
```

Parameters:

- **s:** an output stream iterator
- **ios:** a reference to a ios_base
- **d:** the duration

Retrieves Stores the duration pattern from the `__duration_unit` facet in let say `str`. Last as if

```
return put(s, ios, d, str.data(), str.data() + str.size());
```

Returns: An iterator pointing immediately after the last character produced.

Member Function `put_value(iter_type, std::ios_base&, char_type, duration<Rep, Period> const&)`

```
template <typename Rep, typename Period>
iter_type put_value(iter_type s, std::ios_base& ios, char_type fill, duration<Rep, Period>
od> const& d) const;
```

Parameters:

- **s:** an output stream iterator

- **ios**: a reference to a ios_base
- **d**: the duration

Effects: As if `std::use_facet<std::num_put<CharT, iter_type>>(ios.getloc()).put(s, ios, ' ', static_cast<long int>(d.count()))`.

Returns: An iterator pointing immediately after the last character produced.

Member Function `put_unit(iter_type, std::ios_base&, char_type, duration<Rep, Period> const&)`

```
template <typename Rep, typename Period>
iter_type put_unit(iter_type s, std::ios_base& ios, char_type fill, duration<Rep, Period> const& d) const;
```

Parameters:

- **s**: an output stream iterator
- **ios**: a reference to a ios_base
- **fill**: the fill character
- **d**: the duration

Effects: Let `facet` be the `duration_units<CharT>` facet associated to `ios`. If the associated unit is named, as if

```
string_type str = facet.get_unit(get_duration_style(ios), d);
s=std::copy(str.begin(), str.end(), s);
```

Otherwise, format the unit as "[Period::num/Period::den]" followed by the unit associated to [N/D] obtained using `facet.get_n_d_unit(get_duration_style(ios), d)`.

Returns: `s`, iterator pointing immediately after the last character produced.

Header `<boost/chrono/io/duration_units.hpp>`

```
namespace boost {
  namespace chrono {
    class rt_ratio;
    template <typename CharT = char>
      class duration_units;
  }
}
```

Class `rt_ratio`

```

class rt_ratio
{
public:
    template <typename Period>
    rt_ratio(Period const&) :
        num(Period::type::num), den(Period::type::den)
    {
    }

    rt_ratio(intmax_t n = 0, intmax_t d = 1) :
        num(n), den(d)
    {
    }

    intmax_t num;
    intmax_t den;
};

```

Template Class `duration_units`

```

template <typename CharT = char>
class duration_units: public std::locale::facet
{
public:
    typedef CharT char_type; // Type of character the facet is instantiated on.
    typedef std::basic_string<CharT> string_type; // Type of character string passed to member ↵
    functions.
    static std::locale::id id; // Unique identifier for this type of facet.

    explicit duration_units(size_t refs = 0);
    virtual const string_type* get_n_d_valid_units_start() const = 0;
    virtual const string_type* get_n_d_valid_units_end() const = 0;
    virtual const string_type* get_valid_units_start() const = 0;
    virtual const string_type* get_valid_units_end() const = 0;
    virtual bool match_n_d_valid_unit(const string_type* k) const = 0;
    virtual bool match_valid_unit(const string_type* k, rt_ratio& rt) const = 0;
    virtual string_type get_pattern() const = 0;
    template <typename Rep, typename Period>
    string_type get_unit(duration_style style, duration<Rep, Period> const& d) const;
    template <typename Rep, typename Period>
    string_type get_n_d_unit(duration_style style, duration<Rep, Period> const& d) const;
    template <typename Period>
    bool is_named_unit() const;

protected:
    virtual ~duration_units();
    virtual string_type do_get_n_d_unit(duration_style style, rt_ratio rt, intmax_t v) const = 0;
    virtual string_type do_get_unit(duration_style style, rt_ratio rt, intmax_t v) const = 0;
    virtual bool do_is_named_unit(rt_ratio rt) const = 0;
};

```

`duration_units` facet gives useful information about the duration units, as the number of plural forms, the plural form associated to a duration, the text associated to a plural form and a duration's period,

Constructor `duration_units()`

```
explicit duration_units(size_t refs = 0);
```

Construct a `duration_units` facet.

Parameters:

- **refs:** references

Effects: Construct a `duration_units` facet. If the `refs` argument is 0 then destruction of the object is delegated to the locale, or locales, containing it. This allows the user to ignore lifetime management issues. On the other had, if `refs` is 1 then the object must be explicitly deleted; the locale will not do so. In this case, the object can be maintained across the lifetime of multiple locales.

Destructor `~duration_units()`

```
virtual ~duration_units();
```

Effects: Destroys the facet.

Member Function `get_n_d_valid_units_start()`

```
virtual const string_type* get_n_d_valid_units_start() const =0;
```

Returns: pointer to the start of valid [N/D] units.

Member Function `get_n_d_valid_units_end()`

```
virtual const string_type* get_n_d_valid_units_end() const=0;
```

Returns: pointer to the end of valid [N/D] units.

Member Function `get_valid_units_start()`

```
virtual const string_type* get_valid_units_start() const=0;
```

Returns: pointer to the start of valid units, symbol or prefix with its different plural forms.

Member Function `get_valid_units_end()`

```
virtual const string_type* get_valid_units_end() const=0;
```

Returns: pointer to the end of valid units.

Member Function `match_n_d_valid_unit(const string_type*)`

```
virtual bool match_n_d_valid_unit(const string_type* k) const = 0;
```

Parameters:

- **k:** the found pointer to the [N/D] unit.

Returns: true if k matches a valid unit.

Member Function `match_valid_unit(const string_type*,rt_ratio&)`

```
virtual bool match_valid_unit(const string_type* k, rt_ratio& rt) const = 0;
```

Parameters:

- **k**: the found pointer to the unit.

Effects: `rt` is set to the valid `Period` when the `k` matches a valid unit. **Returns:** `true` if `k` matches a valid unit.

Member Function `get_pattern()`

```
virtual string_type get_pattern() const=0;
```

Returns: the pattern to be used by default.

Template Member Function `get_unit(duration_style, duration<Rep, Period> const&)`

```
template <typename Rep, typename Period>
string_type get_unit(duration_style style, duration<Rep, Period> const& d) const;
```

Returns: `get_unit(style, d.count(), rt_ratio(Period()))`, the unit associated to this duration.

Template Member Function `get_n_d_unit(duration_style, duration<Rep, Period> const&)`

```
template <typename Rep, typename Period>
string_type get_n_d_unit(duration_style style, duration<Rep, Period> const& d) const;
```

Returns: `get_n_d_unit(style, d.count(), rt_ratio(Period()))`, i.e. the [N/D] suffix unit associated to this duration.

Template Member Function `is_named_unit()`

```
template <typename Period>
bool is_named_unit() const;
```

Returns: `do_is_named_unit(rt_ratio(Period()))`, true if the unit associated to the given `Period` is named, false otherwise.

Protected Member Function `do_get_n_d_unit(duration_style, rt_ratio, intmax_t)`

```
virtual string_type do_get_n_d_unit(duration_style style, rt_ratio rt, intmax_t v) const = 0;
```

Returns: the [N/D] suffix unit associated to this duration.

Protected Member Function `do_get_unit(duration_style, rt_ratio, intmax_t)`

```
virtual string_type do_get_unit(duration_style style, rt_ratio rt, intmax_t v) const = 0;
```

Returns: the unit associated to this duration.

Protected Member Function `do_is_named_unit(rt_ratio)`

```
virtual bool do_is_named_unit(rt_ratio rt) const = 0;
```

Returns: true if the unit associated to the given `Period` is named, false otherwise.

Template Class `duration_units_default`

```

template <typename CharT = char>
class duration_units_default: public duration_units<CharT>
{
protected:
    static const std::size_t pfs_ = 2; // The default English facet has two plural forms.

public:
    typedef CharT char_type;
    typedef std::basic_string<CharT> string_type;

    explicit duration_units_default(size_t refs = 0);
    ~duration_units_default();

    bool match_n_d_valid_unit(const string_type* k) const;
    bool match_valid_unit(const string_type* k, rt_ratio& rt) const;
    const string_type* get_n_d_valid_units_start() const;
    const string_type* get_n_d_valid_units_end() const;
    string_type* get_valid_units_start() const;
    string_type* get_valid_units_end() const;
    string_type get_pattern() const;
protected:
    bool do_is_named_unit(rt_ratio rt) const;
    string_type do_get_n_d_unit(duration_style style, rt_ratio, intmax_t v) const;
    string_type do_get_unit(duration_style style, rt_ratio rt, intmax_t v) const;

    virtual std::size_t do_get_plural_forms() const;
    virtual std::size_t do_get_plural_form(int_least64_t value) const;

    virtual string_type do_get_unit(duration_style style, ratio<1> u, std::size_t pf) const;
    virtual string_type do_get_unit(duration_style style, ratio<60> u, std::size_t pf) const;
    virtual string_type do_get_unit(duration_style style, ratio<3600> u, std::size_t pf) const;
    virtual string_type do_get_unit(duration_style style, atto u, std::size_t pf) const;
    virtual string_type do_get_unit(duration_style style, femto u, std::size_t pf) const;
    virtual string_type do_get_unit(duration_style style, pico u, std::size_t pf) const;
    virtual string_type do_get_unit(duration_style style, nano u, std::size_t pf) const;
    virtual string_type do_get_unit(duration_style style, micro u, std::size_t pf) const;
    virtual string_type do_get_unit(duration_style style, milli u, std::size_t pf) const;
    virtual string_type do_get_unit(duration_style style, centi u, std::size_t pf) const;
    virtual string_type do_get_unit(duration_style style, deci u, std::size_t pf) const;
    virtual string_type do_get_unit(duration_style style, deca u, std::size_t pf) const;
    virtual string_type do_get_unit(duration_style style, hecto u, std::size_t pf) const;
    virtual string_type do_get_unit(duration_style style, kilo u, std::size_t pf) const;
    virtual string_type do_get_unit(duration_style style, mega u, std::size_t pf) const;
    virtual string_type do_get_unit(duration_style style, giga u, std::size_t pf) const;
    virtual string_type do_get_unit(duration_style style, tera u, std::size_t pf) const;
    virtual string_type do_get_unit(duration_style style, peta u, std::size_t pf) const;
    virtual string_type do_get_unit(duration_style style, exa u, std::size_t pf) const;

    virtual string_type do_get_ratio_prefix(duration_style style, atto u) const;
    virtual string_type do_get_ratio_prefix(duration_style style, femto u) const;
    virtual string_type do_get_ratio_prefix(duration_style style, pico u) const;
    virtual string_type do_get_ratio_prefix(duration_style style, nano u) const;
    virtual string_type do_get_ratio_prefix(duration_style style, micro u) const;
    virtual string_type do_get_ratio_prefix(duration_style style, milli u) const;
    virtual string_type do_get_ratio_prefix(duration_style style, centi u) const;
    virtual string_type do_get_ratio_prefix(duration_style style, deci u) const;
    virtual string_type do_get_ratio_prefix(duration_style style, deca u) const;
    virtual string_type do_get_ratio_prefix(duration_style style, hecto u) const;
    virtual string_type do_get_ratio_prefix(duration_style style, kilo u) const;

```

```

virtual string_type do_get_ratio_prefix(duration_style style, mega u) const;
virtual string_type do_get_ratio_prefix(duration_style style, giga u) const;
virtual string_type do_get_ratio_prefix(duration_style style, tera u) const;
virtual string_type do_get_ratio_prefix(duration_style style, peta u) const;
virtual string_type do_get_ratio_prefix(duration_style style, exa u) const;
};

```

This class is used to define the strings for the default English. This facet names the units associated to the following periods:

- atto,
- femto,
- pico,
- nano,
- micro,
- milli,
- centi,
- deci,
- ratio<1>,
- deca,
- hecto,
- kilo,
- mega,
- giga,
- tera,
- peta,
- exa,
- ratio<60> and
- ratio<3600>.

Constructor `duration_units_default()`

```
explicit duration_units_default(size_t refs = 0);
```

Construct a `duration_units_default` facet.

Parameters:

- **refs:** references

Effects: Construct a `duration_units_default` facet. If the `refs` argument is 0 then destruction of the object is delegated to the locale, or locales, containing it. This allows the user to ignore lifetime management issues. On the other had, if `refs` is 1 then the object must be explicitly deleted; the locale will not do so. In this case, the object can be maintained across the lifetime of multiple locales.

Destructor `~duration_units_default()`

```
virtual ~duration_units_default();
```

Effects: Destroys the facet.

Member Function `get_n_d_valid_units_start()`

```
virtual const string_type* get_n_d_valid_units_start() const;
```

Returns: pointer to the start of valid [N/D] units.

Member Function `get_n_d_valid_units_end()`

```
virtual const string_type* get_n_d_valid_units_end() const;
```

Returns: pointer to the end of valid [N/D] units.

Member Function `get_valid_units_start()`

```
virtual const string_type* get_valid_units_start() const;
```

Returns: pointer to the start of valid units, symbol or prefix with its different plural forms.

Member Function `get_valid_units_end()`

```
virtual const string_type* get_valid_units_end() const;
```

Returns: pointer to the end of valid units.

Member Function `match_n_d_valid_unit(const string_type*)`

```
virtual bool match_n_d_valid_unit(const string_type* k) const;
```

Parameters:

- **k:** the found pointer to the [N/D] unit.

Returns: true if k matches a valid unit.

Member Function `match_valid_unit(const string_type*,rt_ratio&)`

```
virtual bool match_valid_unit(const string_type* k, rt_ratio& rt) const;
```

Parameters:

- **k:** the found pointer to the unit.

Effects: `rt` is set to the valid Period when the `k` matches a valid unit. **Returns:** true if `k` matches a valid unit.

Member Function `get_pattern()`

```
virtual string_type get_pattern() const;
```

Returns: the pattern to be used by default.

Protected Member Function `do_get_n_d_unit(duration_style,rt_ratio,intmax_t)`

```
virtual string_type do_get_n_d_unit(duration_style style, rt_ratio rt, intmax_t v) const;
```

Returns: the [N/D] suffix unit associated to this duration.

Protected Member Function `do_get_unit(duration_style,rt_ratio,intmax_t)`

```
virtual string_type do_get_unit(duration_style style,rt_ratio rt, intmax_t v) const;
```

Returns: the unit associated to this duration.

Protected Member Function `do_is_named_unit(rt_ratio)`

```
virtual bool do_is_named_unit(rt_ratio rt) const;
```

Returns: true if the unit associated to the given Period is named, false otherwise.

Protected Member Function `do_get_plural_forms()`

```
virtual std::size_t do_get_plural_forms() const;
```

Returns: the number of associated plural forms this facet manages.

Protected Member Function `do_get_plural_form(int_least64_t)`

```
virtual std::size_t do_get_plural_form(int_least64_t value) const;
```

Gets the associated plural form.

Parameters:

value: the duration representation

Returns: the plural form associated to the `value` parameter. In English there are 2 plural forms

- 0 singular (-1 or 1)
- 1 plural for all others

Protected Member Function `do_get_unit(duration_style,ratio<1>,std::size_t)`

```
virtual string_type do_get_unit(duration_style style, ratio<1> u, std::size_t pf) const;
```

Parameters:

- **style:** the duration style.
- **period:** the period associated to the duration hours.
- **pf:** the requested plural form.

Returns: if `style` is symbol returns "s", otherwise if `pf` is 0 return "second", if `pf` is 1 "seconds"

Protected Member Function `do_get_unit(duration_style style, ratio<60>, std::size_t)`

```
virtual string_type do_get_unit(duration_style style, ratio<60> u, std::size_t pf) const;
```

Parameters:

- **style:** the duration style.
- **period:** the period associated to the duration hours.
- **pf:** the requested plural form.

Returns: if style is symbol returns "min", otherwise if pf is 0 return "minute", if pf is 1 "minutes"

Protected Member Function `do_get_unit(duration_style, ratio<3600>, std::size_t)`

```
virtual string_type do_get_unit(duration_style style, ratio<3600> u, std::size_t pf) const;
```

Parameters:

- **style:** the duration style.
- **period:** the period associated to the duration hours.
- **pf:** the requested plural form.

Returns: if style is symbol returns "h", otherwise if pf is 0 return "hour", if pf is 1 "hours"

Protected Member Function `do_get_unit(duration_style, Period, std::size_t)`

```
virtual string_type do_get_unit(duration_style style, atto u, std::size_t pf) const;
virtual string_type do_get_unit(duration_style style, femto u, std::size_t pf) const;
virtual string_type do_get_unit(duration_style style, pico u, std::size_t pf) const;
virtual string_type do_get_unit(duration_style style, nano u, std::size_t pf) const;
virtual string_type do_get_unit(duration_style style, micro u, std::size_t pf) const;
virtual string_type do_get_unit(duration_style style, milli u, std::size_t pf) const;
virtual string_type do_get_unit(duration_style style, centi u, std::size_t pf) const;
virtual string_type do_get_unit(duration_style style, deci u, std::size_t pf) const;
virtual string_type do_get_unit(duration_style style, deca u, std::size_t pf) const;
virtual string_type do_get_unit(duration_style style, hecto u, std::size_t pf) const;
virtual string_type do_get_unit(duration_style style, kilo u, std::size_t pf) const;
virtual string_type do_get_unit(duration_style style, mega u, std::size_t pf) const;
virtual string_type do_get_unit(duration_style style, giga u, std::size_t pf) const;
virtual string_type do_get_unit(duration_style style, tera u, std::size_t pf) const;
virtual string_type do_get_unit(duration_style style, peta u, std::size_t pf) const;
virtual string_type do_get_unit(duration_style style, exa u, std::size_t pf) const;
```

Parameters:

- **style:** the duration style.
- **u:** the period tag atto.
- **pf:** the requested plural form.

Returns: the concatenation of the prefix associated to period u + the one associated to seconds.

Protected Member Function `do_get_ratio_prefix(duration_style, Period)`

```

virtual string_type do_get_ratio_prefix(duration_style style, atto u) const;
virtual string_type do_get_ratio_prefix(duration_style style, femto u) const;
virtual string_type do_get_ratio_prefix(duration_style style, pico u) const;
virtual string_type do_get_ratio_prefix(duration_style style, nano u) const;
virtual string_type do_get_ratio_prefix(duration_style style, micro u) const;
virtual string_type do_get_ratio_prefix(duration_style style, milli u) const;
virtual string_type do_get_ratio_prefix(duration_style style, centi u) const;
virtual string_type do_get_ratio_prefix(duration_style style, deci u) const;
virtual string_type do_get_ratio_prefix(duration_style style, deca u) const;
virtual string_type do_get_ratio_prefix(duration_style style, hecto u) const;
virtual string_type do_get_ratio_prefix(duration_style style, kilo u) const;
virtual string_type do_get_ratio_prefix(duration_style style, mega u) const;
virtual string_type do_get_ratio_prefix(duration_style style, giga u) const;
virtual string_type do_get_ratio_prefix(duration_style style, tera u) const;
virtual string_type do_get_ratio_prefix(duration_style style, peta u) const;
virtual string_type do_get_ratio_prefix(duration_style style, exa u) const;

```

Parameters:

- **style:** the duration style.
- **u:** the period tag atto.

Returns: depending on the value of `style` return the `ratio_string` symbol or prefix.

Header `<boost/chrono/io/duration_io.hpp>`

```

namespace boost {
  namespace chrono {

    // manipulators

    std::ios_base& symbol_format(std::ios_base& ios);
    std::ios_base& name_format(std::ios_base& ios);
    class duration_fmt;
    template<class CharT, class Traits>
    std::basic_ostream<CharT, Traits>&
    operator <<(std::basic_ostream<CharT, Traits>& os, duration_fmt d);

    template<class CharT, class Traits>
    std::basic_istream<CharT, Traits>&
    operator >>(std::basic_istream<CharT, Traits>& is, duration_fmt d);

    // duration I/O

    template <class CharT, class Traits, class Rep, class Period>
    std::basic_ostream<CharT, Traits>&
    operator <<(std::basic_ostream<CharT, Traits>& os, const duration<Rep, Period>& d);

    template <class CharT, class Traits, class Rep, class Period>
    std::basic_istream<CharT, Traits>&
    operator >>(std::basic_istream<CharT, Traits>& is, duration<Rep, Period>& d)

  }
}

```

I/O Manipulators

There is a parameterized manipulator that takes the `duration_style` as parameter. The symbol or name format can be easily chosen by streaming a `symbol_format` or `name_format` manipulators respectively.

Template Class `duration_fmt`

```
class duration_fmt
{
public:

    explicit duration_fmt(duration_style style) noexcept;

#ifdef BOOST_NO_EXPLICIT_CONVERSION_OPERATORS
    explicit
    operator duration_style() const noexcept;
#endif
    duration_style get_duration_style() const noexcept;
};

template<class CharT, class Traits>
std::basic_ostream<CharT, Traits>&
operator <<(std::basic_ostream<CharT, Traits>& os, duration_fmt d);

template<class CharT, class Traits>
std::basic_istream<CharT, Traits>&
operator >>(std::basic_istream<CharT, Traits>& is, duration_fmt d);
```

Constructor `duration_fmt(duration_style)`

```
explicit duration_fmt(duration_style f) noexcept;
```

Effects: Constructs a `duration_fmt` by storing `f`.

Post Conditions: `static_cast<duration_style>(*this) == f`.

Member Function `operator duration_style()`

```
explicit operator duration_style() const noexcept;
duration_style get_duration_style() const noexcept;
```

Returns: The stored `duration_fmt` `f`.

Member Function `operator <<(basic_ostream<>&, duration_fmt)`

```
template<class CharT, class Traits>
    basic_ostream<CharT, Traits>&
    operator<<(basic_ostream<CharT, Traits>& s, duration_fmt d);
```

Effects: `set_duration_style(s, static_cast<duration_style>(d))`.

Returns: `s`.

Member Function `operator >>(basic_istream<>&, duration_fmt)`

```
template<class CharT, class Traits>
    basic_istream<CharT, Traits>&
    operator>>(basic_istream<CharT, Traits>& s, duration_fmt d);
```

Effects: `set_duration_style(s, static_cast<duration_style>(d))`.

Returns: `s`.

Non Member Function `symbol_format(ios_base&)`

```
std::ios_base& symbol_format(ios_base& ios);
```

Effects: `set_duration_style(s, duration_style::symbol)`.

Returns: `ios`

Non Member Function `name_format(ios_base&)`

```
std::ios_base& name_format(ios_base& ios);
```

Effects: `set_duration_style(s, duration_style::prefix)`.

Returns: `ios`

I/O Streams Operations

Member Function operator <<(basic_ostream<>&, const duration<>& d)

Any `duration` can be streamed out to a `basic_ostream`. The run-time value of the `duration` is formatted according to the rules and current format settings for `duration::rep` and the `duration_units` facet.

```
template <class CharT, class Traits, class Rep, class Period>
    std::basic_ostream<CharT, Traits>&
    operator<<(std::basic_ostream<CharT, Traits>& os, const duration<Rep, Period>& d);
```

Effects: Behaves as a formatted output function. After constructing a sentry object, if the sentry converts to true, calls to `facet.put(os, os, os.fill(), d)` where `facet` is the `duration_put<CharT>` facet associated to `os` or a new created instance of the default `duration_put<CharT>` facet.

Returns: `os`.

Member Function operator <<(basic_istream<>&, const duration<>& d)

```
template <class CharT, class Traits, class Rep, class Period>
    std::basic_istream<CharT, Traits>&
    operator>>(std::basic_istream<CharT, Traits>& is, duration<Rep, Period>& d)
```

Effects: Behaves as a formatted input function. After constructing a sentry object, if the sentry converts to true, calls to `facet.get(is, std::istreambuf_iterator<CharT, Traits>(), is, err, d)` where `facet` is the `duration_get<CharT>` facet associated to `is` or a new created instance of the default `duration_get<CharT>` facet.

If any step fails, calls `os.setstate(std::ios_base::failbit | std::ios_base::badbit)`.

Returns: `is`

Header <boost/chrono/io/time_point_get.hpp>

```

namespace boost {
  namespace chrono {
    template <class CharT, class InputIterator = std::istreambuf_iterator<CharT> >
      class time_point_get;
  }
}

```

Template Class time_point_get

```

template <class CharT, class InputIterator = std::istreambuf_iterator<CharT> >
class time_point_get: public std::locale::facet
{
public:
  typedef CharT char_type; // Type of character the facet is instantiated on.
  typedef InputIterator iter_type; // Type of iterator used to scan the character buffer.

  explicit __time_point_get_c(size_t refs = 0);

  template <class Clock, class Duration>
  iter_type __time_point_get_get(iter_type i, iter_type e, std::ios_base& is, std::ios_base::iostate& err,
    time_point<Clock, Duration> &tp, const char_type *pattern, const char_type *pat_end) const;

  template <class Clock, class Duration>
  iter_type __time_point_get_get2(iter_type i, iter_type e, std::ios_base& is, std::ios_base::iostate& err,
    time_point<Clock, Duration> &tp) const;

  template <typename Rep, typename Period>
  iter_type __time_point_get_get_duration(iter_type i, iter_type e, std::ios_base& is, std::ios_base::iostate& err,
    duration<Rep, Period>& d) const;

  template <class Clock>
  iter_type __time_point_get_get_epoch(iter_type i, iter_type e, std::ios_base& is, std::ios_base::iostate& err) const;

  static std::locale::id id; // Unique identifier for this type of facet.

  __time_point_get_d();
};

```

time_point_get is used to parse a character sequence, extracting the duration and the epoch into a class time_point.

The pattern can contain the format specifiers %d and %e in any order.

User confirmation is required for reliable parsing of user-entered durations, but machine-generated formats can be parsed reliably. This allows parsers to be aggressive about interpreting user variations on standard formats.

If the end iterator is reached during parsing the member function sets std::ios_base::eofbit in err.

Constructor time_point_get(size_t)

```
explicit time_point_get(size_t refs);
```

Constructs a __time_point_get facet.

Parameters:

- **refs:** references

Effects: Constructs a `duration_put` facet. If the `refs` argument is 0 then destruction of the object is delegated to the locale, or locales, containing it. This allows the user to ignore lifetime management issues. On the other had, if `refs` is 1 then the object must be explicitly deleted; `locale` will not do so. In this case, the object can be maintained across the lifetime of multiple locales.

Destructor `~time_point_get()`

```
~time_point_get();
```

Effects: Destroy the facet.

Template Member Function `get(iter_type, iter_type, std::ios_base&, std::ios_base::iostate&, time_point<Clock, Duration>&, const CharT*, const CharT*)`

```
template <class Clock, class Duration>
iter_type get(iter_type s, iter_type end, std::ios_base& ios, std::ios_base::iostate& err,
              time_point<Clock, Duration> &tp, const char_type *pattern, const char_type *pat_end) const;
```

Parameters:

- **s:** start input stream iterator
- **end:** end input stream iterator
- **ios:** a reference to a `ios_base`
- **err:** the `ios_base::iostate`
- **tp:** the `time_point`
- **pattern:** begin of the formatting pattern
- **pat_end:** end of the formatting pattern

Requires: `[pattern, pat_end)` must be a valid range.

Effects: The function starts by evaluating `err = std::ios_base::goodbit`. It then enters a loop, reading zero or more characters from `s` at each iteration. Unless otherwise specified below, the loop terminates when the first of the following conditions holds:

- The expression `pattern == pat_end` evaluates to true.
- The expression `err == std::ios_base::goodbit` evaluates to false.
- The expression `s == end` evaluates to true, in which case the function evaluates `err = std::ios_base::eofbit | std::ios_base::failbit`.
- The next element of `pattern` is equal to `'%'`, followed by a conversion specifier character, the functions `get_duration` or `get_epoch` are called depending on whether the format is `'d'` or `'e'`. If the number of elements in the range `[pattern, pat_end)` is not sufficient to unambiguously determine whether the conversion specification is complete and valid, the function evaluates `err |= std::ios_base::failbit`. Otherwise, the function evaluates `s = do_get(s, end, ios, err, d)`. If `err == std::ios_base::goodbit` holds after the evaluation of the expression, the function increments `pattern` to point just past the end of the conversion specification and continues looping.
- The expression `isspace(*pattern, ios.getloc())` evaluates to true, in which case the function first increments `pattern` until `pattern == pat_end || !isspace(*pattern, ios.getloc())` evaluates to true, then advances `s` until `s == end || !isspace(*s, ios.getloc())` is true, and finally resumes looping.

- The next character read from `s` matches the element pointed to by `pattern` in a case-insensitive comparison, in which case the function evaluates `++pattern`, `++s` and continues looping. Otherwise, the function evaluates `err = std::ios_base::failbit`.

Returns: An iterator pointing just beyond the last character that can be determined to be part of a valid `time_point`.

Template Member Function `get(iter_type, iter_type, std::ios_base&, std::ios_base::iostate&, time_point<Clock, Duration>&)`

```
template <class Clock, class Duration>
iter_type get(iter_type s, iter_type end, std::ios_base& ios, std::ios_base::iostate& err,
              time_point<Clock, Duration> &tp) const;
```

Parameters:

- **s:** start input stream iterator
- **end:** end input stream iterator
- **ios:** a reference to a `ios_base`
- **err:** the `ios_base::iostate`
- **tp:** the `time_point`

Effects: Stores the duration pattern from the `duration_unit` facet in let say `str`. Last as if

```
return get(s, end, ios, err, ios, d, str.data(), str.data() + str.size());
```

Returns: An iterator pointing just beyond the last character that can be determined to be part of a valid name.

Template Member Function `get_duration(iter_type, iter_type, std::ios_base&, std::ios_base::iostate&, duration<Rep, Period>&)`

```
template <typename Rep, typename Period>
iter_type get_duration(iter_type s, iter_type end, std::ios_base& ios, std::ios_base::iostate& err,
                       duration<Rep, Period>& d) const;
```

Effects: As if

```
return facet.get(s, end, ios, err, d);
```

where `facet` is either the `duration_get` facet associated to the `ios` or an instance of the default `duration_get` facet.

Returns: An iterator pointing just beyond the last character that can be determined to be part of a valid duration.

Template Member Function `get_epoch(iter_type, iter_type, std::ios_base&, std::ios_base::iostate&)`

```
template <class Clock>
iter_type get_epoch(iter_type s, iter_type end, std::ios_base& ios, std::ios_base::iostate& err) const;
```

Effects: Let `facet` be the `__time_point_units` facet associated to `ios` or a new instance of the default `__time_point_units_default` facet. Let `epoch` be the epoch string associated to the `Clock` using this facet. Scans `s` to match `epoch` or end is reached.

If not match before the end is reached `std::ios_base::failbit` is set in `err`. If end is reached `std::ios_base::failbit` is set in `err`.

Returns: An iterator pointing just beyond the last character that can be determined to be part of a epoch.

Header `<boost/chrono/io/time_point_put.hpp>`

```

namespace boost {
  namespace chrono {
    template <class CharT, class OutputIterator = std::ostreambuf_iterator<CharT> >
      class time_point_put;
  }
}

```

Template Class `time_point_put`

The `__time_point_put` facet provides facilities for formatted output of `time_point` values. The member function of `__time_point_put` take a `time_point` and format it into character string representation.

tparam CharT a character type tparam OutputIterator a model of OutputIterator

```

template <class CharT, class OutputIterator = std::ostreambuf_iterator<CharT> >
class time_point_put: public std::locale::facet
{
public:
  typedef CharT char_type; // Type of character the facet is instantiated on.
  typedef std::basic_string<CharT> string_type; // Type of character string passed to member
functions.
  typedef OutputIterator iter_type; // Type of iterator used to write in the character buffer.

  explicit time_point_put(size_t refs = 0);
  ~time_point_put();

  template <class Clock, class Duration>
  iter_type put(iter_type i, std::ios_base& ios, char_type fill, time_point<Clock, Dura-
tion> const& tp, const CharT* pattern,
               const CharT* pat_end) const;
  template <class Clock, class Duration>
  iter_type put(iter_type i, std::ios_base& ios, char_type fill, time_point<Clock, Dura-
tion> const& tp) const;
  template <typename Rep, typename Period>
  iter_type put_duration(iter_type i, std::ios_base& ios, char_type fill, duration<Rep, Peri-
od> const& d) const;
  template <typename Clock>
  iter_type put_epoch(iter_type i, std::ios_base& os) const;

  static std::locale::id id; // Unique identifier for this type of facet.

};

```

Constructor `time_point_put(size_t)`

```
explicit time_point_put(size_t refs = 0);
```

Construct a `time_point_put` facet.

Effects: Construct a `time_point_put` facet. If the `refs` argument is 0 then destruction of the object is delegated to the locale, or locales, containing it. This allows the user to ignore lifetime management issues. On the other had, if `refs` is 1 then the object must be explicitly deleted; the locale will not do so. In this case, the object can be maintained across the lifetime of multiple locales.

Parameters:

- **refs:** references

Member Function `put()`

```
template <class Clock, class Duration>
iter_type put(iter_type i, std::ios_base& ios, char_type fill, time_point<Clock, Duration> const& tp, const CharT* pattern, const CharT* pat_end) const;
```

Parameters:

- **i**: an output stream iterator
- **ios**: a reference to a `ios_base`
- **fill**: the character used as filler
- **tp**: the `time_point`
- **pattern**: begin of the formatting pattern
- **pat_end**: end of the formatting pattern

Effects: Steps through the sequence from `pattern` to `pat_end`, identifying characters that are part of a pattern sequence. Each character that is not part of a pattern sequence is written to `s` immediately, and each pattern sequence, as it is identified, results in a call to `__put_duration` or `__put_epoch`; thus, pattern elements and other characters are interleaved in the output in the order in which they appear in the pattern. Pattern sequences are identified by converting each character `c` to a `char` value as if by `ct.narrow(c, 0)`, where `ct` is a reference to `ctype<charT>` obtained from `ios.getloc()`. The first character of each sequence is equal to `'%'`, followed by a pattern specifier character `spec`, which can be `'d'` for the duration value or `'e'` for the epoch. For each valid pattern sequence identified, calls `put_duration(s, ios, fill, tp.time_since_epoch())` or `put_epoch(s, ios)`.

Returns: An iterator pointing immediately after the last character produced.

Member Function `put()`

```
template <class Clock, class Duration>
iter_type put(iter_type i, std::ios_base& ios, char_type fill, time_point<Clock, Duration> const& tp) const;
```

Parameters:

- **i**: an output stream iterator
- **ios**: a reference to a `ios_base`
- **fill**: the character used as filler
- **tp**: the `time_point`
- **tern**: begin of the formatting pattern
- **pat_end**: end of the formatting pattern

Effects: Stores the `time_point` pattern from the `__time_point_unit` facet in let say `str`. Last as if

```
return put(s, ios, fill, tp, str.data(), str.data() + str.size());
```

Returns: An iterator pointing immediately after the last character produced.

Member Function `put_duration()`

```
template <typename Rep, typename Period>
iter_type put_duration(iter_type i, std::ios_base& ios, char_type fill, duration<Rep, Peri-
od> const& d) const;
```

Parameters:

- **i**: an output stream iterator
- **ios**: a reference to a `ios_base`
- **fill**: the character used as filler
- **d**: the `duration`

Effects: As if `facet.put(s, ios, fill, d)` where `facet` is the `duration_put<CharT>` facet associated to the `ios` or a new instance of `duration_put<CharT>`.

Returns: An iterator pointing immediately after the last character produced.

Member Function `put_epoch()`

```
template <typename Clock>
iter_type put_epoch(iter_type i, std::ios_base& ios) const;
```

Parameters:

- **i**: an output stream iterator
- **ios**: a reference to a `ios_base`

Effects: As if

```
string_type str = facet.template get_epoch<Clock>();
s=std::copy(str.begin(), str.end(), s);
```

where `facet` is the `__time_point_units<CharT>` facet associated to the `ios` or a new instance of `__time_point_units_default<CharT>`.

Returns: `s`, iterator pointing immediately after the last character produced.

Header `<boost/chrono/io/time_point_units.hpp>`

```
namespace boost {
  namespace chrono {
    template <typename CharT=char>
    class time_point_units;
    template <typename CharT=char>
    class time_point_units_default,
  }
}
```

Template Class `time_point_units`

`__time_point_units` facet gives useful information about the `time_point` pattern, the text associated to a `time_point`'s epoch,

```

template <typename CharT=char>
class time_point_units: public std::locale::facet
{
public:
    typedef CharT char_type; // Type of character the facet is instantiated on.
    typedef std::basic_string<char_type> string_type; // Type of character string used by member functions.
    static std::locale::id id; // Unique identifier for this type of facet.

    explicit time_point_units(size_t refs = 0);

    virtual string_type get_pattern() const = 0;
    template <typename Clock>
    string_type get_epoch() const;

protected:
    virtual ~time_point_units();
    virtual string_type do_get_epoch(system_clock) const=0;
    virtual string_type do_get_epoch(steady_clock) const=0;

#if defined(BOOST_CHRONO_HAS_PROCESS_CLOCKS)
    virtual string_type do_get_epoch(process_real_cpu_clock) const=0;
    virtual string_type do_get_epoch(process_user_cpu_clock) const=0;
    virtual string_type do_get_epoch(process_system_cpu_clock) const=0;
    virtual string_type do_get_epoch(process_cpu_clock) const=0;
#endif
#if defined(BOOST_CHRONO_HAS_THREAD_CLOCK)
    virtual string_type do_get_epoch(thread_clock) const=0;
#endif

};

```

Constructor `time_point_units()`

```
explicit time_point_units(size_t refs = 0);
```

Construct a `__time_point_units` facet.

Parameters:

- **refs:** references

Effects: Construct a `__time_point_units` facet. If the `refs` argument is 0 then destruction of the object is delegated to the locale, or locales, containing it. This allows the user to ignore lifetime management issues. On the other had, if `refs` is 1 then the object must be explicitly deleted; the locale will not do so. In this case, the object can be maintained across the lifetime of multiple locales.

Member Function `get_pattern()`

```
virtual string_type get_pattern() const = 0;
```

Returns: the pattern to be used by default.

Member Function `get_epoch()`

```
template <typename Clock>
string_type get_epoch() const;
```

Returns: the epoch associated to the clock `Clock` calling `__do_get_epoch(Clock())`

Destructor `time_point_units()`

```
virtual ~time_point_units();
```

Destroy the facet.

Member Function `do_get_epoch(system_clock)`

```
virtual string_type do_get_epoch(system_clock) const=0;
```

Parameters:

- **c**: a dummy instance of `system_clock`.

Returns: The epoch string associated to the `system_clock`.

Member Function `do_get_epoch(steady_clock)`

```
virtual string_type do_get_epoch(steady_clock) const=0;
```

Parameters:

- **c**: a dummy instance of `steady_clock`.

Returns: The epoch string associated to the `steady_clock`.

Member Function `do_get_epoch(process_real_cpu_clock)`

```
#if defined(BOOST_CHRONO_HAS_PROCESS_CLOCKS)
    virtual string_type do_get_epoch(process_real_cpu_clock) const=0;
#endif
```

Parameters:

- **c**: a dummy instance of `process_real_cpu_clock`.

Returns: The epoch string associated to the `process_real_cpu_clock`.

Member Function `do_get_epoch(process_user_cpu_clock)`

```
#if defined(BOOST_CHRONO_HAS_PROCESS_CLOCKS)
    virtual string_type do_get_epoch(process_user_cpu_clock) const=0;
#endif
```

Parameters:

- **c**: a dummy instance of `process_real_cpu_clock`.

Returns: The epoch string associated to the `process_user_cpu_clock`.

Member Function `do_get_epoch(process_system_cpu_clock)`

```
#if defined(BOOST_CHRONO_HAS_PROCESS_CLOCKS)
    virtual string_type do_get_epoch(process_system_cpu_clock) const=0;
#endif
```

Parameters:

- **c**: a dummy instance of `process_system_cpu_clock`.

Returns: The epoch string associated to the `process_user_cpu_clock`.

Member Function `do_get_epoch(process_cpu_clock)`

```
#if defined(BOOST_CHRONO_HAS_PROCESS_CLOCKS)
    virtual string_type do_get_epoch(process_cpu_clock) const=0;
#endif
```

Parameters:

- **c**: a dummy instance of `process_cpu_clock`.

Returns: The epoch string associated to the `process_cpu_clock`.

Member Function `do_get_epoch(thread_clock)`

```
#if defined(BOOST_CHRONO_HAS_THREAD_CLOCK)
    virtual string_type do_get_epoch(thread_clock) const=0;
#endif
```

Parameters:

- **c**: a dummy instance of `thread_clock`.

Returns: The epoch string associated to the `thread_clock`.

Template Class `time_point_units_default`

```

// This class is used to define the strings for the default English
template <typename CharT=char>
class time_point_units_default: public time_point_units<CharT>
{
public:
    typedef CharT char_type; // Type of character the facet is instantiated on.
    typedef std::basic_string<char_type> string_type; // Type of character string used by mem-
ber functions.

    explicit time_point_units_default(size_t refs = 0);
    ~time_point_units_default();

    /**
     * __returns the default pattern "%d%e".
     */
    string_type get_pattern() const;

protected:
    /**
     * [param c a dummy instance of __system_clock.
     * __returns The epoch string returned by `clock_string<system_clock,CharT>::since()`.
     */
    string_type do_get_epoch(system_clock ) const;
    /**
     * [param c a dummy instance of __steady_clock.
     * __returns The epoch string returned by `clock_string<steady_clock,CharT>::since()`.
     */
    string_type do_get_epoch(steady_clock ) const;
#if defined(BOOST_CHRONO_HAS_PROCESS_CLOCKS)
    /**
     * [param c a dummy instance of __process_real_cpu_clock.
     * __returns The epoch string returned by `clock_string<pro-
cess_real_cpu_clock,CharT>::since()`.
     */
    string_type do_get_epoch(process_real_cpu_clock ) const;
    /**
     * [param c a dummy instance of __process_user_cpu_clock.
     * __returns The epoch string returned by `clock_string<pro-
cess_user_cpu_clock,CharT>::since()`.
     */
    string_type do_get_epoch(process_user_cpu_clock ) const;
    /**
     * [param c a dummy instance of __process_system_cpu_clock.
     * __returns The epoch string returned by `clock_string<process_sys-
tem_cpu_clock,CharT>::since()`.
     */
    string_type do_get_epoch(process_system_cpu_clock ) const;
    /**
     * [param c a dummy instance of __process_cpu_clock.
     * __returns The epoch string returned by `clock_string<process_cpu_clock,CharT>::since()`.
     */
    string_type do_get_epoch(process_cpu_clock ) const;
#endif
#if defined(BOOST_CHRONO_HAS_THREAD_CLOCK)
    /**
     * [param c a dummy instance of __thread_clock.

```

```

    * __returns The epoch string returned by `clock_string<thread_clock,CharT>::since()`.
    */
    string_type do_get_epoch(thread_clock ) const;
#endif

};

```

Header <boost/chrono/io/time_point_io.hpp>

```

namespace boost {
namespace chrono {

    // manipulators

    unspecified time_fmt(timezone tz);
    template<class CharT>
    unspecified time_fmt(timezone tz, basic_string<CharT> f);
    template<class CharT>
    unspecified time_fmt(timezone tz, const CharT* f);

    // i/o state savers

    template<typename CharT = char, typename Traits = std::char_traits<CharT> >
    struct timezone_io_saver
    {
        typedef std::basic_ios<CharT, Traits> state_type;
        typedef timezone aspect_type;

        explicit timezone_io_saver(state_type &s);
        timezone_io_saver(state_type &s, aspect_type new_value);
        ~timezone_io_saver();
        void timezone_io_saver__restore();
    };

    template<typename CharT = char, typename Traits = std::char_traits<CharT> >
    struct time_fmt_io_saver
    {
        typedef std::basic_ios<CharT, Traits> state_type;

        explicit time_fmt_io_saver(state_type &s);
        time_fmt_io_saver(state_type &s, basic_string<CharT> const& new_value);
        ~time_fmt_io_saver();
        void restore();
    };

    // system_clock I/O

    template <class CharT, class Traits, class Duration>
    basic_ostream<CharT, Traits>&
    operator<<(basic_ostream<CharT, Traits>& os,
              const time_point<system_clock, Duration>& tp);

    template <class CharT, class Traits, class Duration>
    basic_istream<CharT, Traits>&
    operator>>(basic_istream<CharT, Traits>& is,
              time_point<system_clock, Duration>& tp);

    // Other Clocks I/O

    template <class CharT, class Traits, class Clock, class Duration>

```

```

std::basic_ostream<CharT, Traits>&
operator<<(std::basic_ostream<CharT, Traits>& os,
          const time_point<Clock, Duration>& tp);

template <class CharT, class Traits, class Clock, class Duration>
std::basic_istream<CharT, Traits>&
operator>>(std::basic_istream<CharT, Traits>& is,
          time_point<Clock, Duration>& tp);
}
}

```

I/O Manipulators

Non Member Function `time_fmt(timezone)`

```
unspecified time_fmt(timezone tz);
```

Returns: An unspecified object that when streamed to a `basic_ostream<CharT, Traits>` or `basic_istream<CharT, Traits>` `s` will have the effects of:

```
set_timezone(s, tz);
```

Non Member Function `time_fmt(timezone, string)`

```

template<class CharT>
unspecified time_fmt(timezone tz, basic_string<CharT> f);
template<class CharT>
unspecified time_fmt(timezone tz, const CharT* f);

```

Returns: An unspecified object that when streamed to a `basic_ostream<CharT, Traits>` or `basic_istream<CharT, Traits>` `s` will have the effects of:

```

set_timezone(s, tz);
set_time_fmt<CharT>(s, f);

```

I/O Streams Operations

`system_clock`

Non Member Function `operator<<()`

```

template <class CharT, class Traits, class Duration>
std::basic_ostream<CharT, Traits>&
operator<<(std::basic_ostream<CharT, Traits>& os,
          const time_point<system_clock, Duration>& tp);

```

Effects: Behaves as a formatted output function. After constructing a sentry object, if the sentry converts to true, sets a local variable `tz` of type `timezone` to `get_timezone(os)`. Additionally the format string obtained with `get_time_fmt()` is recorded as a pair of `const CharT*`. If the stream has no `time_punct` facet, then this pair of `const CharT*` that represent an empty range.

Next `tp` is converted to a `time_t`, and this `time_t` is converted to a `tm`. The conversion to `tm` use `gmtime` (when available) if the `timezone` is `utc`, else it use `localtime` (if available).

Using the `std::time_put` facet stored in `os`, this inserter writes characters to the stream using the `tm` and the formatting string stored in the `time_punct` facet, unless that facet was missing, or unless it provided an empty string.

If the formatting string is empty, then output as follows:

First output `tm` using `"%F %H:%M: "`

Next output a `double` representing the number of seconds stored in the `tm` plus the fractional seconds represented in `tp`. The format shall be `ios::fixed` and the precision shall be sufficient to represent `system_clock::duration` exactly (e.g. if `system_clock::period` is `micro`, the precision should be sufficient to output six digits following the decimal point). If the number of seconds is less than 10, the output shall be prefixed by `'0'`.

Finally if `tz` is `local`, output the `tm` using the pattern `"%z"`. Else append the sequence `" +0000"` to the stream.

If any step fails, calls `os.setstate(ios_base::failbit | ios_base::badbit)`.

Returns: `os`

Non Member Function `operator>>()`

```
template <class CharT, class Traits, class Duration>
    std::basic_istream<CharT, Traits>&
    operator>>(std::basic_istream<CharT, Traits>& is,
               time_point<system_clock, Duration>& tp);
```

Effects: Behaves as a formatted input function. After constructing a sentry object, if the sentry converts to true, obtains a `std::time_get` facet from `is`, and obtains a formatting string in the same manner as described for insertion operator. Extract a `tm` using the supplied formatting string, or if empty, defaulted as described for the insertion operator. Note that extraction does not use the `timezone` data stored in the `is` for the defaulted string as the `timezone` information is stored in the stream.

Any `time_point<system_clock, Duration>` inserted, and then extracted should result in an equal `time_point<system_clock, Duration>`, excepting any precision that did not get inserted.

Example:

```
void test(std::chrono::system_clock::time_point tp)
{
    std::stringstream s;
    s << tp;
    boost::chrono::system_clock::time_point tp2;
    s >> tp2;
    assert(tp == tp2);
}
```

Returns: `is`

Other Clocks

Non Member Function `operator<<()`

```
template <class CharT, class Traits, class Clock, class Duration>
    std::basic_ostream<CharT, Traits>&
    operator<<(std::basic_ostream<CharT, Traits>& os,
               const time_point<Clock, Duration>& tp);
```

Effects: Behaves as a formatted output function. After constructing a sentry object, if the sentry converts to true, calls to `facet.put(os, os, os.fill(), tp)` where `facet` is the `time_point_put<CharT>` facet associated to `os` or a new created instance of the default `time_point_put<CharT>` facet.

Returns: `os`.

Example:

```
22644271279698 nanoseconds since boot
```

Non Member Function `operator>>()`

```
template <class CharT, class Traits, class Clock, class Duration>
    std::basic_istream<CharT, Traits>&
    operator>>(std::basic_istream<CharT, Traits>& is,
               time_point<Clock, Duration>& tp);
```

Extracts `tp` from the stream `is`.

Effects: Behaves as a formatted input function. After constructing a sentry object, if the sentry converts to true, calls to `facet.get(is, std::istreambuf_iterator<CharT, Traits>(), is, err, tp)` where `facet` is the `time_point_get<CharT>` facet associated to `is` or a new created instance of the default `time_point_get<CharT>` facet.

If any step fails, calls `os.setstate(std::ios_base::failbit | std::ios_base::badbit)`.

Returns: `is`.

Chrono Rounding Utilities

Header `<boost/chrono/floor.hpp>`

```
namespace boost { namespace chrono {
    template <class To, class Rep, class Period>
        To floor(const duration<Rep, Period>& d);
} }
```

This function round down the given parameter.

Header `<boost/chrono/round.hpp>`

```
namespace boost { namespace chrono {
    template <class To, class Rep, class Period>
        To round(const duration<Rep, Period>& d);
} }
```

This function round to nearest, to even on tie the given parameter.

Header `<boost/chrono/ceil.hpp>`

```
namespace boost { namespace chrono {
    template <class To, class Rep, class Period>
        To ceil(const duration<Rep, Period>& d);
} }
```

This function round up the given parameter.

Other Clocks

Header `<boost/chrono/process_cpu_clocks.hpp>`

Knowing how long a program takes to execute is useful in both test and production environments. It is also helpful if such timing information is broken down into real (wall clock) time, CPU time spent by the user, and CPU time spent by the operating system servicing user requests.

Process clocks don't include the time spent by the child process.

```
#define BOOST_CHRONO_HAS_PROCESS_CLOCKS

namespace boost { namespace chrono {

    class process_real_cpu_clock;
    class process_user_cpu_clock;
    class process_system_cpu_clock;
    class process_cpu_clock;

    template <typename Rep>
    struct process_times;
    template <class CharT, class Traits, class Rep>
    std::basic_ostream<CharT, Traits>&
    operator<<(std::basic_ostream<CharT, Traits>& os,
              process_times<Rep> const& rhs);

    template <class CharT, class Traits, class Rep>
    std::basic_istream<CharT, Traits>&
    operator>>(std::basic_istream<CharT, Traits>& is,
              process_times<Rep> const& rhs);

    template <class Rep>
    struct duration_values<process_times<Rep> >;

    template <class CharT>
    struct clock_string<process_real_cpu_clock, CharT>;
    struct clock_string<process_user_cpu_clock, CharT>;
    struct clock_string<process_system_cpu_clock, CharT>;
    struct clock_string<process_cpu_clock, CharT>;

} }
namespace std {
    template <class Rep>
    class numeric_limits<boost::chrono::process_times<Rep> >;
}
}
```

Macro `BOOST_CHRONO_HAS_PROCESS_CLOCKS`

This macro is defined if the platform supports process clocks.

Class `process_real_cpu_clock`

`process_real_cpu_clock` satisfy the `Clock` requirements.

`process_real_cpu_clock` class provides access to the real process wall-clock steady clock, i.e. the real CPU-time clock of the calling process. The process relative current time can be obtained by calling `process_real_cpu_clock::now()`.

```

class process_real_cpu_clock {
public:
    typedef nanoseconds          duration;
    typedef duration::rep        rep;
    typedef duration::period     period;
    typedef chrono::time_point<process_real_cpu_clock> time_point;
    static constexpr bool is_steady = true;

    static time_point now( ) noexcept;
    static time_point now( system::error_code & ec );
};

```

Class `process_user_cpu_clock`

`process_user_cpu_clock` satisfy the `Clock` requirements.

`process_user_cpu_clock` class provides access to the user CPU-time steady clock of the calling process. The process relative user current time can be obtained by calling `process_user_cpu_clock::now()`.

```

class process_user_cpu_clock {
public:
    typedef nanoseconds          duration;
    typedef duration::rep        rep;
    typedef duration::period     period;
    typedef chrono::time_point<process_user_cpu_clock> time_point;
    static constexpr bool is_steady = true;

    static time_point now( ) noexcept;
    static time_point now( system::error_code & ec );
};

```

Class `process_system_cpu_clock`

`process_system_cpu_clock` satisfy the `Clock` requirements.

`process_system_cpu_clock` class provides access to the system CPU-time steady clock of the calling process. The process relative system current time can be obtained by calling `process_system_cpu_clock::now()`.

```

class process_system_cpu_clock {
public:
    typedef nanoseconds          duration;
    typedef duration::rep        rep;
    typedef duration::period     period;
    typedef chrono::time_point<process_system_cpu_clock> time_point;
    static constexpr bool is_steady = true;

    static time_point now( ) noexcept;
    static time_point now( system::error_code & ec );
};

```

Class `process_cpu_clock`

`process_cpu_clock` can be considered as a `tuple<process_real_cpu_clock, process_user_cpu_clock, process_system_cpu_clock>`.

`process_cpu_clock` provides a thin wrapper around the operating system's process time API. For POSIX-like systems, that's the `times()` function, while for Windows, it's the `GetProcessTimes()` function.

The process relative real, user and system current time can be obtained at once by calling `process_clocks::now()`.

```

class process_cpu_clock
{
public:
    typedef process_times<nanoseconds::rep> times ;

    typedef duration<times, nano> duration;
    typedef duration::rep rep;
    typedef duration::period period;
    typedef chrono::time_point<process_cpu_clock> time_point;
    static constexpr bool is_steady = true;

    static time_point now( ) noexcept;
    static time_point now( system::error_code & ec );
};

```

Template Class `process_times`

This class is the representation of the `process_cpu_clock::duration` class. As such it needs to implements the arithmetic operators.

```

template <typename Rep>
struct process_times : arithmetic<process_times<Rep>,
    multiplicative<process_times<Rep>, Rep,
    less_than_comparable<process_times<Rep> > > >
{
    Rep real; // real (i.e wall clock) time
    Rep user; // user cpu time
    Rep system; // system cpu time

    times();
    times(
        process_real_cpu_clock::rep r,
        process_user_cpu_clock::rep u,
        process_system_cpu_clock::rep s);

    template <typename Rep2>
    explicit process_times(
        Rep2 r);
    template <typename Rep2>
    explicit process_times(
        process_times<Rep2> const& rhs);
    operator rep() const;

    bool operator==(process_times const& rhs);
    template <typename Rep2>
    bool operator==(process_times<Rep2> const& rhs);

    times operator+=(process_times const& rhs);
    times operator-=(process_times const& rhs);
    times operator*=(process_times const& rhs);
    times operator/=(process_times const& rhs);
    bool operator<(process_times const & rhs) const;
};

```

`process_times` Input/Output

```

template <class CharT, class Traits, class Rep>
std::basic_ostream<CharT, Traits>&
operator<<(std::basic_ostream<CharT, Traits>& os,
    process_times<Rep> const& rhs);

```

Effects: Output each part separated by ';' and surrounded by '{', '}'.

Throws: None.

```
template <class CharT, class Traits, class Rep>
std::basic_istream<CharT, Traits>&
operator>>(std::basic_istream<CharT, Traits>& is,
           process_times<Rep> const& rhs);
```

Effects: overrides the value of rhs if the input stream has the format "{r;u;s}". Otherwise, set the input stream state as failbit | eofbit.

Throws: None.

`duration_values` Specialization for `process_times<>`

```
template <class Rep>
struct duration_values<process_times<Rep> >
{
    static process_times<Rep> zero();
    static process_times<Rep> max();
    static process_times<Rep> min();
};
```

The times specific functions `zero()`, `max()` and `min()` uses the relative functions on the representation of each component.

`clock_string<process_real_cpu_clock>` Specialization

```
template <class CharT>
struct clock_string<process_real_cpu_clock, CharT>
{
    static std::basic_string<CharT> name();
    static std::basic_string<CharT> since();
};
```

`clock_string<>::name()` returns "process_real_cpu_clock".

`clock_string<>::since()` returns " since process start-up"

`clock_string<process_user_cpu_clock>` Specialization

```
template <class CharT>
struct clock_string<process_user_cpu_clock, CharT>
{
    static std::basic_string<CharT> name();
    static std::basic_string<CharT> since();
};
```

`clock_string<>::name()` returns "process_user_cpu_clock".

`clock_string<>::since()` returns " since process start-up"

clock_string<process_system_cpu_clock> Specialization

```
template <class CharT>
struct clock_string<process_system_cpu_clock, CharT>
{
    static std::basic_string<CharT> name();
    static std::basic_string<CharT> since();
};
```

clock_string<>::name() returns "process_system_cpu_clock".

clock_string<>::since() returns " since process start-up"

clock_string<process_cpu_clock> Specialization

```
template <class CharT>
struct clock_string<process_cpu_clock, CharT>
{
    static std::basic_string<CharT> name();
    static std::basic_string<CharT> since();
};
```

clock_string<>::name() returns "process_cpu_clock".

clock_string<>::since() returns " since process start-up"

numeric_limits Specialization for process_times<>

```
namespace std {
    template <>
    class numeric_limits<boost::chrono::process_times<Rep>> {
        typedef boost::chrono::process_times<Rep> Res;

    public:
        static const bool is_specialized = true;
        static Res min();
        static Res max();
        static Res lowest();
        static const int digits;
        static const int digits10;
        static const bool is_signed = false;
        static const bool is_integer = true;
        static const bool is_exact = true;
        static const int radix = 0;
    };
}
```

The `process_times<Rep>` specialization functions `min()`, `max()` and `lowest()` uses the relative functions on the representation of each component.

Notes

- `min()` returns the tuple of mins.
- `max()` returns the tuple of maxs.
- `lowest()` returns the tuple of lowests.
- `digits` is the sum of (binary) digits.

- `digits10` is the sum of `digits10s`.

Header `<boost/chrono/thread_clock.hpp>`

Knowing the time a thread takes to execute is useful in both test and production environments.

```
#define BOOST_CHRONO_HAS_THREAD_CLOCK
#define BOOST_CHRONO_THREAD_CLOCK_IS_STEADY
namespace boost { namespace chrono {

    class thread_clock;
    template <class CharT>
    struct clock_string<thread_clock, CharT>;

} }
```

Macro `BOOST_CHRONO_HAS_THREAD_CLOCK`

This macro is defined if the platform supports thread clocks.

Macro `BOOST_CHRONO_THREAD_CLOCK_IS_STEADY`

This macro is defined if the platform has a thread clock. Its value is true if it is steady and false otherwise.

Class `thread_clock`

`thread_clock` satisfy the `Clock` requirements.

`thread_clock` class provides access to the real thread wall-clock, i.e. the real CPU-time clock of the calling thread. The thread relative current time can be obtained by calling `thread_clock::now()`.

```
class thread_clock {
public:
    typedef nanoseconds duration;
    typedef duration::rep rep;
    typedef duration::period period;
    typedef chrono::time_point<thread_clock> time_point;
    static constexpr bool is_steady = BOOST_CHRONO_THREAD_CLOCK_IS_STEADY;

    static time_point now( ) noexcept;
    static time_point now( system::error_code & ec );
};
```

`clock_string<thread_clock>` Specialization

```
#if defined(BOOST_CHRONO_HAS_THREAD_CLOCK)
template <class CharT>
struct clock_string<thread_clock, CharT>
{
    static std::basic_string<CharT> name();
    static std::basic_string<CharT> since();
};
#endif
```

`clock_string<>::name()` returns "thread_clock".

`clock_string<>::since()` returns " since thread start-up"

Appendices

Appendix: History

Version 2.0.1, January 18, 2013 - 1.53

Deprecated:

- The chrono i/o version included in Boost.Chrono 1.2.x has been completely refactored in version 2.0.0
- chrono I/O: The manipulators `duration_short`, `duration_long` are deprecated. You should use the parameterized form `duration_fmt` or the renamed manipulators `__duration_symbol` and `__duration_prefix` instead.
- chrono I/O: The `duration_punct<>` facet is deprecated. You should use the `get_duration_style` free function to get the informations and use the `duration_units` facet for localization purposes.

When `BOOST_CHRONO_VERSION==2` the preceding deprecated functions are not available.

Fixes:

- [#7546](#) `time_point<system_clock>` output version 2 fails to compile assigned viboes Bugs Boost 1.53.0 --
- [#7547](#) `time_point<system_clock>` input version 2 fails to compile assigned viboes Bugs Boost 1.53.0 --
- [#7868](#) `chrono_io` parses time incorrectly (1.53 and 1.52)

Version 2.0.0, October 23, 2012 - 1.52

New Features:

- Enhance chrono I/O
 - [#5980](#) Enhance chrono I/O with H. Hinnant proposal [proposal](#) which has the advantage to provide I/O for system clocks using the Gregorian Calendar.
 - [#5981](#) Add i/o state savers for duration and `time_point` formatting state.
 - [#7059](#) Add low level i/o facilities.

Deprecated:

- The chrono i/o version included in Boost.Chrono 1.2.x has been completely refactored in version 2.0.0
- chrono I/O: The manipulators `duration_short`, `duration_long` are deprecated. You should use the parameterized form `duration_fmt` or the renamed manipulators `__duration_symbol` and `__duration_prefix` instead.
- chrono I/O: The `duration_punct<>` facet is deprecated. You should use the `get_duration_style` free function to get the informations and use the `duration_units` facet for localization purposes.

When `BOOST_CHRONO_VERSION==2` the preceding deprecated functions are not available.

Fixes:

- [#7381](#) C++11 compliance: unresolved symbol when assigning a `constexpr` duration to a non-const local variable.
- [#7479](#) Compiles fails with compilers supporting `constexpr` fails if the standard library doesn't provides the `constexpr` interface
- [#7493](#) compile fail on intel-linux-12.1.3.0x because of bug on explicit bool conversion

- [#7542](#) Missing -lpthread in chrono/io tester Sandia-clang-trunk

Would not fix:

- [#6871](#) chrono_io.hpp: operator<<(ostream& os, ...) modifies the state of os.
 - The neww io interface provided in version 2 solves this issue. You should move to the new version.

Known bugs not fixed yet:

- [#7525](#) Wrong clock_string<system_clock>::since() on Windows

Version 1.2.3, August 1, 2012 - 1.51

Fixes:

- [#6918](#) Boost Chrono compilation failure on HP uX due to undefined pthread_getcpuclockid.
- [#6241](#) boost::chrono compilation problems without std::wstring support.
- [#6987](#) Documentation & C++11.
- [#7041](#) time_point.hpp depends on Boost.System.
- [#7042](#) Avoiding time_point and duration dependency on time.h and CLOCK_REALTIME.
- [#7058](#) Make it work when BOOST_NO_EXCEPTIONS is defined.
- [#7069](#) Misspellings in clock_string<thread_clock>.
- [#7081](#) WinError.h capitalization in boost/detail/win/basic_types.hpp.

Version 1.2.2, April 1, 2012 - 1.50

Fixes:

- [#6361](#) integer overflow in boost::chrono::process_real_cpu_clock::now() under Windows 32bits.
- [#6628](#) compiler warning in process_cpu_clocks.hpp.
- [#6666](#) thread_clock.hpp needs pthread.h.

Version 1.2.1, February 1, 2012 - 1.49

Fixes:

- [#6092](#) Input from non integral durations makes the compiler fail.
- [#6093](#) [1/3]second fails as valid duration input.
- [#6113](#) duplicate symbol when BOOST_CHRONO_HEADER_ONLY is defined.
- [#6243](#) Sandia-pgi-11.9: more than one instance of overloaded function "min" matches.
- [#6257](#) process_cpu_clock::now() on linux gives time_points 1/1000 times.

Version 1.2.0, October 17, 2011

New Features:

- [#5979](#) Added chrono rounding utilities as defined By Howard Hinnant [here](#).

- [#5978](#) Added BOOST_CHRONO_HAS_PROCESS_CLOCKS to know if process clocks are available.
- [#5998](#) Make possible to don't provide hybrid error handling.
- [#5906](#) Take in account the constexpr as defined in the standard.
- [#5907](#) Take in account noexcept for compilers supporting it.

Fixes:

- [#2114](#) Enable visibility support (Boost.Chrono part)
- [#5669](#) Intel compiler failure to compile duration.hpp
- [#5909](#) process_cpu_clock::now() on MAC gives time_points 1/1000 times.
- [#5946](#) Process real cpu clock returns the system steady clock (windows).
- [#5974](#) Process real cpu clock should use clock() instead of times() in MAC which is twice faster and have better resolution.

Cleanup:

- [#5975](#) Reduce the combinations of header-only, shared, static link to reduce test time by 50%.
- [#5976](#) chrono_accuracy_test is not deterministic and should be removed from the regression tests
- [#5977](#) Remove old files from Beman's version. Some old files included in the Beman's version and not documented in the reviewed version that have been definitely removed from the repository as
 - boost/chrono/timer.hpp,
 - boost/chrono/process_times.hpp
 - boost/chrono/detail/process_clock.hpp,
 - boost/chrono/detail/mac/process_clock.hpp,
 - boost/chrono/detail/posix/process_clock.hpp,
 - boost/chrono/detail/win/process_clock.hpp,
 - boost/chrono/detail/run_timer.hpp,
 - boost/chrono/detail/run_timer_static.hpp,

Version 1.1.0, Mars 17, 2011

New Features:

- [#????](#) Added time_point unary operators +,-,++,-- and binary operators +, - with Rep at RHS.
- [#5323](#) Add Associated type difference_type for chrono::time_point.

Fixes:

- [#5322](#) Explicit default constructed chrono::durations are uninitialized

Version 1.0.0, January 6, 2011

- Moved chrono to trunk taking in account the review remarks.
- Documentation revision.

Features:

- Boost_Chrono is now a configurable header-only library version (that also allows the user to choose if the `windows.h` file is included or not).
- Added `clock_string<>` traits.
- Define `chrono-io` for all the clocks.
- Add input of `process_times` representation.

Implementation:

- Use of `detail/win` files to avoid the use of `windows.h` file.
- Completed the `error_code` handling.
- Works now with `BOOST_SYSTEM_NO_DEPRECATED`.

Fixes:

- Fix some warnings.
- Fix original errors on Mac
- Don't fix the link with `boost_system` to static.

Test:

- Added test on process and thread clocks.
- Moved to `lightweight_test.hpp`.
- Able to test multiple configurations.

Doc:

- Removed some not useful parts as the test and the tickets.

Appendix: Rationale

See [N2661 - A Foundation to Sleep On](#) which is very informative and provides motivation for key design decisions. This section contains some extracts from this document.

Why duration needs operator%

This operator is convenient for computing where in a time frame a given duration lies. A motivating example is converting a duration into a "broken-down" time duration such as `hours::minutes::seconds`:

```

class ClockTime
{
    typedef boost::chrono::hours hours;
    typedef boost::chrono::minutes minutes;
    typedef boost::chrono::seconds seconds;
public:
    hours hours_;
    minutes minutes_;
    seconds seconds_;

    template <class Rep, class Period>
    explicit ClockTime(const boost::chrono::duration<Rep, Period>& d)
        : hours_(boost::chrono::duration_cast<hours>(d)),
          minutes_(boost::chrono::duration_cast<minutes>(d % hours(1))),
          seconds_(boost::chrono::duration_cast<seconds>(d % minutes(1)))
        {}
};

```

Appendix: Implementation Notes

Which APIs have been chosen to implement each clock on each platform?

The following table presents a resume of which API is used for each clock on each platform

Table 3. Clock API correspondence

| Clock | Windows Platform | Posix Platform | Mac Platform |
|---------------------------------------|---|---|---|
| <code>system_clock</code> | GetSystemTimeAsFileTime | <code>clock_gettime(CLOCK_REALTIME)</code> | <code>gettimeofday</code> |
| <code>steady_clock</code> | QueryPerformanceCounter and QueryPerformanceFrequency | <code>clock_gettime(CLOCK_STEADY)</code> | <code>mach_timebase_info, mach_absolute_time</code> |
| <code>process_real_cpu_clock</code> | GetProcessTimes | <code>times</code> | <code>times</code> |
| <code>process_system_cpu_clock</code> | GetProcessTimes | <code>times</code> | <code>times</code> |
| <code>process_user_cpu_clock</code> | GetProcessTimes | <code>times</code> | <code>times</code> |
| <code>process_cpu_clock</code> | GetProcessTimes | <code>times</code> | <code>times</code> |
| <code>thread_clock</code> | GetThreadTimes | <code>clock_gettime(pthread_getcpuclockid)</code> | <code>clock_gettime(pthread_getcpuclockid)</code> |

Appendix: FAQ

Why does `process_cpu_clock` sometimes give more cpu seconds than real seconds?

Ask your operating system supplier. The results have been inspected with a debugger, and both for Windows and Linux, that's what the OS appears to be reporting at times.

Are integer overflows in the duration arithmetic detected and reported?

Boost.Ratio avoids all kind of overflow that could result of arithmetic operation and that can be simplified. The typedefs durations don't detect overflow. You will need a duration representation that handles overflow.

Which clocks should be used to benchmarking?

Each clock has his own features. It depends on what do you need to benchmark. Most of the time, you could be interested in using a thread clock, but if you need to measure code subject to synchronization a process clock would be better. If you have a multi-process application, a system-wide clock could be needed.

Which clocks should be used for watching?

For trace purposes, it is probably best to use a system-wide clock.

Appendix: Acknowledgements

The library's code was derived from Howard Hinnant's `time2_demo` prototype. Many thanks to Howard for making his code available under the Boost license. The original code was modified by Beman Dawes to conform to Boost conventions.

`time2_demo` contained this comment:

Much thanks to Andrei Alexandrescu, Walter Brown, Peter Dimov, Jeff Garland, Terry Golubiewski, Daniel Krugler, Anthony Williams.

The file `<boost/chrono_io.hpp>` has been adapted from the experimental header `<chrono_io>` from Howard Hinnant. Thanks for all Howard.

Howard Hinnant, who is the real author of the library, has provided valuable feedback and suggestions during the development of the library. In particular, The `chrono_io_io.hpp` source has been adapted from the experimental header `<chrono_io>` from Howard Hinnant.

The acceptance review of `Boost.Ratio` took place between November 5th and 15th 2010. Many thanks to Anthony Williams, the review manager, and to all the reviewers: David Deakins, John Bytheway, Roland Bock and Paul A. Bristow.

Thanks to Ronald Bock, Andrew Chinoff, Paul A. Bristow and John Bytheway for his help polishing the documentation.

Thanks to Tom Tan for reporting some compiler issues with MSVC V10 beta and MinGW-gcc-4.4.0 and for the many pushing for an homogeneous `process_cpu_clock` clock.

Thanks to Ronald Bock for reporting Valgind issues and for the many suggestions he made concerning the documentation.

Appendix: Future plans

For later releases

- Include Stopwatches.
- Add User defined literals for some durations.
- Include `chrono::date` as defined by Howard Hinnant [here](#).